



PARLCARD306 | 3-PHASE MODULAR UPS PARALLEL CONTROL CABLE

Synchronizes parallel UPS systems for increased capacity or N + N redundancy

CyberPower PARLCARD306 3-Phase Modular UPS Hardware Parallel Cables connect UPS systems for capacity or redundancy (N+N) and will keep your UPS systems in-sync. Includes a One-Year Limited Warranty.

For CyberPower Smart App Online 3-Phase Modular UPS systems SM020KAMFA, SM040KAMFA.



SPECIFICATIONS

PHYSICAL

Color Black

Mounting Hardware No

PHYSICAL DIMENSIONS

Physical Dimensions - Length (cm) 19.68 cm

Physical Dimensions - Length (in.) 7.75 in.

Weight (kg) 0.32 kg

Weight (lb) 0.7 lbs.

SHIPPING DIMENSIONS

Shipping Dimensions - WxHxD (cm) 37.59 x 6.6 x 9.91 cm

Shipping Dimensions - WxHxD (in) 14.8 x 2.6 x 3.9 in.

Weight (kg) 0.41 kg

Weight (lb) 0.9 lbs.

ENVIRONMENTAL

Operating Elevation 0 - 10,000 ft (0 - 3,048 m)

Operating Elevation Note At $\leq 1,000$ m above sea level, de-rate power by 1% per 100m between 1,000m and 3,048m

Operating Relative Humidity 0 - 95 % (non-condensing)

Operating Temperature 32 - 104°F (0 - 40°C)

Operating Temperature Note Battery life is halved for every 50°F (10°C) increase above 68°F (20°C)

Storage Battery Temperature Note Optimum battery storage between 5 - 68°F (-15 - 20°C)

Storage Relative Humidity 0 - 95% (non-condensing)

Storage Temperature -4 - 158 °F (-20 - 70 °C)

CERTIFICATIONS

Environmental RoHS Compliant

Safety UL2464

WARRANTY

Product Warranty One-Year Limited Warranty