



PDU30BVHVT20F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

The CyberPower 20-outlet (20 Front) OU vertical rack mount basic power distribution unit (PDU30BVHVT20F) provides 200/230V 30A output. It distributes power to 20 IEC-320 (4-C19 and 16-C13) receptacles from a single NEMA L6-30P twist lock plug, with unfiltered electrical pass-through.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It supports vertical, horizontal and wall mount installation, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

Typical Applications

- Servers
- Network Devices
- Telecom Equipment

Features

- Basic PDU
- Switch-Free Design
- Industrial-Grade Metal Housing
- Lifetime Warranty

PDU30BVHVT20F Basic PDU

Engineered to distribute UPS, generator or utility AC power to equipment.

| GENERAL | |
|------------------------------|---|
| Type | Basic PDU |
| Phase | Single Phase |
| INPUT | |
| Voltage | 200V/230V |
| Frequency | 50Hz/60Hz |
| Maximum Input Current | 30A (Derated to 24A) |
| Plug Type | NEMA L6-30P |
| Plug Style | Straight, Twist Lock |
| Cord Length | 10' |
| OUTPUT | |
| Nominal Output Voltage | 200V/230V |
| Outlets - Total | 20 |
| Outlet Type | IEC-320 C19/C13 |
| Outlets - Front | 4(C19)+16(C13) |
| Outlets - Rear | 0 |
| Overload Protection | 16A x 2 |
| PHYSICAL | |
| Rack Size | 0U |
| Form Factors Supported | Vertical Rackmount, Wallmount |
| Cord Retention Organizers | Yes |
| External Site Ground Pin | Yes |
| Adjustable Mounting Brackets | 3 sets (L-short, L-long, Flat) |
| Dimensions (WxHxD) (in.) | 1.75 x 36 x 1.5 |
| Weight (lbs.) | 8.0 |
| ENVIRONMENTAL | |
| Operating Temperature | 32°F to 95°F / 0°C to 35°C |
| Operating Relative Humidity | 0% - 95% non-condensing |
| Storage Temperature | 5°F to 113°F / -15°C to 45°C |
| Maximum Operating Elevation | 10,000 ft / 3,000 m |
| Maximum Storage Elevation | 50,000 ft / 15,000 m |
| CERTIFICATIONS | |
| Safety | UL60950_1 certified by ETL (USA), CSA C22.2 (Canada) |
| Environmental | RoHS Compliant |
| WARRANTY | |
| Product Warranty | Lifetime |