



# Scotch® High Performance Fine Line Tape 4740

Expertly crafted for Automotive OEM two-tone paint applications

**Precise.  
Conformable.  
Strong.**

This versatile tape is designed to withstand high temperatures to ensure a consistent performance in the most demanding environments.

Designed to remove cleanly with no edge residue or ghosting, this tape delivers professional results with our best clean removal performance yet.

Additionally, its excellent conformability allows it to adhere seamlessly, for precise and reliable application.




## High Temperature Resistance

For temperatures as high as 160° (320° F) for up to 30 minutes.  
And 180° (356° F) for 10 minutes.



## Excellent Conformability

Designed to conform to intricate surfaces and sharp curves.



## Clean Removal

Our best clean removal yet.  
Designed to remove cleanly with no edge residue or ghosting.



## Solventless Adhesive

The pressure-sensitive, solventless adhesive adheres to complex surfaces and resists lifting, even on irregular or depressed areas.



# Scotch® High Performance Fine Line Tape 4740

For high temperature performance, excellent conformability and consistent clean removal.

**Professional results + High performance**

| Product   | Material IDs | Width   | Length | Rolls/Case |
|---|--------------|---------|--------|------------|
| <b>Scotch® High Performance Fine Line Tape 4740</b> | 7100381071   | 12 mm   | 50 m   | 100        |
|   | 7100381874   | 19 mm   | 50 m   | 64         |
|   | 7100382014   | 25 mm   | 50 m   | 48         |
|   | 7100381072   | 30 mm   | 50 m   | 40         |
|   | 7100381170   | 1200 mm | 50 m   | 1          |

## Specifications

|  |   |   |   |
|--|---|---|---|
|  <b>Total Thickness</b><br> 5.2 mil (0.13mm) |  <b>Adhesion to Steel</b><br> 21 oz/in (2.3 N/cm) |  <b>Tensile Strength</b><br>24.4 lb/in (42.7 N/cm) |  <b>Elongation at Break</b><br> 1353% |
|--|---|---|---|



### Engineered to Paint with Precision

3M™ Engineered Industrial Tape provides the clean removal and crisp lines you need.



**3M Industrial Adhesives and Tapes Division**  
3M Center, Building 223  
St. Paul, MN 55144-1000 USA

**Phone** 800-362-3550  
**Fax** 877-369-2923

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for proper evaluation (including, but not limited to, fitness for purpose and suitability of application), selection, and use of 3M products. Safety products should always be selected and used in accordance with all applicable regulations and standards (e.g., OSHA, ANSI, and others), after conducting a proper hazard assessment. Failure to properly evaluate, select, and use a 3M product may result in injury, sickness, death, and/or harm to property. Dispose of used atomizing hacks, residual paint/coatings, used containers/materials, and PPS in accordance with local regulations.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product specification at the time 3M ships the product, 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, CUSTOM, OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

3M is a trademark of 3M Company. Please recycle. Printed in USA.  
© 3M 2025. All rights reserved.