



Coverage SqFt/Gallon	1500-2000
Dry Time (hrs.)	1
Sheen	Gloss
UL Certified	Yes

### Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

### Directions for Use

**PREPARATION:** Strip other finishes from the floor with Hillyard Devastator®, Super Strip, or Power-Strip following label directions. Use floor machine with black pad or brush (do not use abrasive pads on tile containing asbestos). Remove stripping solution with a wet vacuum. Heavy rinse with Hillyard Nutra-Rinse® mixed 4 oz. per gallon of water and pick up with the wet vacuum. Damp mop all flooring twice with clean, cool water. Allow the floor to dry. **APPLICATION:** On newer floors, a sealer is not necessary. Apply a minimum of 5 coats of Expediter with a flat mop applicator or clean synthetic mop. Allow each coat to dry a minimum 50 minutes before applying the next. If a sealer is not used and the floor is porous, apply a minimum of 6 coats of Expediter. **NOTE:** Allow for longer dry time between coats of finish if the humidity is above 80% or the floor temperature is below 60°F (16°C). **MAINTENANCE:** Use a Hillyard Super Hil-Tone® treated dust mop daily to remove loose dirt and grit. Damp mop or autoscrub as scheduled with Hillyard Super Shine-All®, Top Clean®, or Arsenal® Heavy Duty Floor Cleaner. After the floor has been cleaned, gloss may be restored by spray buffing with Hillyard Hil-Glo®, or damp mop with Hillyard Restorer® according to label directions. Scrub and recoat as scheduled with 2 coats of Expediter. **FLOOR PAD**  
**RECOMMENDATIONS:** **Strip** black; **Spray Buff** red followed by white; **Scrub and Recoat** blue or green; **Autoscrubbing** red. **NOTICE:** Do not use an ammoniated cleaner for daily care. If the floor is extremely porous, seal with Hillyard Hil-Tex+® or

A high solids floor polish modified with urethane for outstanding scuff resistance, gloss, and durability. Expediter provides exceptional resistance to black heel marks, scuffing, and scratching. Daily and weekly maintenance is simple with Expediter. It is formulated to take heavy traffic and still come out shining. Daily dust mopping and occasional damp mopping or spray buffing keeps your floors looking beautiful.

### Features & Benefits

Dries to a clear, beautiful high gloss without buffing

Urethane fortified for excellent durability

Designed for limited maintenance floor care programs

### Item Number & Unit of Measure

Item Number	HIL0053206
Unit of Measure	1 gal Bottle

### Specifications

Color	White
Appearance	Milky Emulsion
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	RTU
PH	7.50 - 8.50
Non-Volatile Matter	17.50 - 18.50%
Solids Content	18

## Expediter® Floor Finish (continued)

---



Terrazzine before applying Expediter. If stains are a problem, seal with Strong Guard®. Keep container closed when not in use. Do not pour unused finish or seal back into the original container.