



## WALL FIXTURE INSTALLATION INSTRUCTION

1. Before beginning the installation, carefully unpack and identify all parts, referring to the illustration (see FIGURE 1).
2. Turn the electrical power to the installation point **OFF**.
3. Fasten the CROSSBAR to the OUTLET BOX, using (2) OUTLET BOX SCREWS (not included).
4. Make the wiring connections: Using the GROUND SCREW, connect the HOUSE GROUND WIRE and the FIXTURE GROUND WIRE to the CROSSBAR. Using wire connectors (not supplied) connect the HOUSE WHITE WIRE to the FIXTURE WHITE (or RIBBED) WIRE(S); connect the HOUSE BLACK (or RED) WIRE to the FIXTURE BLACK (or SMOOTH) WIRE(S). Make sure that there are no exposed wires or strands and wrap all connections with approved electrical tape.
5. Carefully tuck all wiring into the OUTLET BOX, and position the FIXTURE BASE over the MOUNTING STUDS on the CROSSBAR. Pass the studs through the (2) MOUNTING HOLES on the FIXTURE BASE and secure to wall with (2) LOCK BALLS.
6. Install bulb. (See fixture markings and/or labels for maximum wattage.) Complete installation of any glass necessary.
7. Restore electrical power to the installation.

FIGURE 1.

