



Safety

See safety datasheet (if applicable) and product label for safety information, handling and proper use.

Directions for Use

Dilute product according to label directions. Allow solution to penetrate soil for 5 minutes. Rinse thoroughly with clean water. Can use with brush cleaning. Light cleaning: Dilute 1:64 (2 oz. per gallon of water). Medium Cleaning: Dilute 1:32 (4 oz. per gallon of water). Heavy Cleaning: Dilute 1:20 (6 oz. per gallon of water).

An industrial vehicle wash specifically formulated for use with high pressure cleaning equipment. CV Pro removes most exhaust deposits, road film, and bug residue from painted vehicle surfaces, cleans aluminum siding, painted wood, and painted metal surfaces. CV Pro rinses residue- free and water will bead up for that "just waxed look". For use with hot or cold water, CV-Pro is heat stable to 180° Fahrenheit, and contains no solvents, free acids or phosphates.

Features & Benefits

Rinses residue free.

Effective in hot or cold water.

Contains no solvents, free acids or phosphates.

Item Number & Unit of Measure

Item Number	HIL0047907
Unit of Measure	5 gal Pail

Specifications

Color	Red
Appearance	Clear
Fragrance	Non-Objectionable
Formula Type	Liquid
Dilution Ratio	1:20 - 1:64
PH	11.50 - 12.50
Non-Volatile Matter	4.50 - 6.50%