

### OL3000RMXL2U

For mission-critical enterprise applications requiring maximum power protection.



#### KEY FEATURES:

- 3000VA / 2100W Pure Sine Wave
- Double Conversion Online Topology
- 2U Rack Mount / Tower convertible
- SNMP/HTTP remote management
- 5 Outlets
- USB, Serial, and EPO ports
- EMI/RFI filters
- External Battery Pack option
- PowerPanel® Business Edition

#### Runtimes:

6 Minutes at Full-load  
12 Minutes at Half-load

#### DESIGNED FOR:

- Corporate Data Centers
- Department Servers
- Network Appliances
- Complex Security Systems
- PBX and VoIP installations

The Smart App Online units are designed for those applications requiring maximum power protection; with its double conversion design and zero transfer time, it provides clean and seamless pure sine wave power to the critical loads.

The front LED panel displays all major UPS power information, which significantly increase manageability and ease of control. The Smart App Online units offer three choices for communication, including: RS232, RS232-USB, or SNMP/AS400 card. Extended runtime (XL) battery packs can also be added to these units which boost runtimes, in event of a power outage. Input and output EMI filters increase the immunity of the load to disturbances and surges, even in bypass.

The Smart App Online unit also incorporates microprocessor-based fully digital control, and includes PowerPanel® Business Edition, which gives the user unsurpassed control and flexibility over power management options. The OL3000RMXL2U comes with six (6) 12V/9Ah batteries (72V), and five (5) power receptacles (4 x NEMA 5-20R, 1 x NEMA L5-30R).

#### FEATURES & BENEFITS:

**Pure Sine Wave:** The UPS generates energy that is identical to or cleaner than the utility company's power grid. Benefits include: low total harmonic distortion, minimal electrical noise, optimal line clarity.

**Microprocessor-based Digital Control:** Digital routing is maintained through a network of integrated circuitry and discrete values that are used for internal system processing, which significantly increases efficiency and responsiveness.

**Extended Runtime (XL) Battery Expansion:** The XL battery expansion port allows for the addition of multiple battery packs to increase back-up time.

**RM/T Configuration:** The OL units can be set up as either a Tower, or Rackmount (2U) configuration.

**Dual PC Support:** The unit has two (2) communication ports that allow the user full control of dual PCs, or servers.

**LED Front Panel:** Immediate vital system information: load capacity, battery capacity, fault status, and bypass status.

**Metal Housing:** Rigid metal construction allows for placement in areas with a demanding environment.

**Audible Alarms:** Audible tones identify when the unit is running off battery power, unit overloads, and low battery.

**Resettable Circuit Breaker:** Convenient unit reset switch in case of an overload.

**PowerPanel® Business Edition:** Manage the power for all the servers and computers electrically connected to a UPS on a network. PowerPanel® Business Edition also has application/OS shutdown, event logging (power, surge, voltage variations), hibernation mode, internal reports and analysis, and remote management.

**Technical Support:** CyberPower assists users with any product, installation, or warranty concerns—free of charge.

**3-Year Warranty:** Stringent manufacturing processes and innovative product design enables CyberPower to offer one of the strongest warranties in our industry. CyberPower will repair or replace damaged units within three (3) years of purchase date.

**ISO & Safety Certifications:** All CyberPower manufacturing facilities are state-of-the-art and ISO-9001 Quality Tested. Our products are certified by the FCC, cUL, and UL.

**Windows Compatibility:** Our PowerPanel® power management software has been fully tested and is compatible with Windows 2000, 2003, XP 32/64, Vista 32/64, 7, and Server 2008.



CyberPower's patented GreenPower UPS™ technology reduces UPS energy costs up to 75%! Save money and help reduce carbon emissions.

### OL3000RML2U SPECIFICATIONS

#### GENERAL

UPS Topology	Online (Double Conversion)
--------------	----------------------------

#### INPUT

Voltage	60Vac - 142Vac
---------	----------------

Phase	Single
-------	--------

Frequency	40Hz - 70Hz
-----------	-------------

Plug Type	NEMA L5-30P
-----------	-------------

Plug Style	Straight
------------	----------

Cord Length	6'
-------------	----

#### OUTPUT

VA	3000
----	------

Watts	2100
-------	------

On Battery Voltage	110Vac / 120Vac / 127Vac +/- 3%
--------------------	---------------------------------

On Battery Frequency	50/60Hz +/- .5%
----------------------	-----------------

On Battery Waveform	Sine Wave
---------------------	-----------

Outlets - Total	5
-----------------	---

Outlet Type	NEMA 5-20R, NEMA L5-30R
-------------	-------------------------

Outlets - Battery & Surge Protected	5
-------------------------------------	---

Overload Protection	Internal circuitry limiting / circuit breaker
---------------------	---

Transfer Time	Zero transfer time
---------------	--------------------

#### BATTERY

Runtime at Half Load (min.)	12
-----------------------------	----

Runtime at Full Load (min.)	6
-----------------------------	---

Battery Type	Sealed lead acid
--------------	------------------

Battery Size	12V/9AH
--------------	---------

User Replaceable	Yes
------------------	-----

Typical Recharge Time	3 Hours to 90%
-----------------------	----------------

Replacement Battery	YUASA - REW45-12
---------------------	------------------

Battery Quantity	6
------------------	---

#### SURGE PROTECTION & FILTERING

Surge Suppression	736 Joules
-------------------	------------

#### MANAGEMENT & COMMUNICATIONS

USB Port	Yes
----------	-----

HID Compliant USB Port	Yes
------------------------	-----

Serial Port	Yes (1x)
-------------	----------

LED Indicators	Power on, battery, inverter, bypass, critical outlet 1, critical outlet 2, wiring fault, battery alarm, overload, load
----------------	--

Audible Alarms	Input fault, battery fault, low battery, overload
----------------	---

Software	PowerPanel® Business Edition
----------	------------------------------

SNMP / HTTP Remote Monitoring	Yes, with optional RMCARD301
-------------------------------	------------------------------

AS400 Management	Yes, with optional COMMCARD300
------------------	--------------------------------

Emergency Power Off (EPO) Port	Yes
--------------------------------	-----

#### PHYSICAL

Dimensions (WxHxD)	17.25" x 3.5" x 26"
--------------------	---------------------

Rack Size	2U
-----------	----

Weight (lbs.)	72
---------------	----

#### CERTIFICATIONS

Certifications	UL1778, cUL, FCC DOC Class B
----------------	------------------------------

RoHS Compliant	RoHS Compliant
----------------	----------------

#### WARRANTY

Product Warranty	3 Years Limited
------------------	-----------------

Connected Equipment Guarantee	Lifetime
-------------------------------	----------

CEG Amount	\$400,000
------------	-----------

