



The SS-801 Microphone

Add Sound to Your Security System

Product Overview

The SS-801 is an omni-directional mic level microphone for indoor use. When paired with select IP cameras the microphone does not require external power.

The SS-801 picks up sounds from approximately 12 feet away in all directions. Its enclosure surface mounts onto ceilings or walls with no exposed screws or connectors.

Installation Instructions

- 1) Using 18/2 or 22/2 AWG shielded cable, connect the SS-801 positive and negative terminals to the camera's audio inputs for signal and ground, respectively.
- 2) Configure the audio settings in your IP camera to enable audio.



The SS-801 Microphone is proudly Made in the USA.

Common Uses:

The SS-801 is commonly paired with IP cameras supporting "mic in" audio and installed in:

- Interview Rooms
- Reception Areas
- Retail Point of Sale
- Convenience Stores
- Quick Service Restaurants

In these applications, audio is frequently used for evidence collection, alarm verification, and to ensure service procedures are followed.

Technical Specifications

Sensitivity	-44db ± 2
Frequency Response	50Hz - 8kHz
Supply Voltage	1.5V- 10V
Current Drain	0.8mA
Output Impedance	2.2KΩ
SNR	60 dB
Operating Temp	-25° - 70° C
Dimensions	3 1/8" D x 1" H
Weight	8 oz
Enclosure Material	Polycarbonate