



COMMCARD300 Remote Management Card

Internal communication/interface card

This communication card provides administrators with means of transmitting UPS data to a PLC management system or an interface utilizing a DB9 connection.

The COMMCARD300 can also be configured as an EPO (Emergency Power Off) interface.

A Three-Year Warranty ensures that this network management card has passed our highest quality standards in design, assembly, material and workmanship.

Features

- Device Type: Remote management adapter
- Form Factor: Plug-in module
- Ports: RS-232
- Connectivity Technology: Wired
- Data Link Protocol: RS-232
- Interfaces: 1 x RS-232 - 9 pin D-Sub (DB-9)
- Quick Installation User Guide

COMMCARD300 Remote Management Card

Internal communication/interface card

GENERAL	
Type	Network Management Card
COMMUNICATION	
Protocols	TCP/IP, UDP, SNMP/HTTP, BOOTP and DHCP
Network Connection	Serial
PHYSICAL	
Dimensions (WxHxD) (in.)	2.71 x 1.49 x 5.39
Dimensions (WxHxD) (mm.)	69 x 38 x 137
Weight (lbs.)	0.2
Weight (kg.)	0.09
SHIPPING DIMENSIONS	
Dimensions (WxHxD) (in.)	5.50 x 3.25 x 9.50
Dimensions (WxHxD) (mm.)	175 x 56 x 166
Weight (lbs.)	0.60
Weight (kg.)	0.27
ENVIRONMENTAL	
Operating Temperature	32°F to 104°F / 0°C to 40°C
Operating Humidity	0% - 90% non-condensing
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	14°F to 122°F / -10°C to 50°C
Storage Relative Humidity	0% - 95% non condensing
Storage Elevation	0-50000 feet (0-15000 meters)
COMPATIBILITY	
UPS Models	OL1000RML2U, OL1500RML2U, OL2000RML2U, OL3000RML2U
CERTIFICATIONS	
Safety	FCC Class A, CE
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	3 Years Limited