

SECTION 1: Identification and Company Details

Product Name: Universal⁺ Resilient Adhesive

Product Code: PS399

Manufacturer/ Supplier:Capitol® Flooring ProductsAddress:300 Cross Plains Blvd.

Dalton, GA 30721

Emergency Phone: (800) 424-9300 (24-hour Response / CHEMTREC)

Product Information: (706) 277-5294
Recommended Use: Adhesive

SECTION 2: Hazard(s) Identification

Classification of the

substance or mixture: This product is not classified as hazardous under GHS criteria.

SECTION 3: Composition / Information on Ingredients

Weight % CAS #

Distillates, petroleum, solvent-dewaxed heavy paraffinic 0.20% 64742-65-0

SECTION 4: First-Aid Measures

Inhalation: Move victim to fresh air. Consult physician if necessary.

Skin Contact: Wash with soap and water. Remove contaminated clothing. Consult physician if necessary. Flush with copious amounts of water for at least 15 minutes. Consult physician if necessary.

Ingestion: Do not induce vomiting. Wash mouth with water. Consult physician.

Note to Physician: Eyes: Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation.

Skin: Treat symptomatically as for contact dermatitis or thermal burns. If burned, treat as thermal burn.

Ingestion: Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the

irritating nature of this compound.

Respiratory: Treatment is essentially symptomatic. Remove individual with symptoms from exposure and assist in

breathing if necessary.

SECTION 5: Fire-Fighting Measures

Flash Point: 0°C (32 F)

Extinguishing Media: This product is not flammable. Use fire- extinguishing media appropriate for surrounding materials.

Hazardous Combustion Products: No particular hazards known.

Protection of Firefighters Fire fighters should be equipped with self-contained breathing apparatus and turnout gear.

SECTION 6: Accidental Release Measures

Personal Precautions: Use protective gloves, goggles and suitable protective clothing. **Environmental Precautions:** Do not allow product to get into drains, soil, or surface water.

Methods of Clean-up: Small spillages: Absorb with sand or other inert absorbent. Large spillages: Dam and absorb. Collect spillage in

containers, seal securely and deliver for disposal according to local regulations. Wear necessary protective

equipment.

Handling Precautions: Provide good ventilation. Do not use in confined spaces without adequate ventilation and/or respirator. Avoid contact

with skin and eyes. Do not eat, drink or smoke when using the product.

Storage: Keep separate from food, feedstuffs, fertilizers and other sensitive material. Store in closed original container at

temperatures between 5°Cand 30°C/40°F and 86°F. Protect from freezing and direct sunlight.

SECTION 8: Exposure Control / Personal Protection

Exposure Guidelines: Not determined

Engineering Controls: Provide adequate ventilation.

Personal Protective Equipment:

Skin Protection - Permeation resistant gloves (butyl rubber, nitrile rubber, PVC or polyvinyl alcohol). **Eye/Face Protection** - Glasses with side shields, chemical splash goggles and/or face shield.

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Distillates, petroleum, solvent- dewaxed heavy paraffinic, 64742-65-0	Not established	Not established	Not established

SECTION 9: Physical and Chemical Properties

Appearance: Off white paste Vapor Density: Not Determined

Odor: Very mild acrylic/ resinous odor

Relative Density: 1.00

Odor Threshold: Not available Solubility(ies): Not available

pH: 8.3

Partition Coefficient: n-octanol/water; Not determined

Melting Point: Not determined Freezing Point: Not determined Auto-ignition Temperature: Not determined

Flash Point: Non- flammable, 0°C (32 F)

Decomposition Temperature: Not determined
Evaporation Rate: Not determined
Viscosity: Not determined
Flammability (Solid/Gas): Not applicable
Upper/Lower Flammability: Not determined

VOC Content: 0 g/L

Vapor Pressure: Not Determined Boiling Point: 100°C/ 212°F

Chemical Stability: Stable under normal temperature conditions and recommended use.

Conditions to Avoid: Excessive heat, direct sunlight and/or frost.

Materials to Avoid: Water, amines, strong bases, and alcohols.

Acute toxicity:

Ingestion: Not determined Inhalation: Not determined Skin Contact: Not determined.

<u>CAS Number</u> %Weight 64742-65-0 0.20%

Distillates, petroleum, solvent-dewaxed heavy paraffinic 64742-65-0 0.2

SECTION 12: Ecological Information

Mobility and Bioaccumulation Potential: Not determined

Degradation: Not determined
Aquatic Toxicity: Not determined
LC50 – 24 hour (Static): Not determined

Ecotoxicity:

Distillates, petroleum, 96 Hr LC50 Pimephales promelas: 35 mg/L; 96 Hr LC50 Pimephales promelas>10000 mg/L

Solvent-dewaxed heavy paraffinic

SECTION 13: Disposal Considerations

Disposal: Dispose of waste and residues in accordance with local authority requirements. Incineration is the preferred method of

disposal.

Wastes or Residues: Same as above.

SECTION 14: Transport Information

Road: DOT Proper Shipping Name: Non-Regulated

DOT Packing Group: N/A

DOT Label: N/A UN Number: N/A

Ocean: Proper Shipping Name: Non-Regulated

Sea - IMO/IMDG Class: N/A

UN Number: N/A Label: N/A

Packing Group: N/A
Marine Pollutant: N/A

EMS: N/A

Air: Proper Shipping Name: Non-Regulated

Air - ICAO/IATA Class: N/A

UN Number: N/A Label: N/A Sub Class: N/A Packing Group: N/A Pack Instr. Passenger: N/A Pack Instr. Cargo: N/A

SECTION 15: Regulatory Information

Status on Substance Lists: The concentrations shown in this document are maximum levels (weight %) to be used for regulations.

TSCA: The components of this product are contained on the chemical substance inventory list.

IARC: Not carcinogenic

OSHA PEL's None

Federal EPA: Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA): Requires

notification of the national response center of release of quantities of hazardous substances equal to or greater than the reportable quantities (RQ's) in 40 CFR 302.4. Components present in this product at level which could

require reporting under the statute are:

Chemical NameCAS Number% by WeightRQNoneNoneNoneNone

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III: Sections 301-304 require emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQ) in 40 CFR 355. Components present in this product at level which could require reporting under this statue are:

Chemical NameCAS Number% by WeightRQNoneNoneNoneNone

Section 311-312 require products be reviewed and applicable EPA Hazard Definitions be identified and

made known- None

NJ RTK None

Pennsylvania RTK

None

SARA 302 Extremely Hazardous Substances

None

Massachusetts RTK

None

EPA Hazard Classifications:

AcuteChronicFirePressureReactiveHazardHazardHazardHazardHazardNoNoNoNoNo

Section 313 requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313). This information must be included in all SDSs that are distributed for this material. Components present

in this product at level which could require reporting under the statute are: None

Canada DSL: All components are on the DSL list or exempt.

California Proposition 65: Does not contain any listed chemical to the best of our knowledge.

SECTION 16: Other Information

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200).

HMIS RATING: HEALTH-1, FLAMMABILITY-0, REACTIVITY-0, PERSONAL PROTECTION- B.

Prepared by: Capitol® Flooring Products' Product Safety & Regulatory Compliance Group, (706) 277-5294

The information herein is given in good faith, but no warranty expressed or implied is made. Capitol urges users of this product to evaluate its suitability and compliance with local regulations as Capitol cannot foresee the final use of the product, nor the final location of usage.

Date of issue: 04/21/23