

# LED Replacement Lamps

## Decorative Lamps

Project Name \_\_\_\_\_

Date \_\_\_\_\_ Type \_\_\_\_\_

Notes \_\_\_\_\_

Current's LED Decorative Lamps now use a design-inspired filament to cast light more similar to traditional incandescent candles and globes. This creates better light distribution and adds more brilliance to decorative fixtures where the lamp is visible, such as chandeliers, pendants, and sconces.



### PERFORMANCE HIGHLIGHTS:

#### CANDLES

**Light Output Range:** 200-500 Lumens

**CRI:** 80

**CCT:** 2700K

**Input Voltage:** 120

**Efficiency:** up to 100 LPW

**Wattage:** 2.5W to 5W

**Life:** 15,000 hours L70

**Temperature Rating:** -20°C to 40°C

**Rating:** Damp

**Dimmable:** Dims from 100% to 10%

#### GLOBES

**Light Output Range:** 250-500 Lumens

**CRI:** 80

**CCT:** 2700K

**Input Voltage:** 120

**Efficiency:** up to 100 LPW

**Wattage:** 2.8W to 5W

**Life:** 15,000 hours L70

**Temperature Rating:** -20°C to 40°C

**Rating:** Damp

**Dimmable:** Dims from 100% to 10%

### FEATURES:

- Candles have “sparkle” similar to incandescent
- Halogen-like color
- Lasts 15X longer than incandescent/halogen (1,000 hrs)
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

### BENEFITS:

- **Energy + Cost Savings**  
For example, using only 6.5 watts of energy, saves over \$88 in energy costs over the rated life of a lamp versus a standard 60 watt incandescent lamp based on \$0.11 per kWh and provides similar light output (550 vs 650 lumens)
- Uses 87% Less energy than incandescent
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

### LEARN MORE:

To learn more about saving money and energy, go to

[www.gecurrent.com](http://www.gecurrent.com).

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

### LIMITED WARRANTY

3 Years

# LED Replacement Lamps

## Decorative Lamps

### Spec Table

Project Name \_\_\_\_\_

Date \_\_\_\_\_ Type \_\_\_\_\_

Notes \_\_\_\_\_

Bulb Type	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Finish	PC per Pack Unit
<b>LED Replacement Lamps for Decorative Lamps</b>																	
CA	E12	2.5	93142792	LED3DFCAC-C	120	12	4.52	200	2700K	80	25W	15,000	Yes	★	Damp	Clear	2 pk
CA	E12	2.5	93142793	LED3DFCAC-W	120	12	4.52	200	2700K	80	25W	15,000	Yes	★	Damp	White	2 pk
CA	E26	2.5	93142804	LED3DFCAM-C	120	12	4.37	200	2700K	80	25W	15,000	Yes	★	Damp	Clear	2 pk
CA	E26	2.5	93142808	LED3DFCAM-W	120	12	4.37	200	2700K	80	25W	15,000	Yes	★	Damp	White	2 pk
G25	E26	2.8	93142805	LED3DFG25-C	120	12	4.64	250	2700K	80	25W	15,000	Yes	★	Damp	Clear	2 pk
G25	E26	2.8	93142807	LED3DFG25-W	120	12	4.64	250	2700K	80	25W	15,000	Yes	★	Damp	White	2 pk
B	E12	3.5	93142794	LED4DFBC-C	120	12	3.89	300	2700K	80	40W	15,000	Yes	★	Damp	Clear	2 pk
B	E12	3.5	93142796	LED4DFBC-W	120	12	3.89	300	2700K	80	40W	15,000	Yes	★	Damp	White	2 pk
B	E26	3.5	93142811	LED4DFBM-C	120	12	3.72	300	2700K	80	40W	15,000	Yes	★	Damp	Clear	2 pk
B	E26	3.5	93142814	LED4DFBM-W	120	12	3.72	300	2700K	80	40W	15,000	Yes	★	Damp	White	2 pk
CA	E12	3.5	93142795	LED4DFCAC-C	120	12	4.52	300	2700K	80	40W	15,000	Yes	★	Damp	Clear	2 pk
CA	E12	3.5	93142797	LED4DFCAC-W	120	12	4.52	300	2700K	80	40W	15,000	Yes	★	Damp	White	2 pk
CA	E26	3.5	93142812	LED4DFCAM-C	120	12	4.37	300	2700K	80	40W	15,000	Yes	★	Damp	Clear	2 pk
CA	E26	3.5	93142815	LED4DFCAM-W	120	12	4.37	300	2700K	80	40W	15,000	Yes	★	Damp	White	2 pk
A15	E26	3.5	93142809	LED4DFA15-C	120	12	3.50	300	2700K	80	40W	15,000	Yes	-	Damp	Clear	2 pk
A15	E26	3.5	93142810	LED4DFA15-W	120	12	3.50	300	2700K	80	40W	15,000	Yes	-	Damp	White	2 pk
G16.5	E12	4	93142798	LED4DFG16C-C	120	12	3.38	350	2700K	80	40W	15,000	Yes	★	Damp	Clear	2 pk
G16.5	E12	4	93142799	LED4DFG16C-W	120	12	3.38	350	2700K	80	40W	15,000	Yes	★	Damp	White	2 pk
G25	E26	4	93142847	LED4DFG25-C	120	12	4.64	350	2700K	80	40W	15,000	Yes	★	Damp	Clear	2 pk
G25	E26	4	93142846	LED4DFG25-W	120	12	4.64	350	2700K	80	40W	15,000	Yes	★	Damp	White	2 pk
B	E12	5	93142802	LED5DFBC-C	120	12	3.89	500	2700K	80	60W	15,000	Yes	★	Damp	Clear	2 pk
B	E12	5	93142803	LED5DFBC-W	120	12	3.89	500	2700K	80	60W	15,000	Yes	★	Damp	White	2 pk
B	E26	5	93142855	LED5DFBM-C	120	12	3.72	500	2700K	80	60W	15,000	Yes	★	Damp	Clear	2 pk
B	E26	5	93142856	LED5DFBM-W	120	12	3.72	500	2700K	80	60W	15,000	Yes	★	Damp	White	2 pk
CA	E12	5	93142800	LED5DFCAC-C	120	12	4.52	500	2700K	80	60W	15,000	Yes	★	Damp	Clear	2 pk
CA	E12	5	93142801	LED5DFCAC-W	120	12	4.52	500	2700K	80	60W	15,000	Yes	★	Damp	White	2 pk
CA	E26	5	93142851	LED5DFCAM-C	120	12	4.37	500	2700K	80	60W	15,000	Yes	★	Damp	Clear	2 pk
CA	E26	5	93142852	LED5DFCAM-W	120	12	4.37	500	2700K	80	60W	15,000	Yes	★	Damp	White	2 pk
G25	E26	5	93142850	LED5DFG25-C	120	12	4.64	500	2700K	80	60W	15,000	Yes	★	Damp	Clear	2 pk
G25	E26	5	93142849	LED5DFG25-W	120	12	4.64	500	2700K	80	60W	15,000	Yes	★	Damp	White	2 pk

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

# UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.



LED  
Globe Lamp



LED  
Globe Lamp



LED  
Globe Lamp



LED  
Globe Lamp



LED  
Candle Lamp



LED  
Candle Lamp



LED  
Candle Lamp