



AC17

LATEX

CARPET SEAM SEALER

1. PRODUCT NAME

Capitol® AC17 Latex Carpet Seam Sealer

2. MANUFACTURER

Capitol® Flooring Products
Dalton, GA 30720
www.capitolflooringproducts.com
866-435-8665

3. DESCRIPTION

Capitol® AC17 Latex Carpet Seam Sealer is developed for use with most types of carpet. Capitol AC17 may also be used to prevent edge unraveling and bubble repair.

FEATURES AND BENEFITS

- Use for seaming carpet, carpet edging, sealing fabric seams and laminating fabric
- Compatible with most carpet backings
- Suitable for indoor use only
- Quick-drying, permanent bond that stays flexible

USES

For seaming carpet edges and preventing edge raveling on: polypropylene, jute, urethane latex, woven, broadloom and unitary carpets.

LIMITATIONS

- For interior use only
- Not recommended for seaming vinyl flooring
- Refer to flooring manufacturer's specific recommendations.
- Do not get sealer on the carpet fibers.
- Ensure adequate ventilation during flooring installation.
- Refer to Safety Data Sheet, www.capitolflooringproducts.com, industry standards, and manufacturer's guidelines and specific recommendations prior to installation for additional information.



AC17

L A T E X

CARPET SEAM SEALER

4. TECHNICAL DATA

Product Type:	Latex Type
Color:	Creamy, off-white liquid
Open Time:	Up to 10 minutes
VOC:	< 1 g/L
Shelf Life:	1 year in unopened container
Storage:	Protect from freezing

5. INSTRUCTION

Prepare or cut the carpet edges according to the manufacturer's recommendations. Edge Sealing (for carpet backings that require edge sealing): Apply adhesive to cover the thickness of the primary and secondary backing without contaminating face yarns on either edge of the seam. Seam sealing: Apply a 1/8" continuous bead of adhesive to the cut edge of one side only to seal both trimmed edges. Ensure the bead thickness is sufficient to cover the primary and secondary backing without contaminating face yarns. Join the edges while the adhesive is still fresh and transferable. Allow seam construction to dry before proceeding with the installation to prevent transfer to the face yarn. Do not expose to heavy traffic for 24 hours.

CLEAN UP: Fresh Adhesive: remove immediately and completely with – warm, soapy water on a clean cloth. Dry Adhesive: use mineral spirits sparingly, with a clean cloth to remove seam sealer. **DO NOT POUR CLEANER DIRECTLY ONTO FLOORING.**

6. AVAILABILITY

Packaging

17-8 8-oz Plastic Bottle 024043260054

17Q-12 1-qt Plastic Bottle 024043260047

7. WARRANTY

Capitol® offers a limited product warranty on this product when installed in accordance with the printed specifications. Ask your sales associate, visit capitolflooringproducts.com or call (866) 435-8665 for a copy of the warranty.

8. MAINTENANCE

Not applicable.

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at 706-277-5294 or visit www.capitolflooringproducts.com.

10. FILING SYSTEM

Division 9