

LED Replacement Lamps

A-Line General Purpose Lamps



Project Name _____

Date _____ Type _____

Notes _____

Current's ENERGY STAR® rated LED A-Line lamps are the perfect low energy, long life replacements for standard incandescent, halogen and CFL lamps. Take advantage of the ENERGY STAR® rating and check for utility rebates in your area.

PERFORMANCE HIGHLIGHTS:

A-Line General Purpose Lamps	
Light Output Range:	400-2155 Lumens
CRI:	80
CCT:	2700K, 3000K, 4000K & 5000K
Input Voltage:	120
Efficiency:	Up to 130 LPW
Wattage:	4W-19W
Life:	15,000 hours L70
Temperature Rating:	-20°C to 40°C
Location Rating:	Damp

LIMITED WARRANTY

3 years

FEATURES:

- Up to 15,000 hours rated life (L70)
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

BENEFITS:

Energy + Cost Savings

- For example, a 60-watt incandescent replacement lamp using 10 watts of energy and producing 800 lumens can save over \$82 in energy costs over the rated life of the lamp vs. a standard 840 lumen, 60-watt incandescent A19 based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

LEARN MORE:

To learn more about saving money and energy, go to

www.gecurrent.com.

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

A-Line Lamps

General Purpose Lamps

Spec Table

Project Name _____

Date _____ Type _____

Notes _____

A-Line Lamps (Dimmable)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty ²	Pack Qty	MOL (in)	Lumens (Initial)	Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	ENERGY STAR [®] Status	Location Rating ³
E26 Base General Purpose A-Line Lamps																
A19	E26	6	93156446	LED6DA19/827/E-4PK	120	24	4	4.3	480	2700	80	40	15,000	Yes	★	Damp, Enclosed
	E26	6	93156447	LED6DA19/830/E-4PK	120	24	4	4.3	480	3000	80	40	15,000	Yes	★	Damp, Enclosed
	E26	6	93156448	LED6DA19/840/E-4PK	120	24	4	4.3	480	4000	80	40	15,000	Yes	★	Damp, Enclosed
	E26	6	93156449	LED6DA19/850/E-4PK	120	24	4	4.3	480	5000	80	40	15,000	Yes	★	Damp, Enclosed
	E26	10	93156450	LED10DA19/827/E-4PK	120	24	4	4.3	800	2700	80	60	15,000	Yes	★	Damp, Enclosed
	E26	10	93156531	LED10DA19/830/E-4PK	120	24	4	4.3	800	3000	80	60	15,000	Yes	★	Damp, Enclosed
	E26	10	93156532	LED10DA19/840/E-4PK	120	24	4	4.3	800	4000	80	60	15,000	Yes	★	Damp, Enclosed
	E26	10	93156533	LED10DA19/850/E-4PK	120	24	4	4.3	800	5000	80	60	15,000	Yes	★	Damp, Enclosed
	E26	12	93156534	LED12DA19/827/E-4PK	120	24	4	4.7	1100	2700	80	75	15,000	Yes	★	Damp, Enclosed
	E26	12	93156535	LED12DA19/830/E-4PK	120	24	4	4.7	1100	3000	80	75	15,000	Yes	★	Damp, Enclosed
	E26	12	93156536	LED12DA19/840/E-4PK	120	24	4	4.7	1100	4000	80	75	15,000	Yes	★	Damp, Enclosed
	E26	12	93156537	LED12DA19/850/E-4PK	120	24	4	4.7	1100	5000	80	75	15,000	Yes	★	Damp, Enclosed
	E26	15	93156538	LED15DA19/827-4PK	120	24	4	4.7	1600	2700	80	100	15,000	Yes	★	Damp
	E26	15	93156539	LED15DA19/830-4PK	120	24	4	4.7	1600	3000	80	100	15,000	Yes	★	Damp
	E26	15	93156540	LED15DA19/840-4PK	120	24	4	4.7	1600	4000	80	100	15,000	Yes	★	Damp
	E26	15	93156541	LED15DA19/850-4PK	120	24	4	4.7	1600	5000	80	100	15,000	Yes	★	Damp

A-Line Lamps (GU24)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty ²	Pack Qty	MOL (in)	Lumens (Initial)	Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	ENERGY STAR [®] Status	Location Rating ³
GU24 Base General Purpose A-Line Lamps																
A19	GU24	10	93156542	LED10DA19/GU24/827/E-4PK	120	24	4	4.2	800	2700	80	60	15,000	Yes	-	Damp, Enclosed
	GU24	15	93156543	LED15DA19/GU24/827-4PK	120	24	4	4.4	1600	2700	80	100	15,000	Yes	-	Damp

A-Line Lamps (3-Way)

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty ²	Pack Qty	MOL (in)	Lumens (Initial)	Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	ENERGY STAR [®] Status	Location Rating ³
3-Way General Purpose A-Line Lamps																
A19	E26d	4/9/13	93156602	LED13A19/30/100/827-4PK	120	24	4	4.7	400/980/1400	2700	80	30/70/100	15,000	-	-	Damp
A21	E26d	5/12/17	93156603	LED17A21/50/150/827-4PK	120	24	4	5.3	650/1500/2155	2700	80	50/100/150	15,000	-	-	Damp

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Case Qty

★ ENERGY STAR[®] status: ENERGY STAR[®] certified. Lamps without a "★" are not ENERGY STAR[®] certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment. When installing outdoors, ensure the socket used is suitably Listed for use in Wet locations and socket gaskets provided by the manufacturer are correctly attached.