

LED Replacement Lamps

Decorative Lamps



Project Name _____

Date _____ Type _____

Notes _____

Current's LED Decorative Lamps now use a design-inspired crown diffuser to cast light more similar to traditional incandescent candles and globes. This creates better light distribution and adds more brilliance to decorative fixtures where the lamp is visible, such as chandeliers, pendants, and sconces.

PERFORMANCE HIGHLIGHTS:

CANDLES

Light Output Range: 200-500 Lumens

CRI: 80

CCT: 2700K & 5000K

Input Voltage: 120

Efficiency: Up to 100 LPW

Wattage: 3.5W/4W/4.2W/5W/7W

Life: 15,000 hours L70

Temperature Rating: -20°C to 40°C

Rating: Damp

Dimmable: Dims from 100% to 10%

GLOBES

Light Output Range: 250-500 Lumens

CRI: 80

CCT: 2700K

Input Voltage: 120

Efficiency: Up to 91 LPW

Wattage: 3.5W/4W/4.5W/5.5W/7W

Life: 15,000 hours L70

Temperature Rating: -20°C to 40°C

Rating: Damp

Dimmable: Dims from 100% to 10%

FEATURES:

- Candles have "sparkle" similar to incandescent
- Halogen-like color
- Lasts 15X longer than incandescent/halogen (1,000 hrs)
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

BENEFITS:

- **Energy + Cost Savings**
For example, using only 6.5 watts of energy, saves over \$88 in energy costs over the rated life of a lamp versus a standard 60 watt incandescent lamp based on \$0.11 per kWh and provides similar light output (550 vs 650 lumens)
- Uses 87% Less energy than incandescent
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

LEARN MORE:

To learn more about saving money and energy, go to

www.gecurrent.com.

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LIMITED WARRANTY

3 Years

LED Replacement Lamps

Decorative Lamps

Spec Table

Project Name _____

Date _____ Type _____

Notes _____

Base Type	Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (In)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	# Location Rating	Additional Information
CANDLES																
CA11	E26	3.5	23179	LED4DBM-AGC-2BT	120	6	4.3	300	2700	80	40	15,000	Yes	★	Damp	All Glass, Clear, 2 pack
	E26	4	21250	LED4DCAM-C3/827	120	6	4.2	300	2700	80	40	15,000	Yes	★	Damp	Clear, Bent tip
	E26	4	23100	LED4DCAM-AGC-2BT	120	6	4.2	300	2700	80	40	15,000	Yes	★	Damp	All glass, Clear, Bent tip, 2 pack
	E26	4.2	92389	LED4DCAM-W3/827	120	6	4.2	300	2700	80	40	15,000	Yes	★	Damp	White, Bent tip
	E26	5	23336	LED5DBM-AGC-2BT	120	6	4.3	500	2700	80	60	15,000	Yes	★	Damp	All Glass, Clear, 2 pack
	E26	7	21251	LED7DCAM-C3/827	120	6	4.8	500	2700	80	60	15,000	Yes	★	Damp	Clear, Bent tip
	E26	7	23270	LED5DCAM-AGC-2BT	120	6	4.8	500	2700	80	60	15,000	Yes	★	Damp	All glass, Clear, Bent tip, 2 pack
	E12	2.5	22560	LED2DBC-AGC-2BT	120	6	4.3	200	2700	80	25	15,000	Yes	★	Damp	All Glass, Clear, 2 pack
	E12	2.5	22521	LED2DCAC-AGC-2BT	120	6	4.2	200	2700	80	25	15,000	Yes	★	Damp	Clear, bent tip
	E12	5	23328	LED5DBC-AGC-2BT	120	6	4.3	500	2700	80	60	15,000	Yes	★	Damp	All Glass, Clear, 2 pack
	E12	3.5	23155	LED4DBC-AGC-2BT	120	6	3.5	300	2700	80	40	15,000	Yes	★	Damp	All Glass, Clear, 2 pack
	E12	3.5	92674	LED4DCAC-AGC-4P	120	6	4.2	300	2700	80	40	15,000	Yes	★	Damp	All Glass, Clear, 4 pack
	E12	4	21231	LED4DCAC-C3/827	120	6	4.3	300	2700	80	40	15,000	Yes	★	Damp	Clear, Bent tip
	E12	4	23090	LED4DCAC-AGC-2BT	120	6	4.3	300	2700	80	40	15,000	Yes	★	Damp	All glass, Clear, Bent tip, 2 pack
E12	4	69109	LED4DCAC-C3/850	120	6	4.3	300	5000	80	40	15,000	Yes	★	Damp	Clear, Bent tip	
E12	7	21233	LED7DCAC-C3/827	120	6	4.8	500	2700	80	60	15,000	Yes	★	Damp	Clear, Bent tip	
GLOBES																
G25	E26	4	23192	LED4DG25-AGC-2BT	120	6	4.3	350	2700	80	40	15,000	Yes	★	Damp	All Glass, Clear, 2 pack
	E26	4.5	21253	LED5DG25-W3/827	120	6	4.3	350	2700	80	40	15,000	Yes	★	Damp	White
	E26	4.5	24954	LED4DG25-AGW-2	120	6	4.3	350	2700	80	40	15,000	Yes	★	Damp	All glass, White, 2 pack
	E26	7	21255	LED7DG25-W3/827	120	6	4.3	500	2700	80	60	15,000	Yes	★	Damp	White
	E26	7	23344	LED5DG25-AGC-2BT	120	6	4.3	500	2700	80	60	15,000	Yes	★	Damp	All glass, Clear, 2 pack
G16	E12	3.5	28297	LED3DFGC-GC-2	120	6	3.0	250	2700	80	25	15,000	Yes		Damp	All glass, Clear, 2 pack
	E12	3.5	28280	LED3DFG16-GW-2T	120	6	3.0	250	2700	80	25	15,000	Yes		Damp	All glass, White, 2 pack
	E12	4.5	24535	LED4DFGC-GC-2	120	6	3.0	350	2700	80	40	15,000	Yes		Damp	All Glass, Clear, 2 pack
	E12	4.5	25046	LED4DGC-AGW-2 120	120	6	3.0	350	2700	80	40	15,000	Yes	★	Damp	All Glass, Frosted, 2 pack
	E12	5.5	25923	LED5DFGC-GW-2 120	120	6	3.0	500	2700	80	60	15,000	Yes	★	Damp	All Glass, Frosted, 2 pack
E12	5.5	24547	LED5DFGC-GC-2	120	6	3.0	500	2700	80	60	15,000	Yes	★	Damp	All Glass, Clear, 2 pack	

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.