



LED Tubes

Complete. Innovative. Trusted



GE current
a Daintree company

Why switch to LED tubes?

LED Tubes are the fast and easy way to upgrade to LED. With Current's UL Type A, Type B and UL Type C options, you can choose the best solution for your needs.



2.3X longer life
(70K vs. 30K hrs.)



Uses 43% less energy
(18W and 2600 lumens vs
LFL 32W and 2800 lumens)



Better quality of light
(Instant-On)

Which LED tube is right for you?

Integrated LED Tube (UL Type A)

Easy Plug & Play Performance



- Uses existing ballast
- Quickest installation
- Lowest installation cost
- Limited dimming
- System compatibility depends on LFL ballast

Double Ended Ballast Bypass LED Tube (UL Type B)


Simplest Total System
direct wiring to mains



- Uses no external driver or ballast
- Eliminates compatibility issues
- Excellent efficacy and additional maintenance savings
- Highest install cost
- Additional safety precautions
Fuse recommended, but not required

Remote Driver LED Tube (UL Type C)

Best Performance



- Uses external driver, providing expanded performance capabilities
- Excellent efficacy
- Controllable dimming system
- Requires LED driver
- Medium installation cost

Current makes updating simpler.

Refit Solutions from Current

It's never been easier to upgrade from linear fluorescents to Current's LED tubes. With Current's expanding offering, there are efficient solutions for many popular applications.

Available in 2, 3, 4, and 8 ft lengths along with u-tubes

Shatter-resistant plastic option to prevent breakage and downtime

Glass options fully illuminate fixture with >270° light distribution

To learn more about LED tube lighting and other Refit Solutions, visit www.gecurrent.com



Complete Offering

Current offers a **broader** and **deeper** LED Tubes assortment than leading competitors.

Innovative Designs

High-performance solutions for demanding market needs.

Trusted Experience

GE invented the first linear fluorescent in 1938, and Current has transferred that leadership to LED tubes.



What features does Current offer versus the leading competitors?

More
total tube
options

More
glass tubes

**Highest
Lumen**
options in T8 & T5


Current offers
Products
Assembled in USA

**No
Compromise**
Right brightness,
type, and material
per application

**Wider Beam
Angle**
Distributes light
better and eliminates
dark spots

Bright Light
Provides high light
output for high-bay
or demanding
applications

**BAA
Compliant
Options**



Statements based on product information on leading competitor public USA websites.

Current makes updating *Simpler*



Refit Solutions from Current.

It's never been easier to upgrade from linear fluorescents to Current's LED tubes. With Current's expanding offering, there are efficient solutions for many popular applications.


Integrated, ballast bypass and remote driver technology in 2, 3, 4 & 8 ft lengths and U-tubes

Shatter-resistant plastic coated glass options to prevent breakage and downtime


Glass options fully illuminate fixture with 270° light distribution



(UL Type A)



(UL Type B)



(UL Type C)



Linear Fluorescent lighting is the most prevalent light source among Commercial and Industrial buildings. LED Tube conversions are the perfect fit for any industry.



Manufacturing



Healthcare



Government



Education



Commercial Office



Retail

LED REPLACEMENT TUBES

Integrated Plastic Tubes - Type A

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated ¹ Life L70 (Hrs) | Power Factor | DLC [®] | UL | Location ³ Rating | Additional Information | |
|--|-----------|-------|------------|-----------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|--------------|------------------|-----|------------------------------|-----------------------------------|--|
| Integrated 4ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | | |
| T8 | G13 | 15 | 62401 | LED15ET8/4/835 | 25 | 48 | 2250 | 3500K | 80+ | | | 70,000 | - | Yes | Yes | Damp | Instant or PRS Ballast, NSF Rated | |
| | G13 | 12 | 61223 | LED12ET8/4/835 | 25 | 48 | 1800 | 3500K | 80+ | | | 70,000 | - | Yes | Yes | Damp | Instant or PRS Ballast, NSF Rated | |
| Integrated 3ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | | |
| | G13 | 12 | 26544 | LED12ET8/3/835 | 25 | 36 | 1550 | 3500K | 80+ | | | 70,000 | - | Yes | Yes | Damp | Instant or PRS Ballast, NSF Rated | |
| Integrated 2ft LED Plastic Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | | |
| | G13 | 9 | 26648 | LED9ET8/2/840 | 25 | 24 | 1400 | 4000K | 80+ | | | 70,000 | - | Yes | Yes | Damp | Instant or PRS Ballast, NSF Rated | |
| Integrated U6 Plastic Tubes | | | | | | | | | | | | | | | | | | |
| | G13 | 13 | 43120 | LED13ET8/U6/830 | 12 | 22.5 | 1800 | 3000K | 80+ | | | 50,000 | - | Yes | Yes | Damp | Instant or PRS Ballast | |
| | G13 | 13 | 43125 | LED13ET8/U6/835 | 12 | 22.5 | 1850 | 3500K | 80+ | | | 50,000 | - | Yes | Yes | Damp | Instant or PRS Ballast | |
| | G13 | 13 | 43129 | LED13ET8/U6/840 | 12 | 22.5 | 1900 | 4000K | 80+ | | | 50,000 | - | Yes | Yes | Damp | Instant or PRS Ballast | |
| | G13 | 13 | 43130 | LED13ET8/U6/850 | 12 | 22.5 | 1900 | 5000K | 80+ | | | 50,000 | - | Yes | Yes | Damp | Instant or PRS Ballast | |

Integrated covRguard[®] T8 Plastic Coated Glass Tubes - Type A

| Type | Base Type | NBF Lamp/System Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated ¹ Life L70 (Hrs) | Power Factor | DLC [®] | UL | Location ³ Rating | Additional Information | |
|---|-----------|-----------------------|------------|---------------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|--------------|------------------|-----|------------------------------|------------------------|--|
| Integrated 2ft covRguard LED Tubes | | | | | | | | | | | | | | | | | | |
| | G13 | 8.5/11 | 93135654 | LED8ET8/G/2/830CVG | 20 | 24 | 1250 | 3000K | 80 | | | 70,000 | >.9 | - | Yes | Damp | NSF Food Zone | |
| | G13 | 8.5/11 | 93135655 | LED8ET8/G/2/835CVG | 20 | 24 | 1300 | 3500K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 8.5/11 | 93135656 | LED8ET8/G/2/840CVG | 20 | 24 | 1300 | 4000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 8.5/11 | 93135657 | LED8ET8/G/2/850CVG | 20 | 24 | 1350 | 5000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| Integrated 3ft covRguard LED Tubes | | | | | | | | | | | | | | | | | | |
| | G13 | 11/13 | 93135658 | LED11ET8/G/3/830CVG | 20 | 36 | 1400 | 3000K | 80 | | | 70,000 | >.9 | - | Yes | Damp | NSF Food Zone | |
| | G13 | 11/13 | 93135659 | LED11ET8/G/3/835CVG | 20 | 36 | 1450 | 3500K | 80 | | | 70,000 | >.9 | - | Yes | Damp | NSF Food Zone | |
| | G13 | 11/13 | 93135660 | LED11ET8/G/3/840CVG | 20 | 36 | 1450 | 4000K | 80 | | | 70,000 | >.9 | - | Yes | Damp | NSF Food Zone | |
| | G13 | 11/13 | 93135661 | LED11ET8/G/3/850CVG | 20 | 36 | 1500 | 5000K | 80 | | | 70,000 | >.9 | - | Yes | Damp | NSF Food Zone | |
| Integrated 4ft covRguard LED Tubes | | | | | | | | | | | | | | | | | | |
| | G13 | 10/13 | 93135713 | LED10ET8/G/4/830CVG | 20 | 48 | 1550 | 3000K | 80 | | | 70,000 | >.9 | - | Yes | Damp | NSF Food Zone | |
| | G13 | 10/13 | 93135714 | LED10ET8/G/4/835CVG | 20 | 48 | 1600 | 3500K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 10/13 | 93135715 | LED10ET8/G/4/840CVG | 20 | 48 | 1600 | 4000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 10/13 | 93135716 | LED10ET8/G/4/850CVG | 20 | 48 | 1650 | 5000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 15/17 | 93135764 | LED15ET8/G/4/830CVG | 20 | 48 | 2000 | 3000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 15/17 | 93135823 | LED15ET8/G/4/835CVG | 20 | 48 | 2100 | 3500K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 15/17 | 93135824 | LED15ET8/G/4/840CVG | 20 | 48 | 2100 | 4000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 15/17 | 93135846 | LED15ET8/G/4/850CVG | 20 | 48 | 2150 | 5000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 18/20 | 93135924 | LED18ET8/G/4/830CVG | 20 | 48 | 2300 | 3000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 18/20 | 93135946 | LED18ET8/G/4/835CVG | 20 | 48 | 2400 | 3500K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 18/20 | 93135947 | LED18ET8/G/4/840CVG | 20 | 48 | 2400 | 4000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |
| | G13 | 18/20 | 93135948 | LED18ET8/G/4/850CVG | 20 | 48 | 2450 | 5000K | 80 | | | 70,000 | >.9 | Yes | Yes | Damp | NSF Food Zone | |

Integrated PET Plastic Coated Glass Tubes - Type A

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC [®] | UL | Location ³ Rating | Additional Information |
|--|-----------|-------|------------|-------------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|------------------|-----|------------------------------|------------------------|
| 4ft T8 LED Tube- Plastic Coated Glass | | | | | | | | | | | | | | | | |
| | G13 | 14 | 93107394 | LED14ET8/G4/830CT | 20 | 48 | 1950 | 3000K | 80+ | | | 50,000 | - | Yes | Damp | NSF Splash Zone |
| | G13 | 14 | 93107506 | LED14ET8/G4/835CT | 20 | 48 | 2000 | 3500K | 80+ | | | 50,000 | Yes | Yes | Damp | NSF Splash Zone |
| | G13 | 14 | 93107507 | LED14ET8/G4/840CT | 20 | 48 | 2000 | 4000K | 80+ | | | 50,000 | Yes | Yes | Damp | NSF Splash Zone |
| | G13 | 14 | 93107510 | LED14ET8/G4/850CT | 20 | 48 | 2050 | 5000K | 80+ | | | 50,000 | Yes | Yes | Damp | NSF Splash Zone |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

² Minimum order quantity = Case Quantity

³ ENERGY STAR[®] status: ENERGY STAR[®] certified. Lamps without a "★" are not ENERGY STAR[®] certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

LED REPLACEMENT TUBES

Integrated Glass Tubes - Type A

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC* | UL | Location ³ Rating | Additional Information |
|---|-----------|-------|------------|------------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|------|-----|------------------------------|------------------------|
| Integrated 4 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| T8 | G13 | 18 | 35767 | LED18ET8/G/4/830 | 20 | 48 | 2400 | 3000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 18 | 35768 | LED18ET8/G/4/835 | 20 | 48 | 2500 | 3500K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 18 | 35769 | LED18ET8/G/4/840 | 20 | 48 | 2500 | 4000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 18 | 35772 | LED18ET8/G/4/850 | 20 | 48 | 2600 | 5000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 18 | 35773 | LED18ET8/G/4/865 | 20 | 48 | 2600 | 6500K | 80+ | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 35790 | LED15ET8/G/4/830 | 20 | 48 | 2100 | 3000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 35791 | LED15ET8/G/4/835 | 20 | 48 | 2200 | 3500K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 35793 | LED15ET8/G/4/840 | 20 | 48 | 2200 | 4000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 35797 | LED15ET8/G/4/850 | 20 | 48 | 2300 | 5000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 35798 | LED15ET8/G/4/865 | 20 | 48 | 2300 | 6500K | 80+ | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 10 | 34277 | LED10ET8/G/4/830 | 20 | 48 | 1550 | 3000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 10 | 34279 | LED10ET8/G/4/835 | 20 | 48 | 1600 | 3500K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 10 | 34280 | LED10ET8/G/4/840 | 20 | 48 | 1600 | 4000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 10 | 34282 | LED10ET8/G/4/850 | 20 | 48 | 1650 | 5000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| Integrated 4 ft 50K Value LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| | G13 | 11.5 | 93107390 | LED11ET8/G/4/830 | 20 | 48 | 1600 | 3000K | 80+ | | | 50,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11.5 | 93107391 | LED11ET8/G/4/835 | 20 | 48 | 1600 | 3500K | 80+ | | | 50,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11.5 | 93107392 | LED11ET8/G/4/840 | 20 | 48 | 1650 | 4000K | 80+ | | | 50,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11.5 | 93107393 | LED11ET8/G/4/850 | 20 | 48 | 1700 | 5000K | 80+ | | | 50,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 14 | 34283 | LED14ET8/G/4/830 | 20 | 48 | 1950 | 3000K | 80+ | | | 50,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 14 | 34289 | LED14ET8/G/4/835 | 20 | 48 | 2000 | 3500K | 80+ | | | 50,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 14 | 34291 | LED14ET8/G/4/840 | 20 | 48 | 2000 | 4000K | 80+ | | | 50,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 14 | 34300 | LED14ET8/G/4/850 | 20 | 48 | 2050 | 5000K | 80+ | | | 50,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| Integrated 3 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| | G13 | 11 | 35783 | LED11ET8/G/3/830 | 20 | 36 | 1450 | 3000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11 | 35784 | LED11ET8/G/3/835 | 20 | 36 | 1500 | 3500K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11 | 35788 | LED11ET8/G/3/840 | 20 | 36 | 1500 | 4000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11 | 35789 | LED11ET8/G/3/850 | 20 | 36 | 1600 | 5000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| Integrated 2 ft LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| | G13 | 8 | 35775 | LED8ET8/G/2/830 | 20 | 24 | 1300 | 3000K | 80+ | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 8 | 35776 | LED8ET8/G/2/835 | 20 | 24 | 1350 | 3500K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 8 | 35778 | LED8ET8/G/2/840 | 20 | 24 | 1350 | 4000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 8 | 35779 | LED8ET8/G/2/850 | 20 | 24 | 1400 | 5000K | 80+ | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |

Integrated Glass Tubes with reveal[®] TriGain[™] Technology - Type A

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC* | UL | Location ³ Rating | Additional Information |
|---|-----------|-------|------------|------------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|------|-----|------------------------------|------------------------|
| Integrated 4 ft High CRI with reveal[®] TriGain[™] Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| | G13 | 15 | 34307 | LED15ET8/G/4/935 | 20 | 48 | 2150 | 3500K | 90 | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 34313 | LED15ET8/G/4/940 | 20 | 48 | 2200 | 4000K | 90 | | | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| Integrated 3 ft High CRI with reveal[®] TriGain[™] Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| | G13 | 11 | 34323 | LED11ET8/G/3/935 | 20 | 36 | 1500 | 3500K | 90 | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11 | 34326 | LED11ET8/G/3/940 | 20 | 36 | 1500 | 4000K | 90 | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11 | 34332 | LED11ET8/G/3/950 | 20 | 36 | 1600 | 5000K | 90 | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| Integrated 2 ft High CRI with reveal[®] TriGain[™] Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| | G13 | 9 | 34341 | LED9ET8/G/2/940 | 20 | 24 | 1300 | 4000K | 90 | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 9 | 34342 | LED9ET8/G/2/950 | 20 | 24 | 1400 | 5000K | 90 | | | 70,000 | - | Yes | Damp | Instant or PRS Ballast |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

² Minimum order quantity = Case Quantity

★ ENERGY STAR[®] status: ENERGY STAR[®] certified. Lamps without a "★" are not ENERGY STAR[®] certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

LED REPLACEMENT TUBES

Integrated BAA Compliant Glass Tubes (Type A) MTO 1000 PC MIN 12 Weeks

| Type | Base Type | Watts | Order Code | Description | Case ² Volts | MOL Qty | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC ⁶ | UL | Location ³ Rating | Additional Information |
|---|-----------|-------|------------|----------------------|-------------------------|---------|----------------|--------------------|-----|---------------------|-----------------------------------|------------------|-----|------------------------------|------------------------|
| Integrated BAA Compliant Glass Tubes (Type A) MTO 1000 PC MIN 12 Weeks | | | | | | | | | | | | | | | |
| T8 | G13 | 14 | 93152320 | LED14ET8/G4G4/830BAA | 25 | 48 | 2200 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 14 | 93152353 | LED14ET8/G4/835BAA | 25 | 48 | 2200 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 14 | 93152351 | LED14ET8/G4/840BAA | 25 | 48 | 2200 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 14 | 93152352 | LED14ET8/G4/850BAA | 25 | 48 | 2200 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 11 | 93152354 | LED11ET8/G4/830BAA | 25 | 48 | 1800 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 11 | 93152355 | LED11ET8/G4/835BAA | 25 | 48 | 1800 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 11 | 93152356 | LED11ET8/G4/840BAA | 25 | 48 | 1800 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 11 | 93152357 | LED11ET8/G4/850BAA | 25 | 48 | 1800 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 9 | 93152358 | LED9ET8/G4/830BAA | 25 | 48 | 1650 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 9 | 93152359 | LED9ET8/G4/835BAA | 25 | 48 | 1650 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 9 | 93152361 | LED9ET8/G4/840BAA | 25 | 48 | 1650 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 9 | 93152360 | LED9ET8/G4/850BAA | 25 | 48 | 1650 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 10 | 93152412 | LED10ET8/G3/830BAA | 25 | 36 | 1450 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 10 | 93152413 | LED10ET8/G3/835BAA | 25 | 36 | 1450 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 10 | 93152414 | LED10ET8/G3/840BAA | 25 | 36 | 1450 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 10 | 93152415 | LED10ET8/G3/850BAA | 25 | 36 | 1450 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 8 | 93152416 | LED8ET8/G2/830BAA | 25 | 24 | 1250 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 8 | 93152417 | LED8ET8/G2/835BAA | 25 | 24 | 1250 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 8 | 93152418 | LED8ET8/G2/840BAA | 25 | 24 | 1250 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | |
| | G13 | 8 | 93152419 | LED8ET8/G2/850BAA | 25 | 24 | 1250 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

² Minimum order quantity = Case Quantity

★ ENERGY STAR[®] status: ENERGY STAR[®] certified. Lamps without a "★" are not ENERGY STAR[®] certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Updated / New Product

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

Get more information at
www.gecurrent.com

LED REPLACEMENT TUBES

Integrated Glass Tubes - Type A

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC [®] | UL | Location ³ Rating | Additional Information |
|---|-----------|-------|------------------|------------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|------------------|-----|------------------------------|------------------------|
| Integrated 4 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| T5 | G5 | 25.5 | 19203 | LED26ET5/G/4/830 | 20 | 46 | 3650 | 3000K | 80+ | | | 50,000 | Yes | Yes | Damp | Requires T5 HO Ballast |
| | G5 | 25.5 | 19221 | LED26ET5/G/4/835 | 20 | 46 | 3750 | 3500K | 80+ | | | 50,000 | Yes | Yes | Damp | Requires T5 HO Ballast |
| | G5 | 25.5 | 19227 | LED26ET5/G/4/840 | 20 | 46 | 3800 | 4000K | 80+ | | | 50,000 | Yes | Yes | Damp | Requires T5 HO Ballast |
| | G5 | 25.5 | 19348 | LED26ET5/G/4/850 | 20 | 46 | 3900 | 5000K | 80+ | | | 50,000 | Yes | Yes | Damp | Requires T5 HO Ballast |
| | G5 | 5 | 19488 | LED26ET5/G/4/865 | 20 | 46 | 3800 | 6500K | 80+ | | | 50,000 | - | Yes | Damp | Requires T5 HO Ballast |
| Integrated 2 ft LED Glass T5 HO Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| G5 | 11 | 34413 | LED11ET5/G/2/830 | 20 | 22 | 1500 | 3000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HO Ballast |
| G5 | 11 | 34417 | LED11ET5/G/2/835 | 20 | 22 | 1550 | 3500K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HO Ballast |
| G5 | 11 | 34418 | LED11ET5/G/2/840 | 20 | 22 | 1600 | 4000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HO Ballast |
| G5 | 11 | 34424 | LED11ET5/G/2/850 | 20 | 22 | 1600 | 5000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HO Ballast |
| Integrated 4 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| G5 | 13 | 34351 | LED13ET5G4/830HE | 20 | 46 | 1900 | 3000K | 80+ | | | | 50,000 | Yes | Yes | Damp | Requires T5 HE Ballast |
| G5 | 13 | 34354 | LED13ET5G4/835HE | 20 | 46 | 1950 | 3500K | 80+ | | | | 50,000 | Yes | Yes | Damp | Requires T5 HE Ballast |
| G5 | 13 | 34355 | LED13ET5G4/840HE | 20 | 46 | 2000 | 4000K | 80+ | | | | 50,000 | Yes | Yes | Damp | Requires T5 HE Ballast |
| G5 | 13 | 34367 | LED13ET5G4/850HE | 20 | 46 | 2000 | 5000K | 80+ | | | | 50,000 | Yes | Yes | Damp | Requires T5 HE Ballast |
| Integrated 3 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| G5 | 10 | 34371 | LED10ET5G3/830HE | 20 | 34 | 1500 | 3000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |
| G5 | 10 | 34376 | LED10ET5G3/835HE | 20 | 34 | 1550 | 3500K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |
| G5 | 10 | 34401 | LED10ET5G3/840HE | 20 | 34 | 1600 | 4000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |
| G5 | 10 | 34402 | LED10ET5G3/850HE | 20 | 34 | 1600 | 5000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |
| Integrated 2 ft LED Glass T5 HE Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | |
| G5 | 7 | 34403 | LED7ET5/G2/830HE | 20 | 22 | 1000 | 3000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |
| G5 | 7 | 34404 | LED7ET5/G2/835HE | 20 | 22 | 1100 | 3500K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |
| G5 | 7 | 34411 | LED7ET5/G2/840HE | 20 | 22 | 1150 | 4000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |
| G5 | 7 | 34412 | LED7ET5/G2/850HE | 20 | 22 | 1150 | 5000K | 80+ | | | | 50,000 | - | Yes | Damp | Requires T5 HE Ballast |

Dual Mode Glass Tubes-Type A + Type B

| | | | | | | | | | | | | | | | | | Type A Mode | | | Type B Mode | | | | | | | |
|--|-----------|-------|------------|------------------|-----------------------|----------|---------------|------------|------------------|------|----|---------------------|------|----|------------|----------------|-------------|--------------|-------|--------------------------|------------------|------|--|--|--|--|--|
| Type | Base Type | Watts | Order Code | Description | Case ² Qty | MOL (In) | Input Voltage | Lamp Watts | System Watts (W) | | | Initial Lumens (lm) | | | Lamp Watts | Initial Lumens | CRI | Power Factor | CCT | L70 Lumen Maint. (hours) | DLC [®] | | | | | | |
| | | | | | | | | | | | | | | | | | LBF | NBF | HBFB | LBF | NBF | HBFB | | | | | |
| Dual Mode LED Tubes (Type A + Type B) | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| T8 | G13 | 13 | 93138405 | LED13ABT8/G4/830 | 25 | 48 | 120/277 | 13 | 14 | 15.5 | NA | 1600 | 1850 | NA | 13 | 1850 | 80 | >0.9 | 3000k | 50,000 | Yes | | | | | | |
| | G13 | 13 | 93138426 | LED13ABT8/G4/835 | 25 | 48 | 120/277 | 13 | 14 | 15.5 | NA | 1650 | 1900 | NA | 13 | 1900 | 80 | >0.9 | 3500k | 50,000 | Yes | | | | | | |
| | G13 | 13 | 93138429 | LED13ABT8/G4/840 | 25 | 48 | 120/277 | 13 | 14 | 15.5 | NA | 1700 | 1950 | NA | 13 | 1950 | 80 | >0.9 | 4000k | 50,000 | Yes | | | | | | |
| | G13 | 13 | 93138430 | LED13ABT8/G4/850 | 25 | 48 | 120/277 | 13 | 14 | 15.5 | NA | 1700 | 1950 | NA | 13 | 1950 | 80 | >0.9 | 5000k | 50,000 | Yes | | | | | | |

Ballast Bypass Glass Tubes XL - Double Ended - Type B T8

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated ¹ Life L70 (Hrs) | Power Factor | DLC [®] | UL | Location ³ Rating | Additional Information |
|---|-----------|-------|------------|--------------------|---------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|--------------|------------------|-----|------------------------------|------------------------|
| Ballast Bypass - 4 ft LED XL Glass Tubes | | | | | | | | | | | | | | | | | |
| T8 | G13 | 9.5 | 93132548 | LED9BDT8/G4/830XL | 120-277 | 20 | 48 | 1550 | 3000K | 80 | | 70,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | G13 | 9.5 | 93132549 | LED9BDT8/G4/835XL | 120-277 | 20 | 48 | 1600 | 3500K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 9.5 | 93132550 | LED9BDT8/G4/840XL | 120-277 | 20 | 48 | 1650 | 4000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 9.5 | 93132551 | LED9BDT8/G4/850XL | 120-277 | 20 | 48 | 1650 | 5000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 13 | 93132552 | LED13BDT8/G4/830XL | 120-277 | 20 | 48 | 1950 | 3000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 13 | 93132553 | LED13BDT8/G4/835XL | 120-277 | 20 | 48 | 2000 | 3500K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 13 | 93132554 | LED13BDT8/G4/840XL | 120-277 | 20 | 48 | 2050 | 4000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 13 | 93132555 | LED13BDT8/G4/850XL | 120-277 | 20 | 48 | 2050 | 5000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 16 | 93132586 | LED16BDT8/G4/830XL | 120-277 | 20 | 48 | 2450 | 3000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 16 | 93132587 | LED16BDT8/G4/835XL | 120-277 | 20 | 48 | 2500 | 3500K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 16 | 93132588 | LED16BDT8/G4/840XL | 120-277 | 20 | 48 | 2550 | 4000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | G13 | 16 | 93132589 | LED16BDT8/G4/850XL | 120-277 | 20 | 48 | 2550 | 5000K | 80 | | 70,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

² Minimum order quantity = Case Quantity

★ ENERGY STAR[®] status: ENERGY STAR[®] certified. Lamps without a "★" are not ENERGY STAR[®] certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

LED REPLACEMENT TUBES

Ballast Bypass Glass Tubes - Double Ended - Type B

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (in) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated ¹ Life L70 (Hrs) | Power Factor | DLC [®] | UL | Location ³ Rating | Additional Information |
|---|-----------|----------|---------------------|-------------------|---------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|--------------|------------------|-----|------------------------------|--------------------------|
| Ballast Bypass - 8 ft LED Glass Tubes | | | | | | | | | | | | | | | | | |
| T8 | Fa8 | 34 | 93122170 | LED34BDT8/G/8/830 | 120-277 | 20 | 96 | 4000 | 3000K | 80 | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | Fa8 | 34 | 93122171 | LED34BDT8/G/8/835 | 120-277 | 20 | 96 | 4000 | 3500K | 80 | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | Fa8 | 34 | 93122172 | LED34BDT8/G/8/840 | 120-277 | 20 | 96 | 4400 | 4000K | 80 | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | Fa8 | 34 | 93122174 | LED34BDT8/G/8/850 | 120-277 | 20 | 96 | 4400 | 5000K | 80 | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | r17d | 43 | 93132590 | LED43BDT8/G/8/830 | 120-277 | 20 | 96 | 5000 | 3000K | 80 | | 50,000 | >.9 | - | Yes | Damp | Double Ended Power |
| | r17d | 43 | 93132591 | LED43BDT8/G/8/835 | 120-277 | 20 | 96 | 5000 | 3500K | 80 | | 50,000 | >.9 | - | Yes | Damp | Double Ended Power |
| | r17d | 43 | 93132592 | LED43BDT8/G/8/840 | 120-277 | 20 | 96 | 5500 | 4000K | 80 | | 50,000 | >.9 | - | Yes | Damp | Double Ended Power |
| | r17d | 43 | 93132593 | LED43BDT8/G/8/850 | 120-277 | 20 | 96 | 5500 | 5000K | 80 | | 50,000 | >.9 | - | Yes | Damp | Double Ended Power |
| Ballast Bypass - 4 ft LED Glass Tubes | | | | | | | | | | | | | | | | | |
| G13 | 16 | 93123476 | LED16BDT8/G4/830 | 120-277 | 20 | 48 | 2100 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 16 | 93125618 | LED16BDT8/G4/835 | 120-277 | 20 | 48 | 2150 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 16 | 93125620 | LED16BDT8/G4/840 | 120-277 | 20 | 48 | 2200 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 16 | 93125622 | LED16BDT8/G4/850 | 120-277 | 20 | 48 | 2200 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 39493 | LED14BDT8/G4/830 | 120-277 | 20 | 48 | 1700 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 39494 | LED14BDT8/G4/835 | 120-277 | 20 | 48 | 1750 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 39498 | LED14BDT8/G4/840 | 120-277 | 20 | 48 | 1800 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 39519 | LED14BDT8/G4/850 | 120-277 | 20 | 48 | 1850 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 11 | 93117212 | LED11BDT8/G4/830 | 120-277 | 20 | 48 | 1600 | 3000K | 80 | | | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| G13 | 11 | 93117213 | LED11BDT8/G4/835 | 120-277 | 20 | 48 | 1650 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 11 | 93117214 | LED11BDT8/G4/840 | 120-277 | 20 | 48 | 1650 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 11 | 93117215 | LED11BDT8/G4/850 | 120-277 | 20 | 48 | 1700 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 3 ft LED Glass Tubes | | | | | | | | | | | | | | | | | |
| G13 | 12 | 39525 | LED12BDT8/G3/830 | 120-277 | 20 | 36 | 1450 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 12 | 39547 | LED12BDT8/G3/835 | 120-277 | 20 | 36 | 1500 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 12 | 39554 | LED12BDT8/G3/840 | 120-277 | 20 | 36 | 1550 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 12 | 39557 | LED12BDT8/G3/850 | 120-277 | 20 | 36 | 1550 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 2 ft LED Glass Tubes | | | | | | | | | | | | | | | | | |
| G13 | 9 | 39558 | LED9BDT8/G2/830 | 120-277 | 20 | 24 | 1100 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 9 | 39560 | LED9BDT8/G2/835 | 120-277 | 20 | 24 | 1150 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 9 | 39561 | LED9BDT8/G2/840 | 120-277 | 20 | 24 | 1200 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 9 | 39563 | LED9BDT8/G2/850 | 120-277 | 20 | 24 | 1200 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 4 ft LED Tube - PET Plastic Coated Glass | | | | | | | | | | | | | | | | | |
| G13 | 14 | 93123123 | LED14BDT8/G4/830CT | 120-277 | 20 | 48 | 1650 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Shatter containment, NSF |
| G13 | 14 | 93123124 | LED14BDT8/G4/835CT | 120-277 | 20 | 48 | 1750 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Shatter containment, NSF |
| G13 | 14 | 93123316 | LED14BDT8/G4/840CT | 120-277 | 20 | 48 | 1750 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Shatter containment, NSF |
| G13 | 14 | 93123317 | LED14BDT8/G4/850CT | 120-277 | 20 | 48 | 1800 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Shatter containment, NSF |
| G13 | 11 | 93129539 | LED11BDT8/G4/830CT | 120-277 | 20 | 48 | 1550 | 3000K | 80 | | | 50,000 | >.9 | - | Yes | Damp | Shatter containment, NSF |
| G13 | 11 | 93129660 | LED11BDT8/G4/835CT | 120-277 | 20 | 48 | 1600 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Shatter containment, NSF |
| G13 | 11 | 93129666 | LED11BDT8/G4/840CT | 120-277 | 20 | 48 | 1650 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Shatter containment, NSF |
| G13 | 11 | 93129717 | LED11BDT8/G4/850CT | 120-277 | 20 | 48 | 1700 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Shatter containment, NSF |
| Ballast Bypass - 4 ft LED Glass BAA Compliant Tubes MTO 1000 PC Min 12 weeks | | | | | | | | | | | | | | | | | |
| G13 | 10.5 | 93138099 | LED10BDT8/G4/830BAA | 120-277 | 25 | 48 | 1650 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 10.5 | 93138132 | LED10BDT8/G4/835BAA | 120-277 | 25 | 48 | 1650 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 10.5 | 93138239 | LED10BDT8/G4/840BAA | 120-277 | 25 | 48 | 1650 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 10.5 | 93138240 | LED10BDT8/G4/850BAA | 120-277 | 25 | 48 | 1650 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 93138241 | LED14BDT8/G4/830BAA | 120-277 | 25 | 48 | 1800 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 93138242 | LED14BDT8/G4/835BAA | 120-277 | 25 | 48 | 1800 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 93138244 | LED14BDT8/G4/840BAA | 120-277 | 25 | 48 | 1800 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 14 | 93138245 | LED14BDT8/G4/850BAA | 120-277 | 25 | 48 | 1800 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 15 | 93138262 | LED15BDT8/G4/830BAA | 120-277 | 25 | 48 | 2200 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 15 | 93138263 | LED15BDT8/G4/835BAA | 120-277 | 25 | 48 | 2200 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 15 | 93138264 | LED15BDT8/G4/840BAA | 120-277 | 25 | 48 | 2200 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 15 | 93138265 | LED15BDT8/G4/850BAA | 120-277 | 25 | 48 | 2200 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 3 ft LED Glass BAA Compliant Tubes MTO 1000 PC Min 12 weeks | | | | | | | | | | | | | | | | | |
| G13 | 12 | 93151855 | LED12BDT8/G3/830BAA | 120-277 | 25 | 36 | 1450 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 12 | 93151858 | LED12BDT8/G3/835BAA | 120-277 | 25 | 36 | 1450 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 12 | 93151857 | LED12BDT8/G3/840BAA | 120-277 | 25 | 36 | 1450 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 12 | 93151856 | LED12BDT8/G3/850BAA | 120-277 | 25 | 36 | 1450 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 2 ft LED Glass BAA Compliant Tubes MTO 1000 PC Min 12 weeks | | | | | | | | | | | | | | | | | |
| G13 | 9 | 93151812 | LED9BDT8/G2/830BAA | 120-277 | 25 | 24 | 1150 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 9 | 93151813 | LED9BDT8/G2/835BAA | 120-277 | 25 | 24 | 1150 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 9 | 93151832 | LED9BDT8/G2/840BAA | 120-277 | 25 | 24 | 1150 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| G13 | 9 | 93151833 | LED9BDT8/G2/850BAA | 120-277 | 25 | 24 | 1150 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass Type B Double Ended LED U1-Tubes | | | | | | | | | | | | | | | | | |
| 2G13 | 13 | 93107387 | LED13BDT8/U/830 | 120-277 | 15 | 22.5 | 1750 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |
| 2G13 | 13 | 93107352 | LED13BDT8/U/835 | 120-277 | 15 | 22.5 | 1800 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |
| 2G13 | 13 | 93107388 | LED13BDT8/U/840 | 120-277 | 15 | 22.5 | 1850 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |
| 2G13 | 13 | 93107389 | LED13BDT8/U/850 | 120-277 | 15 | 22.5 | 1850 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |
| Ballast Bypass Type B Double Ended LED U6-Tubes | | | | | | | | | | | | | | | | | |
| 2G13 | 13 | 93133049 | LED13BDT8/U6/830 | 120-277 | 12 | 22.5 | 1750 | 3000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |
| 2G13 | 13 | 93133050 | LED13BDT8/U6/835 | 120-277 | 12 | 22.5 | 1800 | 3500K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |
| 2G13 | 13 | 93133051 | LED13BDT8/U6/840 | 120-277 | 12 | 22.5 | 1850 | 4000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |
| 2G13 | 13 | 93133052 | LED13BDT8/U6/850 | 120-277 | 12 | 22.5 | 1850 | 5000K | 80 | | | 50,000 | >.9 | Yes | Yes | Damp | Double Ended Power |

Updated / New Product

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

Get more information at
www.gecurrent.com

LED REPLACEMENT TUBES

Ballast Bypass Glass Tubes - Double Ended - Type B T5

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated ¹ Life L70 (Hrs) | Power Factor | DLC® | UL | Location ³ Rating | Additional Information |
|--|-----------|-------|------------|------------------|---------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|--------------|------|-----|------------------------------|------------------------|
| Ballast Bypass - 4 ft LED Glass T5 HO Tubes | | | | | | | | | | | | | | | | | |
| T5 | | 25 | 93100292 | LED25BDT5/G4/830 | 120-277 | 20 | 46 | 3300 | 3000 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | | 25 | 93100293 | LED25BDT5/G4/835 | 120-277 | 20 | 46 | 3400 | 3500 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | | 25 | 93100294 | LED25BDT5/G4/840 | 120-277 | 20 | 46 | 3500 | 4000 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | | 25 | 93100295 | LED25BDT5/G4/850 | 120-277 | 20 | 46 | 3600 | 5000 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 3 ft LED Glass T5 HO Tubes | | | | | | | | | | | | | | | | | |
| | | 17 | 93114325 | LED17BDT5/G3/830 | 120-277 | 20 | 33 | 2300 | 3000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 17 | 93114626 | LED17BDT5/G3/835 | 120-277 | 20 | 33 | 2400 | 3500 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 17 | 93114629 | LED17BDT5/G3/840 | 120-277 | 20 | 33 | 2500 | 4000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 17 | 93114814 | LED17BDT5/G3/850 | 120-277 | 20 | 33 | 2550 | 5000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 2 ft LED Glass T5 HO Tubes | | | | | | | | | | | | | | | | | |
| | | 11 | 93113793 | LED11BDT5/G2/830 | 120-277 | 20 | 22 | 1500 | 3000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 11 | 93114322 | LED11BDT5/G2/835 | 120-277 | 20 | 22 | 1550 | 3500 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 11 | 93114323 | LED11BDT5/G2/840 | 120-277 | 20 | 22 | 1600 | 4000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 11 | 93114324 | LED11BDT5/G2/850 | 120-277 | 20 | 22 | 1650 | 5000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 4 ft LED Glass T5 HE Tubes | | | | | | | | | | | | | | | | | |
| T5 | | 14 | 93128354 | LED14BDT5G4830HE | 120-277 | 20 | 46 | 2050 | 3000 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | | 14 | 93128355 | LED14BDT5G4835HE | 120-277 | 20 | 46 | 2100 | 3500 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | | 14 | 93128486 | LED14BDT5G4840HE | 120-277 | 20 | 46 | 2150 | 4000 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| | | 14 | 93128487 | LED14BDT5G4850HE | 120-277 | 20 | 46 | 2150 | 5000 | 80 | - | 50,000 | >.9 | Yes | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 3 ft LED Glass T5 HE Tubes | | | | | | | | | | | | | | | | | |
| | | 11 | 93128488 | LED11BDT5G3830HE | 120-277 | 20 | 33 | 1600 | 3000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 11 | 93128490 | LED11BDT5G3835HE | 120-277 | 20 | 33 | 1650 | 3500 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 11 | 93128491 | LED11BDT5G3840HE | 120-277 | 20 | 33 | 1700 | 4000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 11 | 93128492 | LED11BDT5G3850HE | 120-277 | 20 | 33 | 1700 | 5000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| Ballast Bypass - 2 ft LED Glass T5 HE Tubes | | | | | | | | | | | | | | | | | |
| | | 9 | 93128494 | LED9BDT5G2/830HE | 120-277 | 20 | 22 | 1250 | 3000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 9 | 93128495 | LED9BDT5G2/835HE | 120-277 | 20 | 22 | 1300 | 3500 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 9 | 93128570 | LED9BDT5G2/840HE | 120-277 | 20 | 22 | 1350 | 4000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |
| | | 9 | 93128571 | LED9BDT5G2/850HE | 120-277 | 20 | 22 | 1350 | 5000 | 80 | - | 50,000 | >.9 | - | Yes | Damp | Double-Ended Power |

Ballast Bypass Glass Tubes - Single Ended - Type B

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated ¹ Life L70 (Hrs) | DLC® | UL | Location ³ Rating | Additional Information | |
|---|-------------|-------|------------|-----------------|---------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|------|-----|------------------------------|------------------------------|--|
| Ballast Bypass - 3 ft LED Glass Tubes | | | | | | | | | | | | | | | | | |
| T8 | G13 | 13 | 34472 | LED13BT8/G3/830 | 120-277 | 20 | 36 | 1700 | 3000K | 80+ | - | 50,000 | - | Yes | Damp | Non-shunted Sockets Required | |
| | G13 | 13 | 34474 | LED13BT8/G3/835 | 120-277 | 20 | 36 | 1800 | 3500K | 80+ | - | 50,000 | - | Yes | Damp | Non-shunted Sockets Required | |
| | G13 | 13 | 34477 | LED13BT8/G3/840 | 120-277 | 20 | 36 | 1850 | 4000K | 80+ | - | 50,000 | - | Yes | Damp | Non-shunted Sockets Required | |
| | G13 | 13 | 34478 | LED13BT8/G3/850 | 120-277 | 20 | 36 | 1900 | 5000K | 80+ | - | 50,000 | - | Yes | Damp | Non-shunted Sockets Required | |
| Ballast Bypass - 2 ft LED Glass Tubes | | | | | | | | | | | | | | | | | |
| | G13 | 8 | 34468 | LED8BT8/G2/830 | 120-277 | 20 | 24 | 950 | 3000K | 80+ | - | 50,000 | Yes | Yes | Damp | Non-shunted Sockets Required | |
| | G13 | 8 | 32125 | LED8BT8/G2/835 | 120-277 | 20 | 24 | 1000 | 3500K | 80+ | - | 50,000 | Yes | Yes | Damp | Non-shunted Sockets Required | |
| Ballast Bypass Type B LED U6-Tubes | | | | | | | | | | | | | | | | | |
| | 2G13 | 13 | 34480 | LED13BT8/U6/830 | 120-277 | 12 | 36 | 1800 | 3000K | 80+ | - | 50,000 | Yes | Yes | Damp | Non-shunted Sockets Required | |
| | 2G13 | 13 | 34481 | LED13BT8/U6/835 | 120-277 | 12 | 36 | 1850 | 3500K | 80+ | - | 50,000 | Yes | Yes | Damp | Non-shunted Sockets Required | |
| | 2G13 | 13 | 34484 | LED13BT8/U6/850 | 120-277 | 12 | 36 | 1900 | 5000K | 80+ | - | 50,000 | Yes | Yes | Damp | Non-shunted Sockets Required | |
| Ballast Bypass Type B LED U1-5/8-Tubes | | | | | | | | | | | | | | | | | |
| | 2G13 | 13 | 34487 | LED13BT8/U/830 | 120-277 | 15 | 22.5 | 1750 | 3000K | 80+ | - | 50,000 | Yes | Yes | Damp | Non-shunted Sockets Required | |
| | 2G13 | 13 | 34489 | LED13BT8/U/835 | 120-277 | 15 | 22.5 | 1800 | 3500K | 80+ | - | 50,000 | Yes | Yes | Damp | Non-shunted Sockets Required | |

In-Line Fuse - Type B

| Order Code | Description | Kit Contents |
|------------|---------------|----------------------------|
| 39017 | BT8-1AFUSEKIT | 1 Fuse (1A), 1 Fuse Holder |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

² Minimum order quantity = Case Quantity

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

LED REPLACEMENT LAMPS

Remote Plastic Tubes - Type C

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC [®] | UL | Location ³ Rating | Additional Information | |
|--|-----------|-------|------------|---------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|---|-----|------------------------------|----------------------------|--|
| Remote Plastic 4ft LED Tubes (Operates on Remote Driver) | | | | | | | | | | | | | See LumenChoice™ Section for Replacements | | | | |
| T8 | G13 | 13 | 38954 | LED15T8/4/830 | | 10 | 48 | 1950 | 3000K | 80+ | | 70,000 | Yes | Yes | Damp | Requires Driver, NSF Rated | |
| Remote Plastic 3ft LED Tubes (Operates on Remote Driver) | | | | | | | | | | | | | See LumenChoice™ Section for Replacements | | | | |
| | G13 | 16 | 82345 | LED18T8/3/840 | | 10 | 36 | 1800 | 4000K | 80+ | | 70,000 | - | Yes | Damp | Requires Driver, NSF Rated | |
| | G13 | 13 | 99694 | LED15T8/3/840 | | 20 | 36 | 1950 | 4000K | 80+ | | 70,000 | - | Yes | Damp | Requires Driver, NSF Rated | |
| Remote Plastic 2ft LED Tubes (Operates on Remote Driver) | | | | | | | | | | | | | See LumenChoice™ Section for Replacements | | | | |
| | G13 | 8 | 92997 | LED9T8/2/865 | | 20 | 24 | 1000 | 5000K | 80+ | | 70,000 | - | Yes | Damp | Requires Driver, NSF Rated | |
| Remote Plastic LED U Tubes (Operates on Remote Driver) | | | | | | | | | | | | | | | | | |
| | G13 | 12 | 28084 | LED14T8/U/835 | | 15 | 22.5 | 1700 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| | G13 | 12 | 28164 | LED14T8/U/840 | | 15 | 22.5 | 1700 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |

Remote Glass Tubes - Type C

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC [®] | UL | Location ³ Rating | Additional Information | |
|--|-----------|-------|------------|-------------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|------------------|-----|------------------------------|------------------------------------|--|
| Remote 4ft LED Glass Tubes (Operates on Remote Driver) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 18 | 62485 | LED21T8/G/4/840 | | 10 | 48 | 2700 | 4000K | 80+ | | 70,000 | Yes | Yes | Damp | Requires Driver | |
| | G13 | 18 | 62407 | LED21T8/G/4/840HL | | 10 | 48 | 3200 | 4000K | 80+ | | 70,000 | Yes | Yes | Damp | Requires Driver | |
| | G13 | 18 | 91498 | LED21T8/G/4/850US | | 20 | 48 | 2600 | 5000K | 80+ | | 70,000 | Yes | Yes | Damp | Requires Driver - Assembled in USA | |
| | G13 | 13 | 38944 | LED15T8/G/4/830 | | 10 | 48 | 1850 | 3000K | 80+ | | 70,000 | Yes | Yes | Damp | Requires Driver | |
| Remote 3ft LED Glass Tubes (Operates on Remote Driver) | | | | | | | | | | | | | | | | | |
| | G13 | 13 | 99687 | LED15T8/G/3/830 | | 20 | 36 | 1800 | 3000K | 80+ | | 70,000 | - | Yes | Damp | Requires Driver | |
| | G13 | 13 | 99689 | LED15T8/G/3/840 | | 20 | 36 | 1900 | 4000K | 80+ | | 70,000 | - | Yes | Damp | Requires Driver | |
| | G13 | 16 | 38258 | LED18T8/G/3/835 | | 20 | 36 | 1800 | 3500K | 80+ | | 70,000 | - | Yes | Damp | Requires Driver | |
| Remote 8ft LED Glass Tubes (Operates on Remote Driver) | | | | | | | | | | | | | | | | | |
| | Fa8 | 30 | 62326 | LED36T8/G/8/830 | | 20 | 96 | 4200 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| | Fa8 | 30 | 62327 | LED36T8/G/8/835 | | 20 | 96 | 4400 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| | Fa8 | 30 | 62329 | LED36T8/G/8/840 | | 20 | 96 | 4400 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| | Fa8 | 30 | 62349 | LED36T8/G/8/850 | | 20 | 96 | 4400 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| Remote Glass U6 Tubes (Operates on Remote Driver) | | | | | | | | | | | | | | | | | |
| | G13 | 13 | 43131 | LED15T8/G/U6/830 | | 12 | 22.5 | 1700 | 3000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| | G13 | 13 | 43135 | LED15T8/G/U6/835 | | 12 | 22.5 | 1800 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| | G13 | 13 | 43143 | LED15T8/G/U6/840 | | 12 | 22.5 | 1800 | 4000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| | G13 | 13 | 43145 | LED15T8/G/U6/850 | | 12 | 22.5 | 1800 | 5000K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |

Remote Glass Tubes - Type C

| Type | Base Type | Watts | Order Code | Description | Volts | Case ² Qty | MOL (In) | Lumens Initial | Initial Color Temp | CRI | Wattage Replacement | Rated Life ¹ L70 (Hrs) | DLC [®] | UL | Location ³ Rating | Additional Information | |
|--|-----------|-------|------------|------------------|-------|-----------------------|----------|----------------|--------------------|-----|---------------------|-----------------------------------|---|-----|------------------------------|------------------------|--|
| Remote 2ft LED Glass T5 HO Tubes (Operates on Remote Driver) | | | | | | | | | | | | | See LumenChoice™ Section for Replacements | | | | |
| T5 | G5 | 13 | 76150 | LED15T5/G/2/830 | | 20 | 22 | 1800 | 3000K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver | |
| | G5 | 13 | 76164 | LED15T5/G/2/835 | | 20 | 22 | 1850 | 3500K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver | |
| | G5 | 13 | 76129 | LED15T5/G/2/840 | | 20 | 22 | 1900 | 4000K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver | |
| Remote 4ft LED Glass T5 HE Tubes (Operates on Remote Driver) | | | | | | | | | | | | | See LumenChoice™ Section for Replacements | | | | |
| | G5 | 13 | 34182 | LED15T5/G4/835HE | | 20 | 46 | 1950 | 3500K | 80+ | | 50,000 | Yes | Yes | Damp | Requires Driver | |
| Remote 2ft LED Glass T5 HE Tubes (Operates on Remote Driver) | | | | | | | | | | | | | See LumenChoice™ Section for Replacements | | | | |
| | G5 | 8 | 34196 | LED9T5/G2/830HE | | 20 | 22 | 1100 | 3000K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver | |
| | G5 | 8 | 34197 | LED9T5/G2/835HE | | 20 | 22 | 1150 | 3500K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver | |
| | G5 | 8 | 34204 | LED9T5/G2/840HE | | 20 | 22 | 1200 | 4000K | 80+ | | 50,000 | - | Yes | Damp | Requires Driver | |

LED REPLACEMENT DRIVERS

Remote Drivers

| Type | Base Type | Max Watts | Order Code | Description | Volts | Case ² Qty | Output Current (A) | Frequency | Eff | Output | Output Voltage | Temp (Min) | Temp (Max) | Dimmable | Additional Information |
|-------------------|-----------|-----------|------------|----------------|----------|-----------------------|--------------------|-----------|-----|--------|----------------|------------|------------|----------|------------------------|
| Drivers - Dimming | | | | | | | | | | | | | | | |
| | | 72 | 63126 | LED36T8/DR/D2L | 120-277V | 10 | 1.06x2 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 113° F | Yes | Maximum 2 Tubes |
| | | 144 | 92013 | LED36T8/DR/D4L | 120-277V | 10 | 1.06x4 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 113° F | Yes | Maximum 4 Tubes |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

² Minimum order quantity = Case Quantity

³ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

Get more information at
www.gecurrent.com

LumenChoice® Type C LED Tube and Driver System

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time.

Current's LumenChoice® Type C system utilizes one LED tube to create multiple lumen options via the wattage of the selected LED driver. See reverse for LED tubes and driver product details.

Current offers two driver platforms:

- 1) **Regular Drivers**-choose the desired fixed-wattage option based on the desired lumen output, i.e. 12W, 15W, 21W. Available in Dimming and Non-Dimming.
- 2) **LumenChoice® Drivers**-adjust the wattage/lumen level on the driver, in the field i.e. toggle from 9W, 12W, 16W. This option simplifies bill of materials and inventory even further, and allows for making on-the-fly wattage/lumen adjustments at the point of installation. Low Watt drivers (LW) and High watt drivers (HW) come pre-set at 12W and 21W respectively and can easily be adjusted pre or post installation. All LumenChoice Drivers are 0-10V dimming also, allowing for even more control over lumen output and efficiency.

FEATURES

- T8 & T5 Configurations
- 2', 3' & 4' Tubes
- 1050 – 3000 lumens
- >120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K, 5000K and 6500K color temperatures
- T8 70,000 hr life rating & 7 year warranty
- T5 50,000 hr life rating & 5 year warranty
- UL and cUL
- Open or enclosed fixtures
- Damp rating
- Dimmable (0-10V with dimming driver)

PERFORMANCE BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 2.3X Longer Life vs LFL (70,000 vs. 30,000 hours)
- Better quality of light –instant on
- Glass-270° light distribution
- Easy disposal, non-hazardous waste

General Lamp Product Information and Performance Data

| General information | | | | | | |
|---------------------|-----------|-----|-----------|------------------|-----|-----------------|
| Lamp Type | Base Type | CRI | Case Pack | Rated life (L70) | UL | Location Rating |
| T8 | G13 | 80+ | 20 | 70,000 | Yes | Damp |
| T5 | G5 | 80+ | 20 | 50,000 | Yes | Damp |

Performance Data

The tables on the following pages show the LumenChoice LED tubes in combination with regular fixed wattage driver options and LumenChoice® driver options that will result in different lumen levels.

LumenChoice® TYPE C LED TUBE AND DRIVER SYSTEM

Lamp Performance-LumenChoice® Drivers

| 2'-4' Glass T8 and LumenChoice® Driver | | | | | | | | | | |
|--|------------------|-------|------------------|----------------|------|-------|--------------------|------|--|-------|
| 4ft Glass | | | | Driver | Low | Watt | LumenChoice Driver | | 21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW | |
| Lamp Product Code | Lamp Description | CCT | DLC ⁶ | Wattage | 8W | 9W | 12W | 15W | 16.5W | Notes |
| 34211 | LEDT8/LC/G/4/830 | 3000K | Yes | Initial Lumens | 1050 | 1150 | 1550 | 1900 | 2000 | |
| 34227 | LEDT8/LC/G/4/835 | 3500K | Yes | | 1050 | 1200 | 1600 | 1950 | 2050 | |
| 34235 | LEDT8/LC/G/4/840 | 4000K | Yes | | 1050 | 1200 | 1600 | 1950 | 2050 | |
| 34239 | LEDT8/LC/G/4/850 | 5000K | Yes | | 1050 | 1200 | 1600 | 1950 | 2050 | |
| 4ft Glass | | | | Driver | High | Watt | LumenChoice Driver | | 21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW | |
| Lamp Product Code | Lamp Description | CCT | DLC ⁶ | Wattage | 18W | 19.5W | 21W | 23W* | 25W* | Notes |
| 34211 | LEDT8/LC/G/4/830 | 3000K | Yes | Initial Lumens | 2250 | 2500 | 2650 | 2850 | 2950 | |
| 34227 | LEDT8/LC/G/4/835 | 3500K | Yes | | 2300 | 2550 | 2700 | 2900 | 3000 | |
| 34235 | LEDT8/LC/G/4/840 | 4000K | Yes | | 2300 | 2550 | 2700 | 2900 | 3000 | |
| 34239 | LEDT8/LC/G/4/850 | 5000K | Yes | | 2300 | 2550 | 2700 | 2900 | 3000 | |
| 3ft Glass | | | | Driver | Low | Watt | LumenChoice Driver | | 21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW | |
| Lamp Product Code | Lamp Description | CCT | DLC ⁶ | Wattage | 8W | 9W | 12W | 15W | 16.5W | Notes |
| 36394 | LEDT8/LC/G/3/830 | 3000K | Yes | Initial Lumens | 1050 | 1150 | 1550 | 1900 | 2050 | |
| 36395 | LEDT8/LC/G/3/835 | 3500K | Yes | | 1050 | 1200 | 1600 | 1950 | 2100 | |
| 36398 | LEDT8/LC/G/3/840 | 4000K | Yes | | 1050 | 1200 | 1600 | 1950 | 2100 | |
| 36401 | LEDT8/LC/G/3/850 | 5000K | Yes | | 1050 | 1200 | 1600 | 1950 | 2100 | |
| 2ft Glass | | | | Driver | Low | Watt | LumenChoice Driver | | 21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW | |
| Lamp Product Code | Lamp Description | CCT | DLC ⁶ | Wattage | 8W | 9W | 12W | | | Notes |
| 36406 | LEDT8/LC/G/2/830 | 3000K | - | Initial Lumens | 1000 | 1100 | 1450 | | | |
| 36408 | LEDT8/LC/G/2/835 | 3500K | Yes | | 1050 | 1200 | 1550 | | | |
| 36409 | LEDT8/LC/G/2/840 | 4000K | Yes | | 1050 | 1200 | 1550 | | | |
| 36413 | LEDT8/LC/G/2/850 | 5000K | Yes | | 1050 | 1200 | 1550 | | | |

LumenChoice® TYPE C LED TUBE AND DRIVER SYSTEM

Lamp Performance-Regular Drivers

| 4' HO and Regular Driver | | | | | | | | | | |
|--------------------------|------------------|-------|------------------|----------------|---------------|--|--|--|--|--|
| 4ft Glass | | | | Driver | LED36T8/DR/XX | | | | | |
| Lamp Product Code | Lamp Description | CCT | DLC ⁶ | Wattage | Notes | | | | | |
| 38926 | LEDT5/LC/G/4/830 | 3000K | Yes | Initial Lumens | 36W | | | | | |
| 38934 | LEDT5/LC/G/4/835 | 3500K | Yes | | 4300 | | | | | |
| 38940 | LEDT5/LC/G/4/840 | 4000K | Yes | | 4350 | | | | | |
| 38946 | LEDT5/LC/G/4/850 | 5000K | Yes | | 4400 | | | | | |

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LumenChoice® TYPE C LED TUBE AND DRIVER SYSTEM

Lamp Performance-LumenChoice® Drivers

| 2'-4' T5 HO and LumenChoice® Driver | | | | | | | | | | |
|-------------------------------------|------------------|-------|------|----------------|------------------------------|-------|------|---|-------|-------|
| 4ft Glass | | | | Driver | High Watt LumenChoice Driver | | | 21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW *4L driver Max Setting at 21W per lamp | | |
| Lamp Product Code | Lamp Description | CCT | DLC* | Wattage | 18W | 19.5W | 21W | 23W* | 25W* | Notes |
| 38926 | LEDT5/LC/G/4/830 | 3000K | - | Initial Lumens | 2350 | 2500 | 2650 | 2850 | 3050 | |
| 38934 | LEDT5/LC/G/4/835 | 3500K | - | | 2400 | 2550 | 2750 | 2950 | 3150 | |
| 38940 | LEDT5/LC/G/4/840 | 4000K | - | | 2450 | 2600 | 2850 | 3050 | 3250 | |
| 38946 | LEDT5/LC/G/4/850 | 5000K | - | | 2450 | 2600 | 2850 | 3050 | 3250 | |
| 3ft Glass | | | | Driver | High Watt LumenChoice Driver | | | 21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW | | |
| Lamp Product Code | Lamp Description | CCT | DLC* | Wattage | 18W | 19.5W | 21W | 23W* | 25W* | Notes |
| 38947 | LEDT5/LC/G/3/830 | 3000K | - | Initial Lumens | 2300 | 2450 | 2600 | 2800 | 3000 | |
| 38948 | LEDT5/LC/G/3/835 | 3500K | - | | 2350 | 2500 | 2700 | 2900 | 3100 | |
| 38949 | LEDT5/LC/G/3/840 | 4000K | - | | 2400 | 2550 | 2800 | 3000 | 3200 | |
| 38955 | LEDT5/LC/G/3/850 | 5000K | - | | 2400 | 2550 | 2800 | 3000 | 3200 | |
| 2ft Glass | | | | Driver | Low Watt LumenChoice Driver | | | 21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW | | |
| Lamp Product Code | Lamp Description | CCT | DLC* | Wattage | 8W | 9W | 12W | 15W | 16.5W | Notes |
| 38968 | LEDT5/LC/G/2/830 | 3000K | - | Initial Lumens | 1000 | 1200 | 1550 | 1800 | 2000 | |
| 38980 | LEDT5/LC/G/2/835 | 3500K | - | | 1050 | 1200 | 1600 | 1850 | 2050 | |
| 38983 | LEDT5/LC/G/2/840 | 4000K | - | | 1100 | 1250 | 1650 | 1900 | 2100 | |
| 38992 | LEDT5/LC/G/2/850 | 5000K | - | | 1100 | 1250 | 1650 | 1900 | 2100 | |

LED REPLACEMENT DRIVERS

Regular Remote Drivers

| Type | Max Watts | Order Code | Description | Volts | Case ¹ Qty | Output Current (A) | Frequency | Eff | Output | Output Voltage | Temp (Min) | Temp (Max) | 0-10V Dimmable | Additional Information |
|----------------------------|-----------|----------------|-------------|-------|-----------------------|--------------------|-----------|-----|--------|----------------|------------|------------|-----------------|------------------------|
| Lichtech Drivers - Dimming | | | | | | | | | | | | | | |
| 72 | 63126 | LED36T8/DR/D2L | 120-277V | 10 | 1.06x2 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 113° F | Yes | Maximum 2 Tubes | |
| 144 | 92013 | LED36T8/DR/D4L | 120-277V | 10 | 1.06x4 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 113° F | Yes | Maximum 4 Tube | |

LumenChoice® Drivers

| Type | Max Watts | Order Code | Description | Volts | Case ¹ Qty | Max Output Current (A) | Frequency | Eff | Output | Output Voltage | Temp (Min) | Temp (Max) | 0-10V Dimmable | Additional Information |
|---------------------------------|-----------|---------------|-------------|-------|-----------------------|------------------------|-----------|-----|--------|----------------|------------|------------|---|------------------------|
| Lumen Choice® Drivers - Dimming | | | | | | | | | | | | | | |
| 33 | 21378 | LED/DR/D2L/LW | 120-277V | 10 | 0.48x2 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 104° F | Yes | Max 2 Tubes: 12W per tube default setting | |
| 66 | 21379 | LED/DR/D4L/LW | 120-277V | 10 | 0.48x4 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 104° F | Yes | Max 4 Tubes: 12W per tube default setting | |
| 50 | 21383 | LED/DR/D2L/HW | 120-277V | 10 | 0.72x2 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 104° F | Yes | Max 2 Tubes: 21W per tube default setting | |
| 84 | 21392 | LED/DR/D4L/HW | 120-277V | 10 | 0.72x4 | 50/60 Hz | >.9 | DC | 26-34V | -4° F | 104° F | Yes | Max 4 Tubes: 21W per tube default setting | |

¹ Minimum order quantity = Case Quantity

Current's Hybrid Driver & Type A LED Tube (UL Type C System)

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time.

Current's Type A LED tubes and hybrid drivers create a UL Type C system to maximize rebate potential. Current offers compatible 2', 3', and 4' tubes rated at 70,000 hours and a value 4' tube rated at 50,000 hours.

Drivers are non-dimmable and must be paired with the exact lamps listed below to qualify as UL Type C system. Electrical ratings for the 2-lamp and 4-lamp hybrid drivers:

| Order Code | Driver Description | Input (V) | Max Input (W) | Max Input (A) | Output (V) | Max Output (W) | Output (A) | PF | THD | Frequency (Hz) |
|------------|--------------------|-----------|---------------|---------------|------------|----------------|-------------|------|-----|----------------|
| 21418 | LED-ET8/DR/2L | 120-277 | 35 | 0.4 | 100-160 | 32 | 0.14-0.17x2 | >0.9 | <15 | 50/60 |
| 21506 | LED-ET8/DR/4L | 120-277 | 64 | 0.8 | 100-160 | 60 | 0.14-0.17x4 | >0.9 | <15 | 50/60 |

Lamp performance with the 2-lamp driver for 2 lamps (2L) and one lamp (1L):

| Base Type | Order Code | Lamp Description | DLC® | UL | Lamp Watts | Lumens Per Lamp (2L) | System Watts (2L) | Lumens Per Lamp (1L) | System Watts (1L) |
|-----------|------------|------------------|------|-----|------------|----------------------|-------------------|----------------------|-------------------|
| G13 | 35775 | LED8ET8/G/2/830 | - | Yes | 8.5 | 1300 | 21 | 1950 | 19 |
| G13 | 35776 | LED8ET8/G/2/835 | - | Yes | 8.5 | 1350 | 21 | 2150 | 19 |
| G13 | 35778 | LED8ET8/G/2/840 | - | Yes | 8.5 | 1400 | 21 | 2300 | 19 |
| G13 | 35779 | LED8ET8/G/2/850 | - | Yes | 8.5 | 1350 | 21 | 2200 | 19 |
| G13 | 35783 | LED11T8/G/3/830 | - | Yes | 10.5 | 1450 | 24 | 2200 | 21 |
| G13 | 35784 | LED11T8/G/3/835 | - | Yes | 10.5 | 1500 | 24 | 2250 | 21 |
| G13 | 35788 | LED11T8/G/3/840 | - | Yes | 10.5 | 1500 | 24 | 2300 | 21 |
| G13 | 35789 | LED11T8/G/3/850 | - | Yes | 10.5 | 1550 | 24 | 2300 | 21 |
| G13 | 34277 | LED10ET8/G/4/830 | - | Yes | 10 | 1500 | 23 | 2350 | 20 |
| G13 | 34279 | LED10ET8/G/4/835 | Yes | Yes | 10 | 1600 | 23 | 2650 | 20 |
| G13 | 34280 | LED10ET8/G/4/840 | Yes | Yes | 10 | 1700 | 23 | 2800 | 20 |
| G13 | 34282 | LED10ET8/G/4/850 | Yes | Yes | 10 | 1650 | 23 | 2700 | 20 |
| G13 | 34283 | LED14ET8/G/4/830 | Yes | Yes | 13 | 1950 | 30 | 2700 | 23 |
| G13 | 34289 | LED14ET8/G/4/835 | Yes | Yes | 13 | 2000 | 30 | 2700 | 23 |
| G13 | 34291 | LED14ET8/G/4/840 | Yes | Yes | 13 | 2050 | 30 | 2850 | 23 |
| G13 | 34300 | LED14ET8/G/4/850 | Yes | Yes | 13 | 2050 | 30 | 2850 | 23 |
| G13 | 35790 | LED15ET8/G/4/830 | Yes | Yes | 13.5 | 1950 | 23 | 2750 | 23 |
| G13 | 35791 | LED15ET8/G/4/835 | Yes | Yes | 13.5 | 2000 | 23 | 2800 | 23 |
| G13 | 35793 | LED15ET8/G/4/840 | Yes | Yes | 13.5 | 2100 | 30 | 2900 | 23 |
| G13 | 35797 | LED15ET8/G/4/850 | Yes | Yes | 13.5 | 2100 | 30 | 2900 | 23 |
| G13 | 35798 | LED15ET8/G/4/865 | - | Yes | 13.5 | 2100 | 30 | 2900 | 23 |

Lamp performance with the 4-lamp driver for 4 lamps (4L) and three lamps (3L):

| Base Type | Order Code | Lamp Description | DLC® | UL | Voltage | Lamp Watts | Lumens Per Lamp (4L) | System Watts (4L) | Lumens Per Lamp (3L) | System Watts (3L) |
|-----------|------------|------------------|------|-----|----------|------------|----------------------|-------------------|----------------------|-------------------|
| G13 | 35775 | LED8ET8/G/2/830 | - | Yes | 120-277V | 8.5 | 1300 | 41 | 1450 | 37 |
| G13 | 35776 | LED8ET8/G/2/835 | - | Yes | 120-277V | 8.5 | 1300 | 41 | 1550 | 37 |
| G13 | 35778 | LED8ET8/G/2/840 | - | Yes | 120-277V | 8.5 | 1400 | 41 | 1650 | 37 |
| G13 | 35779 | LED8ET8/G/2/850 | - | Yes | 120-277V | 8.5 | 1350 | 41 | 1600 | 37 |
| G13 | 35783 | LED11T8/G/3/830 | - | Yes | 120-277V | 10.5 | 1450 | 49 | 1600 | 43 |
| G13 | 35784 | LED11T8/G/3/835 | - | Yes | 120-277V | 10.5 | 1500 | 49 | 1700 | 43 |
| G13 | 35788 | LED11T8/G/3/840 | - | Yes | 120-277V | 10.5 | 1500 | 49 | 1700 | 43 |
| G13 | 35789 | LED11T8/G/3/850 | - | Yes | 120-277V | 10.5 | 1550 | 49 | 1750 | 43 |
| G13 | 34277 | LED10ET8/G/4/830 | - | Yes | 120-277V | 10 | 1500 | 47 | 1450 | 41 |
| G13 | 34279 | LED10ET8/G/4/835 | Yes | Yes | 120-277V | 10 | 1600 | 47 | 1500 | 41 |
| G13 | 34280 | LED10ET8/G/4/840 | Yes | Yes | 120-277V | 10 | 1700 | 47 | 1600 | 41 |
| G13 | 34282 | LED10ET8/G/4/850 | Yes | Yes | 120-277V | 10 | 1650 | 47 | 1550 | 41 |
| G13 | 34283 | LED14ET8/G/4/830 | Yes | Yes | 120-277V | 13 | 1900 | 58 | 2150 | 45 |
| G13 | 34289 | LED14ET8/G/4/835 | Yes | Yes | 120-277V | 13 | 2000 | 58 | 2200 | 45 |
| G13 | 34291 | LED14ET8/G/4/840 | Yes | Yes | 120-277V | 13 | 2050 | 58 | 2250 | 45 |
| G13 | 34300 | LED14ET8/G/4/850 | Yes | Yes | 120-277V | 13 | 2050 | 58 | 2250 | 45 |
| G13 | 35790 | LED15ET8/G/4/830 | Yes | Yes | 120-277V | 13.5 | 1950 | 60 | 2200 | 51 |
| G13 | 35791 | LED15ET8/G/4/835 | Yes | Yes | 120-277V | 13.5 | 2000 | 60 | 2250 | 51 |
| G13 | 35793 | LED15ET8/G/4/840 | Yes | Yes | 120-277V | 13.5 | 2050 | 60 | 2300 | 51 |
| G13 | 35797 | LED15ET8/G/4/850 | Yes | Yes | 120-277V | 13.5 | 2050 | 60 | 2300 | 51 |
| G13 | 35798 | LED15ET8/G/4/865 | - | Yes | 120-277V | 13.5 | 2050 | 60 | 2300 | 51 |