

# AHG Series

LED Hazardous Location Luminaire



Enclosed and Gasketed for Class 1, Division 2 environments

Latches, Polyacetal (POM) Standard (Stainless Steel, Tamper resistant options available)

Non-porous gasketing ensures a tight seal


Durable Fiberglass UL 5VA Housing




F1 Weatherability rating, suitable for indoor or outdoor use

Lens Options available in Clear or Diffuse Acrylic or Polycarbonate

Available in 4 or 8 foot lengths



Up to 8,000 nominal lumens



Up to 16,000 nominal lumens



Surface Mounting Brackets (Included)

# Safe, Reliable & Improves Operating Costs

The Albeo® AHG LED fixture is an enclosed and gasketed hazardous location LED product. AHG is standard Class 1, Division 2, Groups A, B, C and D. It is offered in 4' and 8' lengths with lumen packages ranging from 5,000-16,000 lumens.

## Applications

- Chemical Processing Facilities
- Ethanol Refineries
- Manufacturing Facilities
- Petroleum Refineries
- Power Generation Facilities
- Wastewater and Water Treatment Facilities



**Size:** 4ft, 8ft

**Lens:** Diffused and Clear Acrylic, and Polycarbonate

**Housing:** Formed UL 5VA Fiberglass

**Finish:** White Painted Parts

**Color Temp:** 3000K, 3500K, 4000K and 5000K

**CRI:** 80

**Lumen Output:** 5,000 to 16,000

**Dimming:** Continuous 0-10V Dimming

**Voltage:** 120-277V; 347V; 480V



HAZARDOUS ENVIRONMENTS



WET RATED



IP65  
IP66  
IP67



## Want to learn more?

For Specific product technical questions, contact: [lightingproinfo@gecurrent.com](mailto:lightingproinfo@gecurrent.com)