



CPA039

LATEX
**CARPET PAD
ADHESIVE**

1. PRODUCT NAME

Capitol® CPA039 Latex Carpet Pad Adhesive

2. MANUFACTURER

Capitol® Flooring Products
Dalton, GA 30720
www.capitolflooringproducts.com
866-435-8665

3. DESCRIPTION

Capitol® CPA039 Latex Carpet Pad Adhesive is a solvent-free, latex-based enviro-friendly carpet pad adhesive developed to quickly bond carpet pads to subfloors in stretch-in carpet installations. CPA039 provides a permanent bond to porous and non-porous substrates. VOC: < 1 g/L

FEATURES AND BENEFITS

- Fast setting, it quickly bonds carpet pads to sub floors
- Allows for stretching of carpet without carpet cushion wrinkling and slippage
- Protected by AMP Guard® to inhibit the growth of mold, mildew and odor-causing bacteria

USES

Carpet padding— rebonded or synthetic and rubber foam. Test adhesive with carpet pad prior to installation for any pads not listed.

SUBSTRATES

Install over porous and non-porous substrates such as concrete, vinyl composition tile (free of wax), primed gypcrete, terrazzo, APA underlayment grade plywood, particleboard and hardboard

LIMITATIONS

- For interior use only
- Always follow pad manufacturer's specific installation guidelines.
- Ensure adequate ventilation during flooring installation.
- Refer to Safety Data Sheet, www.capitolflooringproducts.com, industry standards, and manufacturer's guidelines and specific recommendations prior to installation for additional information.



CPA039

L A T E X

CARPET PAD ADHESIVE

4. TECHNICAL DATA

Product Type:	Latex Type
Color:	Light Tan
Coverage:	Up to 700 lineal feet per gallon
Open Time:	Up to 15 minutes
Working Time:	Up to 45 minutes
VOC:	< 1 g/L
Shelf Life:	1 year in unopened container
Storage:	Protect from freezing

5. INSTRUCTION

Preparation

Subfloors must be structurally sound, dry, smooth, flat ($\leq 3/16''$ within 10'), level and free of excess moisture/alkali and all substances (oil, wax, grease, paint, oil based sealers, adhesive residue, etc.) that may inhibit the bond of the adhesive or the performance of the flooring or its installation. All substrate cracks, chips, holes, joints, high spots and irregularities must be adequately repaired. Expansion or other moving joints must not be filled or covered with flooring. Patching compounds must be suitable for the use application, cement based and polymer-modified, and applied according to the manufacturer's instructions.

Installation

Materials and area temperature must be between 65-95°F with a maximum RH of 65% for 48 hours before and during installation as well as for 72 hours afterward. Large temperature or humidity increases or decreases can affect the flooring and performance of the installation.

Pre-cut the carpet padding and lay it loosely in place. Pull the padding back from the walls and seams to expose the substrate. Using a zig zag motion, pour a continuous bead of adhesive around the perimeter, under all padding seams and throughout the field.

Wait approximately 10-15 minutes (or longer for non-porous materials or substrates) and then place carpet pad into the adhesive. The amount of time in which you have to place the padding will vary with temperature and humidity.

After installation, restrict foot traffic and moving of heavy objects for 24-48 hours to allow adhesive to cure properly. Premature traffic can cause installation failure.

6. AVAILABILITY

Packaging

CPA039 | Gal Plastic Bottle 024043670693

7. WARRANTY

Capitol[®] offers a limited product warranty on this product when installed in accordance with the printed specifications. Ask your sales associate, visit capitolflooringproducts.com or call (866) 435-8665 for a copy of the warranty.

8. MAINTENANCE

CLEAN UP: Fresh adhesive – warm soapy water on a clean cloth.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth. **DO NOT POUR DIRECTLY ONTO FLOORING.**

STORAGE: Protect from freezing. Does not require thinning. Store in an unopened container for up to one year from date of manufacture

9. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at 706-277-5294 or visit www.capitolflooringproducts.com.

10. FILING SYSTEM

Division 9