

EU-Type Examination Certificate

No. P5A 106210 0005 Rev. 00

Holder of Certificate: **MSA Europe GmbH**

Schlüsselstraße 12
8645 Rapperswil-Jona
SWITZERLAND

Product: **PPE against fall from a height**
Full Body Harness EN 361, belt for work
positioning EN 358

Model(s): **V-FLEX**
in different versions

Tested according to: DIN EN 361:2002
DIN EN 358:2019

The Certification Body of TÜV SÜD Product Service GmbH confirms that the listed product fulfils the basic requirements with Annex V (Module B) of Regulation (EU) 2016/425 on personal protective equipment according to Article 19 (PPE of category III). This certificate refers only to the submitted sample for testing and certification and on its technical documentation. The validity of this certificate based on an ongoing surveillance in accordance with Module C2 or D of Regulation (EU) 2016/425 by a Notified Body. For details see: www.tuvsud.com/ps-cert

Test report no.: 713348084-2

Valid from: 2025-12-10

Valid until: 2030-12-09

Date, 2025-12-10



(Daniel Würtz)

EU-Type Examination Certificate

No. P5A 106210 0005 Rev. 00

Parameters:

previous EU-type Examination Certificate:	P5A 106210 0003 Rev. 00
previous Technical Report:	713172848

Construction:	Full Body Harness in different versions; made of 45mm PES webbing with PES multifilament yarn
Versions:	- V-FLEX Standard (art.-no.: 10211350, 10211351, 10211352): Full Body Harness with 1 sternal attachment point for fall arrest EN 361 and 1 dorsal attachment point for fall arrest EN 361; with shoulder/back and leg loop paddings - V-FLEX Construction (art.-no.: 10211353, 10211354, 10211355): Full Body Harness with 1 sternal attachment point for fall arrest EN 361, 1 dorsal attachment point for fall arrest EN 361 and 2 side attachment points for work positioning EN 358; with shoulder/back and leg loop paddings and rigid waist belt padding (up to 100mm width)
Adjustment:	- all versions: adjustable in chest harness over 2pc. steel slide-block buckles; in both leg loops over 2pc. aluminium click-lock closure buckles; webbing ends sewn with plastic protection and additional webbing keeper - additional for version V-FLEX Construction: adjustable in chest harness/waist belt fixation webbing over 2pc. aluminium slide-block buckles; in front waist belt over 1pc. aluminium click-lock closure buckles
Attachment Points:	availability depends on the different versions: - upper front: EN 361 made of aluminium click-lock closure buckle with D-ring, attached to shoulder webbing and chest webbing - back: EN 361 made of aluminium angled D-ring, in crossing webbing of shoulder straps - waist side: 2x EN 358 for work positioning made of aluminium angled D-ring, in waist belt fixation
load bearing stitchings:	in optical contrast to webbing
Extras:	- all versions: 2 dorsal fall arrest indicators - additional for version V-FLEX Construction: metallic gear loops at rear waist belt padding;
Marking:	manufacturer; manufacturer address; type; article no.; serial no.; size; waist belt size range in cm; manufacturing month + year; CE-marking; "read-instruction"- pictogram; EN 361:2002; EN 358:2018; "A" on fall arrest attachment elements; materials; pictograms of correct use of adjusting elements;
Sizes:	XS / Standard / XL

EU-Type Examination Certificate

No. P5A 106210 0005 Rev. 00

V-FLEX Standard



V-FLEX Construction

