

3M Science. Applied to Life.™

Challenging environmental conditions have met their match.

3M™ Air and Vapour Through Wall Flashing Tape 3015TWF

Save time and hassles with 3M™ Air and Vapour Through Wall Flashing Tape for your through wall flashing and damp proof course applications. It features an aggressive, high tack acrylic pressure sensitive adhesive that does not require primer on most surfaces. Easy-to-handle rolls allow it to be applied in just one step by a single applicator—helping to reduce labour time by up to 20%.



-18 to 66°C
application temperature.

Adheres
to damp surfaces.

Ultra tough
puncture and abrasion resistance.

Let's Build Smarter.



Benefits

- Specially designed for use as a through wall flashing and damp proof course
- Helps reduce labour time by up to 20%—easy-to-handle roll allows one-step application by a single worker
- Hot and cold temperature application—apply in temperatures -18° to 66°C (0° to 150°F)
- Designed to withstand wear and tear—exceptional puncture and abrasion resistance
- Acrylic-based adhesive sticks to a wide range of building materials—concrete, metal and wood
- No primer required—pressure sensitive adhesive technology eliminates the time and materials usually required for applying air barriers
- Adheres to damp surfaces
- UV resistant up to 24 months

Extended temperature range increases production.

- Productivity in all conditions. Application temperatures from -18° to 66°C (0° to 150°F)
- Service temperature range from -40° to 116°C (-40° to 240°F)

Works in all weather.

High-tack acrylic adhesive sticks to damp surfaces that have not absorbed water.

Tough enough to take it.

Get the exceptional puncture and abrasion resistance you need to help ensure successful air barrier installations.

3M Industrial Adhesives and Tapes Division
3M Canada
P.O. Box 5757
London, ON N6A 4T1

1-800-364-3577
3M.ca/AirBarrier

Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. **Limitation of Liability:** Except for the limited remedy above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted.

3M and 3M Science. Applied to Life. are trademarks of 3M. Used under license in Canada. © 2021, 3M. All rights reserved.
2106-20921 E

Let's Build Smarter.