



DBI-SALA® CHOKING GIRDER LOOP HEAVY DUTY TEMPORARY ANCHORAGE POINT

REF: KM419, KM421

DESCRIPTION

Choking Girder Loop heavy duty temporary anchorage point CE marked and conforming to the standard EN795 CLASS B.

Available in 2 lengths, 90 cm and 200 cm, they are equipped at one end with stainless steel half round D-links and at the other end with stainless steel triangular links. The triangle may be passed through the D-link to choke on the structure on which it is installed. It may also be used as a simple Girder loop by connecting the triangle and the D-link together.

Suitable for installation on a wide range of sizes of structure.

6 mm thick cloth reinforced rubber anti slip interior surface, which also provides an extremely high level of protection to the webbing when installed on structures of metal and concrete.

MAIN FEATURES

- May be used as a Choking Girder Loop or as Simple Girder Loop
- Portable, simple and quick to fit
- Suitable for most supporting structures
- Fits a wide range of sizes of structures
- Rubber interior offers extremely high level of protection
- Individual serially numbered, for quality control purposes

APPLICATIONS

Designed to be used as a temporary anchorage point for Personal Protective Equipment, ideal for use in the following areas

- Mast tower work
- Structural steel
- Scaffolding/steel work
- Rope Access, Tree surgery
- Rescue

ASSOCIATED PRODUCTS

This anchorage point should always be used with

- A DBI-SALA® connector or karabiner conforming to EN362

It can be used with the following products

- A DBI-SALA® energy absorbing lanyard (EN355)
- A DBI-SALA® retractable fall arrest device (EN360)
- A DBI-SALA® temporary vertical life line (EN353-2)
- The DBI-SALA® RPD access and rescue system KA1PRPD
- The DBI-SALA® "Rescumatic" device KG1P100

Restraint - **NOT FOR FALL ARREST PURPOSES**

- A DBI-SALA® restraint lanyard conforming to EN354

CERTIFICATION

EN795 Class B





DBI-SALA® CHOKING GIRDER LOOP HEAVY DUTY TEMPORARY ANCHORAGE POINT

REF: KM419, KM421



	OVERALL LENGTH	NET WEIGHT	 SIMPLE	 CHOKE	 SIMPLE	 CHOKE
KM419	90 cm	445 g	23 cm diameter	21 cm diameter	18 cm by 18 cm	16 cm by 16 cm
KM421	200 cm	860 g	60 cm diameter	55 cm diameter	40 cm by 40 cm	37 cm by 37 cm

TECHNICAL SPECIFICATION

Webbing - 45 mm width, 100% Polyester, Breaking strength >3400 daN

- Thread - High strength, 100% Polyester
- Triangular links - Breaking strength > 2200 daN, 8 mm diameter bar, stainless steel 316 with polished finish

- Half round D-links - Breaking strength > 3750 daN, 7 mm diameter bar, stainless steel 316 with polished finish.
- Individual serially numbered
- System breaking Strength >15 kN

OPTIONS

The KM418 is a simple Girder loop, constructed in a similar way as the KM419, but with 2 triangles, and cannot be choked. It has an over all length of 90 cm.

CERTIFICATION

EN 795 Class B



Capital Safety (Northern Europe) Ltd
5a Merse Road, North Moons Moat
Redditch, B98 9HL, UK
t: +44 (0) 1527 548 000 f: +44 (0) 1527 591 000



All rights reserved. The material contained herein is copyrighted; no part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording or otherwise without prior written permission from Capital Safety. Capital Safety Group (Northern Europe) Limited, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT, Registered in England and Wales No. 1918922.