



NEW

RESILIENT

SPECS

320 FPS

AXLE-TO-AXLE | **30"**

BRACE HEIGHT | **6"**

DRAW WEIGHT | **30-50/50-70 LBS.**

DRAW LENGTH | **23.5"-28"**

LET OFF | **80%, 85%**

FEATURES

- RTH PACKAGE WITH INTEGRATED MOUNTING SYSTEM[®] REST MOUNT AND PICATINNY SIGHT MOUNT
- NEW EKO 2 SD CAM DESIGNED FOR 23.5"–28" DRAW LENGTHS WITH ADJUSTABLE 80% OR 85% LET-OFF
- IN-LIMB AND IN-RISER DAMPENING SYSTEM FOR REDUCED VIBRATION
- MAXIMUM VERSATILITY WITH 30" ATA AND 6" BRACE HEIGHT
- STRING STOP SYSTEM FOR A VIBRATION-FREE FEEL

FINISHES



RTH
READY TO HUNT

- Trophy Ridge Integrated 4-Pin Sight
- Trophy Ridge IMS™ Whisker Biscuit
- Trophy Ridge 5 Arrow Quiver
- Trophy Ridge Stabilizer & Sling
- Peep Sight & D Loop

AVAILABLE IN:

