

Version 5.1 – 06.19.25

Full Product Description

Oregon® SpeedCut™ Max 3/8" Saw Chain (70TXL) fits: [brand 1], [brand 2], [brand 3]

Specifications:

- Pitch: 3/8"
- Full chisel
- Gauge: .050", .058", .063"
- Standard sequence
- Saw size: 60-100+ cc
- Bar lengths: 16"-32"

For arborists and woodcutting professionals looking for reliable cutting in complex or confined situations, the 70TXL saw chain is fast, smooth, and is low kickback. The full chisel cutter with patented grind geometry delivers increased speed, while an optimized bumper drive link reduces kickback – without sacrificing an ounce of performance or responsiveness in the cut. No more compromises, just fast, smooth cutting with low kickback.

- **Fits: TBD**
- Full Chisel - An aggressive cutting corner and optimized gullet are achieved with a patented grind geometry to deliver increased speed, chip clearance, and overall performance straight out of the box
- Optimized Bumper Drive Link Design - Engineered to work with the cutter to provide greater responsiveness and kickback control without sacrificing an ounce of performance.
- Certified Low Kickback - This saw chain meets the industry standards for low kickback chain certification when tested according to the provisions of ANSI B175.1 and CSA Z62.3.
- Low Vibration Heel – Small space between the saw chain and the guide bar, which dissipates much of the energy – acting as a shock absorber. Reduces vibrations by 25% or more.

- Oregon® OCS-01 Steel - Custom-formulated alloy steel for greater durability in all weather environments. Resists fractures during extreme temperature changes when processing cold or frozen timber. Induction-hardened rivets for greater wear resistance.
- Enhanced Cutters - Chrome plating maintains the cutting edge longer. Heat treating and shot peening strengthen and reduce breakage.
- *(could be part of Enhanced Cutters)* Blued Components - Provides corrosion resistance on cutters and tie straps.
- LubriTec™ Oiling System extends chain and bar life - Tie strap reservoirs keep oil on the chain, and the integrated design with Oregon® guide bars enhances LubriTec performance, keeping high-friction areas well-lubricated to reduce wear.
- Top-Plate Filing Indicators – Show the correct angle to make sharpening easier and more accurate, also indicates end of life
- Maintain Sharpness with Ease - The 70TXL cutter is engineered and manufactured to pair with a 7/32" round file — achieving the perfect hook angle with ease.
- Convenient Sharpening Tip - Gold loop start indicator makes sharpening easier with start and stop identification
- Manufacturing Excellence - Oregon Tool's advanced manufacturing facilities and highly-skilled technicians combine to deliver industry-leading saw chain that meets professional demands.
- Rigorous Quality Control Teams – Inspect and verify every last detail to ensure all 38 saw chain quality standards are achieved
- Limited Warranty – Oregon Tool, Inc. warrants its products to be free from defects in materials and workmanship for as long as it is owned by the original retail purchaser.