

TECHNICAL DATA SHEET

3813 Protective film

Full surface self-adhesive standard film for various short-term covering work.

PROPERTIES

- Full surface self-adhesive
- Standard LDPE film
- Available in blue/transparent

AREA OF USE

- For protection for work by painters, plasterers and facade cleaning work
- Applicable for glass surfaces, stone and carpet flooring as well as staircases
- Take care with porous substrates such as marble and natural stone (terracotta) and weathered PVC

TECHNICAL DATA

- Backing: LDPE
- Adhesive: Acrylic
- Adhesion to Stainless Steel: 0,8 N / 10 mm
- Tensile: 12 N / 10 mm
- Elongation: 200%
- Thickness: 37 μ



10 Days



10 Days



40 °C

APPLICATION	FITNESS
Indoor	●●●
Outdoor	●●●
Sensitive Surfaces	●
Finished wood	●●
PVC	●
Finery, Stone, Concrete*	
Remarks	

* Do not use on marble, natural stone and terra-cotta.

● limited suitability

●● suitable

●●● good suitability

Physical and technical data displayed in this document are based on international accepted test methods but are no guarantee for product characteristics or product performance. Individual roles may vary slightly from these averages. The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use..