

# Technical Data Sheet

376

## WASHI-TEC® FLEX FORCE

**Extremely strong special Washi-Tec® tape for the highest requirements.**

### Properties

- Flat and supple tape made of reinforced special paper for sharp edges
- Can be removed without leaving any residue
- Extremely stable and tear-resistant thanks to multiple fiber reinforcement
- Particularly abrasion-resistant

### Area of Use

- Very suitable for applications with high coating thickness or for coatings that are applied in multiple layers
- Particularly suitable for stucco and plastering work
- Surface protection during grinding work

### Technical Data

- Backing: Washi (reinforced)
- Adhesive: Acrylic
- Thickness: 0,14 mm
- Adhesion to Steel : 3 N / 10 mm
- Tensile: 59 N / 10 mm
- Elongation: 10 %



6 months



2 months



100 °C

Application	Fitness
Inside	●●●
Outside	●●●
Sensitive Surfaces	●●
Finished wood	●●
PVC	●●
Finery, Stone, Concrete*	●●
Remarks	

\* Do not use on marble, natural stone and terra-cotta.

● good      ●● better      ●●● best

Physical and technical data displayed in this document are based on international accepted test methods but are no guarantee for product characteristics or product performance. Individual roles may vary slightly from these averages.

The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use.