

Ram Board Seam Tape™

Ram Board Seam Tape has an aggressive, high-tack adhesive that is specifically designed to seam Ram Board rolls together but also works well with seaming other surface protection. The tape blocks out liquid, dust, dirt and more from reaching your protected floor's surface.

Available sizes:

2.83" x 164' (72mm x 50m)



FEATURES:

- Strong, flexible, and conformable backing
- Thermoplastic rubber adhesive with natural kraft paper backing
- Resists curling, abrasion, and water
- Excellent holding power



TYPICAL PROPERTIES:

Property	Value	Test Method
Thickness	7.6 mil (0.19mm)	PSTC-133
Tensile	38 lb/in	PSTC-131
Adhesion	44 oz/in	PSTC-101
Elongation	9.0%	
Application Temperature	41°F to 140°F	
Service Temperature	14°F to 140°F	

FURTHER TECHNICAL INFORMATION:

- Store Seam Tape away from direct sunlight and in a cool and dry area
- For optimum performance, Seam Tape should be used within 12 months of date of shipment
- Seam Tape works best when applied to a surface that is clean, dry, and free of grease, oil, or other contaminants.
- DO NOT apply directly to floor or finished surface

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product. © 2021 Ram Board, Inc. Product names & attributes trademark of Ram Board, Inc. where applicable.