

TECHNICAL DATA SHEET

319 PE Protection Tape - Pro Quality

Premium PE tape for professional masking and marking applications.

Properties

- Sticks to a wide range of different materials, even some hard-to-stick surfaces such as structured coatings
- Easy to unwind and tear by hand
- Extreme temperature resistance!

Area of Use

- Protection during transportation or production
- Masking delicate surfaces during painting/renovation
- Do not mask anodized aluminum!

Technical Data

- Backing: PE film
- Thickness: 0,1 mm
- Adhesive: Acrylic
- Adhesion Steel: 1,5 N / 10 mm
- Tensile: 6 N / 10 mm
- Elongation: 220%



6 weeks



6 weeks



-40 °C - +60 °C

Application	Fitness
Inside	●●●
Outside	●●●
Sensitive Surfaces	●
Finished wood	●●
PVC	●●●
Finery, Stone, Concrete*	●
Remarks	

* Do not use on marble, natural stone and terra-cotta.

● limited suitability ●● suitable ●●● good suitability

Krip[®]

Physical and technical data displayed in this document are based on international accepted test methods but are no guarantee for product characteristics or product performance. Individual roles may vary slightly from these averages. The user should determine whether a product is fit for a particular purpose and is suitable for the user's method of application before use.