

Thread Seal Tape

SPECIALTY COATED TAPE

DESCRIPTION

100% virgin PTFE film. Withstands alkalis, acids, hydro-carbons, solvents, refrigerants, gases and steam. Meets MIL-T-27730-A. Contains no lead or toxic chemicals. Not suited for petroleum products.

PRODUCT APPLICATION

Can be used on iron, stainless steel, copper, brass or plastic pipe.

GOVERNMENT CONFORMANCE

MIL-T-27730 A

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	100% Virgin PTFE Film
Tensile Strength (lbs/in ²) ASTM D-882	>1.8 (8 N/mm ²)
Elongation (% at break)	>25
Total Thickness (mil) ASTM D-882	>2.9 (0.074mm)
Temperature Range (oz/in) ASTM D-3330	-400°F ~ +700°F (-240°C ~ +370°C)
Color	White



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 9/11

