Functional Devices, Inc.
101 Commerce Drive
Sharpsville, IN 46068
Confidence & Peace of Mind in Every Box™

Office: (765) 883-5538
Toll Free: (800) 888-5538
www.functionaldevices.com
sales@functionaldevices.com

WIRELESS ROCKER SWITCH TRANSMITTER & COVER PLATE

WWS2-EN3

EnOcean 902 MHz Wireless Wall Transmitter Switch with Barrier and Cover Plate, White

RoHS

enocean alliance Member

SPECIFICATIONS

Operating Modes	On/Off, Toggle, Scene control	
Power Supply	Powered by finger press (Electrodynamic Energy Harvester)	
Frequency	902 MHz	
Antenna	Integrated antenna, 6.4 cm	
Transmission Power	Max. 10mW EIRP	
Energy Bowtravel/Operating Force	50,000 actuations tested to EN60669 / VDE 0632	
Operating Temperature	-25 to 65° C	
Relative Humidity	5 to 92% (noncondensing)	
Dimensions	2.75" H x 4.50" W x 0.8" D	
Approvals	RoHS	
Agency Compliance	SWITCH FCC ID: SZV-PTM210U IC: 5713A-PTM210U	BARRIER PLATE Certified to UL514D CSA C22.2 #42-1-13



NOTES

Control one load or one group of loads with a single rocker style Wireless Switch Transmitter

Typical range is 50-150 feet. Open area transmission could be farther. Consult factory for more information.

Mounting
- Includes barrier plate and mounts to electrical wall boxes (screws included).
- Alternate surface mount accessory AWSTFM to install on any surface using double sided tape or Velcro™ (sold separately).

Only for use with -EN3 model relays.

EEP F6-02-02

