A19 Thermostat for Portable Cooling Applications (Chain Mount and Drop Cord Electrical Connection) Catalog Page

LIT-1900402

2020-04-22



Description

The A19 Series Thermostat is a sturdy compact thermostat designed especially for temporary installations.

Refer to the *A19 Series Hot Water Heating Controls Well Immersion Product Bulletin (LIT-125025)* for important product application information.

Features

- 6-foot extension cord with piggyback style plug
- NEMA 1 enclosure
- Chain mount
- Remote sensing bulb with 6 ft (1.8 m) capillary tube

Applications

- On/off control of portable cooling applications
- Home brewing

Repair Information

If the A19 Thermostat for Portable Cooling Applications (Chain Mount and Drop Cord Electrical Connections) fails to operate within its specifications, replace the unit. For a replacement thermostat, contact the nearest Johnson Controls® representative.

A19 Thermostat for Portable Cooling Applications (Chain Mount and Drop Cord Electrical Connection) technical specifications

Table 1: Electrical Ratings

Motor Ratings VAC	120
AC Full Load Amperes	15
AC Locked Rotor Amperes	90

Selection Chart

Table 2: Selection Chart

Product Code Number	Switch Action	Range °F (°C)	Differential F° (C°)	Maximum Bulb Temperature °F (°C)
A19AAT-2C	Single-Pole, Single-Throw (SPST) open low	20 to 80 (-7 to 27)	3-1/2 ± 2 (2 ± 1.11) Non-adjustable	140 (60)

Product warranty

This product is covered by a limited warranty, details of which can be found at www.johnsoncontrols.com/buildingswarranty.

Single point of contact

APAC	Europe	NA/SA
JOHNSON CONTROLS C/O CONTROLS PRODUCT MANAGEMENT NO. 32 CHANGJIJANG RD NEW DISTRICT WUXI JIANGSU PROVINCE 214028 CHINA	JOHNSON CONTROLS WESTENDHOF 3 45143 ESSEN GERMANY	JOHNSON CONTROLS 507 E MICHIGAN ST MILWAUKEE WI 53202 USA

Contact information

Contact your local branch office:
www.johnsoncontrols.com/locations

Contact Johnson Controls:
www.johnsoncontrols.com/contact-us

© 2020 Johnson Controls. All rights reserved. All specifications and other information shown were current as of document revision and are subject to change without notice.
www.penncontrols.com

Johnson Controls