T-4000 Series Accessories Catalog Page


LIT-1921710

2020-01-07

T-4000 Accessories


Selection Chart

Table 1: T-4000 Series Accessories selection chart

Code Number	Figure	Description	Application (High or Low Volume)
F-100-20	 F-300-30	Coupler, 5/32 x 3/16 in. copper sweat	High
F-300-30		Coupler, 5/32 x 1/4 in. (100/pkg.)	Low
F-300-34		Coupler, 5/32 x 1/4 in. (10/pkg.	
F-300-31		Coupler, 5/32 x 5/32 in. (100/pkg.)	
F-300-35		Coupler, 5/32 x 5/32 in. (10/pkg.)	
F-500-45		Barbed elbow fitting, 5/32 in. x 5/32 in., for plug-in connection to 5/32 in. O.D. polyethylene tubing	High Low
F-700-83	 F-700-85	Brass tee, 5/32 x 5/32 x 5/32 in. (50/pkg.)	High
F-700-94		Brass tee, 5/32 x 5/32 x 5/32 in. (10/pkg.)	Low
F-700-84		Tee, 1/4 x 1/4 x 5/32 in. (100/pkg.	
F-700-95		Tee, 1/4 x 1/4 x 5/32 in. (10/pkg.)	
F-700-85		Tee, 3/8 x 3/8 x 5/32 in.	
F-700-86		Tee (plastic) coupler fitting: 5/32 x 5/32 x 5/32 in. barbed (100/kit)	
F-1000-322		Anti-kink spring, 3/32 in., S.S., 8 in. long, for use with 5/32 in. OD plastic tubing (50/pkg.)	
F-1000-395		Anti-kink spring, 3/32 in., S.S., 8 in. long, for use with 5/32 in. OD plastic tubing (10/pkg.)	
GRD10A-608		Plastic guard provides surface-mounted thermostat protection after construction	High Low




Johnson Controls

Table 1: T-4000 Series Accessories selection chart

Code Number	Figure	Description	Application (High or Low Volume)
JC 5361		Hypodermic needle test probe for calibration	High
JC 5384		Spare hypodermic needles (12/kit)	Low
JC 5310		Screw-In gage for calibration	High Low
R-3710-1005		Restrictor, 0.005 in. (red), for restricted supply source	High Low
R-3710-1007		Restrictor, 0.007 in. (aqua), for restricted supply source	Low
R-3710-3205		Restrictor tee, 0.005 in., 1/4 x 5/32 x 5/32 in. (red), for restricted supply source	Low
R-3710-3207		Restrictor, 0.007 in., 1/4 x 5/32 x 5/32 (Aqua), for Restricted supply source	Low
F-1000-321		Plastic screw anchors (order in multiples of 100) for mounting brackets and wallbox	High Low
T-4000-108		Stick-on thermometer for concealed thermometer cover applications	High





Johnson Controls

Table 1: T-4000 Series Accessories selection chart

Code Number	Figure	Description	Application (High or Low Volume)
T-4000-110		Aspirator wallbox kit for concealed mounted thermostats without push buttons	High
T-4000-111		Wallplate Cover Kit, beige finish, for concealed-mounted thermostats without push buttons	High
T-4000-112		Wallplate Cover Kit, stainless steel finish, for concealed-mounted thermostats without push buttons	High
T-4000-114		Setpoint label card for identifying control functions	High Low
T-4002-3004		Cast aluminum guard and mounting bracket provide surface-mounted thermostat protection after construction	High Low
T-4002-100		Ceiling-Suspended Mounting Kit provides a method, other than wall mounting, of installing a 4000 Series thermostat	High





Johnson Controls

Table 1: T-4000 Series Accessories selection chart

Code Number	Figure	Description	Application (High or Low Volume)
T-4002-122		Terminal Connector, with Two Straight Fittings, for Plug-In Connection to 5/32 in. O.D. Polyethylene Tubing	High
T-4002-123		Terminal connector with two angle fittings for surface-mounted thermostats with exposed tubing	High
T-4002-124		Room instrument mounting bracket for surface-mounting all thermostats and covers; includes drywall clips, spacers, and mounting templates	High
T-4002-125		Plastic surface-mounting back for surface-mounted thermostats with exposed tubing	High
T-4002-3000		Wire guard for exposed tubing provides surface-mounted thermostat protection after construction	Low High
T-4002-3001		Wire guard for concealed tubing	
T-4002-5003		Restricted adjustment pin (100/Kit) restricts adjustment of setpoint dial	High Low
T-4002-5010		Cover for groundplate or metal wallbox keeps dirt out of groundplate and wallbox during construction	High Low
T-4002-5012		Adjusting Knob Kit provides a means of external setpoint adjustment	High



Johnson Controls

Table 1: T-4000 Series Accessories selection chart

Code Number	Figure	Description	Application (High or Low Volume)
T-4002-5017		External setpoint dialHorizontal °F	High
T-4002-5018		External setpoint dialVertical °F	Low
T-4002-6029		Metal wallbox for rough-in of surface-mounted thermostats in masonry	High Low
T-4002-6038		Plaster groundplate for rough-in of surface-mounted thermostats in masonry	High
T-4002-6045		Wire guard mounting plate provides surface-mounted thermostat protection after construction	High Low
T-4100-100		Blank Faceplate Kit for T-4100 and T-4600 Series thermostat covers	Low
T-4100-101		Horizontal Faceplate Kit (no thermometer) for T-4100 and T-4600 Series thermostat covers	Low
T-4100-102		Horizontal Faceplate Kit, with thermometer °F and °C, for T-4100 and T-4600 Series thermostat covers	Low

Johnson Controls

Table 1: T-4000 Series Accessories selection chart

Code Number	Figure	Description		Application (High or Low Volume)
T-4100-103		Universal Wallplate Adaptor Kit mounts on standard electrical wallbox and some competitors' hardware		Low
T-4512-100		Terminal connector, with three straight fittings, for plug-in connection to 5/32 in. O.D. polyethylene tubing		High
T-4000-115		0 to 150°F dial strip (select 30°C span for special range)	Horizontal lower	High
T-4506-100			Horizontal upper	
T-4000-116			Vertical right	
T-4506-101			Vertical left	
T-4000-117		-20 to 65°C dial strip (select 150°C span for special range)	Horizontal lower	
T-4506-102			Horizontal upper	
T-4506-103			Vertical left	
TE-1800-9600		Wallplate Cover Kit, stainless steel finish, adapts 4000 Series brackets and covers to standard conduit wallbox		High

Johnson Controls

© 2020 Johnson Controls. All rights reserved. All specifications and other information shown were current as of document revision and are subject to change without notice.
www.johnsoncontrols.com

Johnson Controls