2025-09-25 LIT-1901109

Description

The TEC3000 Color Series Thermostats are wireless, stand-alone, and field-selectable BACnet® MS/TP or N2 networked devices that provide on/off, floating, and proportional control of the following:

- local hydronic reheat valves
- pressure-dependent VAV equipment with or without local reheat
- two- or four-pipe fan coils
- cabinet unit heaters
- other zoning equipment using an on/off, floating, or 0 VDC to 10 VDC proportional control input
- single- or two-stage control of unitary rooftop units (RTUs)
- single- or two-stage control of RTUs with economizers
- single- or two-stage control of heat pumps
- single- or two-stage control of heat pumps with economizers
- Up to three-stage control of heat pumps
- Up to three-stage control of heat pumps with economizers

ⓘ **Note:** The third stage is a supplemental heat stage and not a compressor like the first two stages.

Figure 1: TEC3000 Color Series Thermostat shown with occupancy sensor in white and black enclosures



You can monitor and program the wireless and field-selectable BACnet MS/TP or N2 networked thermostats remotely through the building automation system, to provide efficient space temperature control. The wireless thermostats feature a connection to the ZFR Pro Series Wireless Field Bus Systems. All models include a USB port configuration that reduces installation time by allowing simple backup and restore features from a USB drive, which enables rapid cloning of configuration between like units. The programming memory of all TEC3000 Series Thermostats is non-volatile.

➤ **Important:** ZFR182x Pro Series Wireless System compatible TEC30xx-1x-000 models and ZFR183x Pro Series Wireless System compatible TEC31xx-1x-000 models are not compatible with each other and cannot be used under the same PAN ID (network address).

Some models feature a built-in occupancy sensing capability. These thermostats use additional standby setpoints to maximize up to 30% energy savings in high-energy usage commercial buildings, such as schools and hotels, during occupied times.

A bright, high-definition capacitive touchscreen display provides responsive feedback and improved readability of text and icons. The home screen is configurable to Modern and Classic, and Light and Dark themes.

Models are available in modern black or white high-gloss designs with or without the Johnson Controls® logo.

The following fan configurations are supported for fan coil equipment types:

- single-speed
- multi-speed (two or three discrete speeds)
- variable-speed/EC motors (0 VDC to 10 VDC control)

All models support dehumidification on two-pipe fan coil units with reheat, four-pipe fan coil units with individual coils or single coil with heating and cooling valves installed, rooftop units with hot gas reheat, and rooftop units with an auxiliary dehumidifier.

Johnson Controls

When no heating is required and mechanical cooling is available, the thermostat monitors space humidity and activates dehumidification control as necessary. Heat or reheat is used as required to maintain the space temperature.

For optimal dehumidification performance, use a fan coil unit that includes a multi-speed or variable-speed fan (VSF).

Refer to the *TEC3000 Color Series Wireless, Stand-Alone, and Field-Selectable BACnet® MS/TP or N2 Networked Thermostats Product Bulletin (LIT-12013193)* for important product application information.

Refer to the *WNC1800/ZFR182x Pro Series Wireless Field Bus System Catalog Page (LIT-1901026)* for information about the ZFR182x Pro Series Wireless System.

Refer to the *WRG1800/ZFR183x Pro Series Wireless Field Bus System Catalog Page (LIT-1901153)* for information about the ZFR183x Pro Series Wireless System.

Features and benefits

Two configurable binary inputs

Provide additional inputs for advanced functions such as remote night setback, service or filter alarms, motion detector, and door, window, or fan status.

Two or three configurable analog inputs

Provide additional inputs such as remote relative humidity, remote zone temperature, zone carbon dioxide level, damper feedback, or outdoor air temperature to support advanced control strategies.

Field-Selectable BACnet MS/TP or N2 Networked Communication (TEC36xx-1x-000 models)

Simplifies the upgrade from N2 networked communication to BACnet MS/TP networked communication without changing hardware.

USB port configuration

Rapidly clone the configuration between like units through simple backup and restore features from a USB drive to reduce installation time.

Programmable in seven languages

Provides English, Spanish, French, German, Italian, Dutch, Portuguese (requires a downloadable language pack)

Backlit full-color liquid crystal display (LCD)

Offers an intuitive color backlit display that makes setup and operation quick and easy. The new display features on all models and offers real-time control status of the environment in easy-to-read, plain text messages with an adjustable backlight that brightens during user interaction.

Configurable touchscreen UI

Allows facility managers limit the user interaction with the thermostat display based on specific energy policies.

Various models available

Offers models in modern black or white high-gloss designs with or without the Johnson Controls logo.

- The black thermostat color code is hex #2d2926 or RAL 9017.
- The white thermostat color code is hex #F4F5F0 or RAL 9016.

End-of-line switch

Simplifies the layout and installation of communication buses.

Mobile Access Portal (MAP) Gateway compatibility (MAP Release 4.0 or later)

Facilitates remote configuration, viewing, and configuration control through your mobile devices.

Johnson Controls

Onboard occupancy sensor (TEC3x13-1x-000, TEC3x23-1x-000, and TEC3x31-1x-000 models)

Provides energy savings in high-energy usage commercial buildings without additional installation time or cost.

Integral humidity sensor

Monitors space humidity on all models. Activates dehumidification control on two-pipe fan coil units with reheat, four-pipe fan coil units with individual coils or single coil with heating and cooling valves installed, rooftop units with hot gas reheat, and rooftop units with an auxiliary dehumidifier.

Multiple fan configurations for fan coil equipment types

Provide field-selectable single-speed, multi-speed, and variable-speed fan control capabilities.

Full line of remote TE-6300 Series Temperature Sensors

Support a wide usage commercial buildings without additional installation time or cost.

Built-in schedule object

Enables all wireless and wired thermostat models to be scheduled as stand-alone devices; allows wireless and BACnet MS/TP models to be defined and adjusted through the building automation system.

Optimal start

Allows each thermostat to anticipate the heating or cooling needs of a space by starting the equipment early enough to reach the setpoint at the beginning of the scheduled occupancy.

Auto-tuned control loops

Reduce commissioning time, eliminate change-of-season recommissioning, and reduce wear and tear of the mechanical devices.

Load shed

Commands a load shed input to offset the heating and cooling setpoints by a fixed amount on networked models. The change rate of the setpoints is adjustable. The load shed feature is in place to help satisfy the California Title 24 requirements that are defined in joint appendix JA5, section JA5.2.4 for demand signal response. The trigger for this event is defined in another thermostat and passed through the network command.

Scheduled circulation

Runs the fan for a minimum duration per hour. If the minimum hourly fan runtime is not exceeded as part of normal HVAC operation, the fan turns on at the end of the hour for the length of time required to fulfill the minimum run time.

Demand control ventilation (DCV)

ⓘ **Note:** DCV is only applicable to Model 3 (TEC3x3x-1x-000).

Modulates the damper to control the rate of outdoor airflow into the zone in order to maintain the zone CO_2 value at the zone CO_2 setpoint. The following variants of DCV are available: demand control ventilation, occupant sensor control ventilation, and epidemic control ventilation. Occupant sensor control ventilation is a variation of demand control ventilation for zones where the zone occupancy is determined with an occupancy sensor. Epidemic control ventilation removes pathogens from the zone through ventilation. The epidemic control ventilation feature takes priority over demand control ventilation and occupant sensor control ventilation. You must install an economizer to enable the epidemic control ventilation feature. You can set the minimum ventilation position for the economizer damper between 0% to 100% and this applies to both occupied mode and unoccupied mode.

Johnson Controls

Selection charts

Table 1: Wireless ZFR183x Pro Series thermostat models

Code number	Control output	Occupancy	Dehumidification	Johnson Controls logo	Color
TEC3112-14-000	On/off or floating fan coil and zoning	No	Yes	Yes	White
TEC3113-14-000	On/off or floating fan coil and zoning	Yes	Yes	Yes	White
TEC3122-14-000	0 VDC to 10 VDC proportional fan coil and zoning	No	Yes	Yes	White
TEC3123-14-000	0 VDC to 10 VDC proportional fan coil and zoning	Yes	Yes	Yes	White
TEC3130-14-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	No	Yes	Yes	White
TEC3131-14-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	Yes	Yes	Yes	White

Important: ZFR182x Pro Series Wireless System compatible TEC30xx-1x-000 models and ZFR183x Pro Series Wireless System compatible TEC31xx-1x-000 models are not compatible with each other and cannot be used under the same PAN ID (network address).

Table 2: Stand-alone thermostat models

Code number	Control output	Occupancy	Dehumidification	Johnson Controls logo	Color
TEC3312-14-000	On/off or floating fan coil and zoning	No	Yes	Yes	White
TEC3312-16-000	On/off or floating fan coil and zoning	No	Yes	No	White
TEC3313-14-000	On/off or floating fan coil and zoning	Yes	Yes	Yes	White
TEC3322-14-000	0 VDC to 10 VDC proportional fan coil and zoning	No	Yes	Yes	White
TEC3322-16-000	0 VDC to 10 VDC proportional fan coil and zoning	No	Yes	No	White
TEC3323-14-000	0 VDC to 10 VDC proportional fan coil and zoning	Yes	Yes	Yes	White
TEC3330-14-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	No	Yes	Yes	White

Johnson Controls

Table 2: Stand-alone thermostat models

Code number	Control output	Occupancy	Dehumidification	Johnson Controls logo	Color
TEC3330-16-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	No	Yes	No	White
TEC3331-14-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	Yes	Yes	Yes	White

Table 3: Field-selectable BACnet MS/TP or N2 Networked thermostat models

Code number	Control output	Occupancy	Dehumidification	Johnson Controls logo	Color
TEC3612-14-000	On/off or floating fan coil and zoning	No	Yes	Yes	White
TEC3612-16-000	On/off or floating fan coil and zoning	No	Yes	No	White
TEC3613-14-000	On/off or floating fan coil and zoning	Yes	Yes	Yes	White
TEC3622-14-000	0 VDC to 10 VDC proportional fan coil and zoning	No	Yes	Yes	White
TEC3622-16-000	0 VDC to 10 VDC proportional fan coil and zoning	No	Yes	No	White
TEC3623-14-000	0 VDC to 10 VDC proportional fan coil and zoning	Yes	Yes	Yes	White
TEC3630-14-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	No	Yes	Yes	White
TEC3630-16-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	No	Yes	No	White
TEC3631-14-000	Up to two-stage control of RTUs, or up to three-stage control of heat pumps with economizers	Yes	Yes	Yes	White

Johnson Controls

Accessories

Table 4: TEC3000 Color common accessories (order separately)

Code number	Description
TEC-WALLPLT	Wallplate for retrofitting existing installations or concealing mounting surface damage; can be used with any TEC3000 Color Series Thermostat
TE-6300 Series	Remote temperature sensors. **Note:** Refer to the *TEC3000 Color Series Thermostats Product Bulletin (LIT-12013193)* for ordering details regarding Johnson Controls TE-6300 Series Remote Temperature Sensors.
TE-636P-2	Thermistor (10k ohm) Type II, plastic button sensor, 24 in. leads
CD-W00-00-2U	Room CO_2 and temperature with 1k platinum sensor, wall mount, logo, concealed LCD
CD-W00-N0-2U	Room CO_2 and temperature with 1k platinum sensor, wall mount, no logo, concealed LCD
CD-WA0-00-2U	Room CO_2 and temperature sensor, wall mount, logo, concealed LCD
CD-WAD-00-2U	Room CO_2 and temperature sensor, wall mount, logo, viewable LCD
CD-310-U00-00U	Room CO_2, temperature, and humidity sensor, wall mount, logo, concealed LCD
CD-311-U00-00U	Room CO_2, temperature, and humidity sensor, wall mount, logo, viewable LCD
CD-P2016-00-00U	Duct CO_2 and temperature with 1k platinum sensor, duct mount, logo, concealed LCD
CD-P2017-00-00U	Duct CO_2 and temperature with NTC 10k sensor, duct mount, logo, concealed LCD
CD-P1000-00-00U	Duct CO_2 sensor, duct mount, logo, concealed LCD
CD-P2010-00-00U	Duct CO_2 and temperature sensor, 4 mA to 20 mA or 0 V to 10V, duct mount, logo, concealed LCD
T-4000-119	Allen-head adjustment tool (30 per bag)

Table 5: ZFR182x Pro Series Wireless compatible kits and accessories (order separately)

Code number	Description
MS-WNC1820-0A	WNC1800-0SZ with base, 120 VAC to 230 VAC power, ZFR1820 ProCordFlag, with 3 ft (0.9 m) cable
MS-WNC1823-0A	WNC1800-0SZ with base, 120 VAC to 230 VAC power, ZFR1823 ProCordWall, with 10 ft (3 m) cable
MS-WNC1820-0B	WNC1800-0SZ with base, 24 VAC power, ZFR1820 ProCordFlag, with 3 ft (0.9 m) cable
MS-WNC1823-0B	WNC1800-0SZ with base, 24 VAC power, ZFR1823 ProCordWall, with 10 ft (3 m) cable
MS-ZFR1821-0B	ZFR1821 Pro Flag Router/Repeater, 24 VAC/DC power, with 3 ft (0.9 m) cable
MS-ZFR1822-0B	ZFR1822 Pro Wall Mount Router/Repeater, 24 VAC/DC power, with 10 ft (3 m) cable
ZFR-HPSST-0	High Power Wireless Survey Tool Kit (quantity of two required to perform site survey)
ZFR-SSTBAT-0	Wireless Survey Tool, Battery Kit
ZFR-CBLEXT-0	10 ft (3 m) extension cable accessory, RJ12 terminated, RJ12 F-F coupler
ZFR-CBLEXT-1	10 ft (3 m) extension cable accessory, RJ12 terminated
ZFR-USBHA-0	Wireless USB dongle
ZFR-WALLCOVER	ZFR Repeater wallplate cover

Table 6: ZFR183x Pro Series Wireless compatible kits and accessories (order separately)

Code number	Description
JC-WRGKIT-0	WRG1830/ZFR183x Pro Series Wireless Gateway-Coordinator Router Kit. This kit includes a WRG Gateway, a ZFR Coordinator Router, and a Wi-Fi Dongle
JC-ZFR1831-0	WRG1830/ZFR183x Pro Series Wireless Router (used as a repeater)
ZFR-HPSST-0	High Power Wireless Survey Tool Kit (quantity of two required to perform site survey)

Johnson Controls

Table 6: ZFR183x Pro Series Wireless compatible kits and accessories (order separately)

Code number	Description
ZFR-SSTBAT-0	Wireless Survey Tool, Battery Kit
ZFR-CBLEXT-0	10 ft (3 m) extension cable accessory, RJ12 terminated, RJ12 F-F coupler
ZFR-CBLEXT-1	10 ft (3 m) extension cable accessory, RJ12 terminated

Important: ZFR182x Pro Series Wireless System compatible TEC30xx-1x-000 models and ZFR183x Pro Series Wireless System compatible TEC31xx-1x-000 models are not compatible with each other and cannot be used under the same PAN ID (network address).

Johnson Controls

Technical specifications

Table 7: TEC3000 Color Series Thermostats technical specifications

Specification		Description
Power requirements		19 VAC to 30 VAC, 50/60 Hz, 4 VA at 24 VAC nominal, Class 2 or safety extra-low voltage (SELV)
USB port power rating		120 mA to 250 mA current draw supported
Analog output rating (for TEC3x2x models)		0 VDC to 10 VDC into 2k ohm resistance (minimum)
Relay contact rating (for TEC3x1x and TEC3x3x models)	On/off or floating control (for TEC3x1x models)	19 VAC to 30 VAC, 1.0 A maximum, 15 mA minimum, 3.0 A in-rush, Class 2 or SELV
Fan relay output rating (for TEC3x1x and TEC3x2x models)		19 VAC to 30 VAC, 1.0 A maximum, 15 mA minimum, 3.0 A in-rush
Auxiliary output rating/triac output (for TEX3x1x and TEC3x2x models)		19 VAC to 30 VAC, 1.0 A maximum, 15 mA minimum, 3.0 A in-rush
Binary inputs		For TEC3x1x and TEC3x2x models: Dry contact across terminal COM to terminals BI1, BI2, or COS
		For TEC3x3x models: Dry contact across terminal COM to terminals BI1 or BI2
Analog inputs		For TEC3x1x and TEC3x2x models (two AIs): Nickel, platinum, A99B, 2.25k ohm NTC, 10k ohm NTC, 10k ohm NTC Type 3 across terminal COM to terminals R SEN or COS, 0-10 VDC
		For TEC3x3x models (three AIs): Nickel, platinum, A99B, 2.25k ohm NTC, 10k ohm NTC, 10k ohm NTC Type 3 across terminal COM to terminals R SEN, SAT, or OAT, 0-10 VDC
Temperature and humidity sensor type		Local digital sensor
Wire size		18 AWG (1.0 mm diameter) maximum, 22 AWG (0.6 mm diameter) recommended
MS/TP network guidelines		For wired models: up to 100 devices maximum for each network engine; 4,000 ft (1,219 m) maximum cable length. Refer to the MS/TP Technical Bulletin for the Metasys, FX, or Verasys® system installed.
		For wireless models: up to 100 devices maximum for each network engine
Wireless band (for wireless models)		Direct-sequence spread-spectrum 2.4 GHz ISM bands
Transmission power (for wireless models)	TEC30xx-1x-000 compatible with ZFR182x Pro Series	10 mW maximum
	TEC31xx-1x-000 compatible with ZFR183x Pro Series	100 mW maximum
Transmission range (for wireless models)	TEC30xx-1x-000 compatible with ZFR182x Pro Series	50 ft (15.2 m) recommended indoor 250 ft (76.2 m) line of sight, maximum
	TEC31xx-1x-000 compatible with ZFR183x Pro Series	250 ft (76.2 m) recommended indoor 1000 ft (304.8 m) line of sight, maximum
Temperature range	Backlit display	-40.0°F/-40.0°C to 122.0°F/50.0°C in 0.5° increments
	Heating control	40.0°F/4.5°C to 90.0°F/32.0°C
	Cooling control	54.0°F/12.0°C to 100.0°F/38.0°C
Accuracy	Temperature	±0.9F°/±0.5C° at 70.0°F/21.0°C typical calibrated
	Humidity	±5% RH from 20% to 80% RH at 50°F to 90°F (10°C to 32°C)
Minimum deadband		2F°/1C° between heating and cooling

Johnson Controls

Table 7: TEC3000 Color Series Thermostats technical specifications

Specification		Description
Occupancy sensor motion detection (occupancy sensing models)		Minimum of 94 angular degrees up to a distance of 15 ft (4.6 m); based on a clear line of sight
Ambient conditions	Operating	32°F to 122°F (0°C to 50°C); 95% RH maximum, noncondensing
	Storage	-22°F to 122°F (-30°C to 50°C); 95% RH maximum, noncondensing
Compliance	BACnet International	BACnet Testing Laboratories™ (BTL) 135-2001 Listed BACnet Advanced Application Controller (B-AAC)
	United States	UL Listed, File E27734, CCN XAPX, Under UL60730
		Networked models: FCC Compliant to CFR 47, Part 15, Subpart B, Class B
		Wireless models: Transmission complies with FCC Part 15.247 regulations for low power unlicensed transmitters; transmitter identification FCC ID: OEJ-WRZRADIO (ZFR182x), OEJ-ZFRRADIO (ZFR183x)
	Canada	UL Listed, File E27734, CCN XAPX7, Under E60730
		Networked models: Industry Canada, ICES-003
		Wireless models: Industry Canada (IC) RSS-210; Transmitter identification ZFR1810-1: IC ID: 279A-WRZRADIO (ZFR182x), 279A-ZFRRADIO (ZFR183x)
CE	Europe (for networked models only)	CE Mark – Johnson Controls declares that this product is in compliance with the essential requirements and other relevant provisions of the EMC Directive and the RoHS Directive.
	Australia and New Zealand	RCM Mark, Australia/NZ Emissions Compliant
Shipping weight	Models without occupancy sensor	0.75 lb (0.34 kg)
	Models with occupancy sensor	0.77 lb (0.35 kg)

Repair Information

If the TEC3000 Color Series Thermostat fails to operate within its specifications, replace the unit. For a replacement TEC3000 Thermostat contact the nearest Johnson Controls® representative.

Product warranty

This product is covered by a limited warranty, details of which can be found at www.johnsoncontrols.com/buildingswarranty.

Software terms

Use of the software that is in (or constitutes) this product, or access to the cloud, or hosted services applicable to this product, if any, is subject to applicable end-user license, open-source software information, and other terms set forth at www.johnsoncontrols.com/techterms. Your use of this product constitutes an agreement to such terms.

Patents

Patents: https://jcipat.com

Single point of contact

APAC	EU	UK	NA/SA
JOHNSON CONTROLS C/O CONTROLS PRODUCT MANAGEMENT NO. 32 CHANGJIANG RD NEW DISTRICT WUXI JIANGSU PROVINCE 214028 CHINA	JOHNSON CONTROLS VOLTAWEG 20 6101 XK ECHT THE NETHERLANDS	JOHNSON CONTROLS TYCO PARK GRIMSHAW LANE MANCHESTER M40 2WL UNITED KINGDOM	JOHNSON CONTROLS 5757 N GREEN BAY AVE. GLENDALE, WI 53209 USA

Johnson Controls

Contact information

Contact your local Johnson Controls representative:
www.johnsoncontrols.com/locations
Contact Johnson Controls:
www.johnsoncontrols.com/contact-us

© 2025 Johnson Controls. All rights reserved. All specifications and other information shown were current as of document revision and are subject to change without notice.

www.johnsoncontrols.com

Johnson Controls