Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-12108ELJWSS6



Product Specifications:

Part Number: SCE-12108ELJWSS6
Description: S.S. ELJ Enclosure W/Viewing Window
Height: 12.00"
Width: 10.00"
Depth: 8.00"
Catalog Page: 246
Est. Ship Weight: 12 lbs

Construction

- 0.063 In. stainless steel Type 316/316L.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Pour in place oil & water resistant gasket
- 0.25 In. polycarbonate window.
- Standoffs provided for mounting optional panels.
- Removable hinges.
- Doors open 180 degrees.
- Black mini quarter turn latches.
- Latches are opened or closed with a screwdriver.
- Sealing washers and hole plugs included.
- Ground stud on door & body.
- Optional mounting feet available.
- Optional latches available.

Application

Designed to house electrical controls, instruments and components that require unrestricted viewing of the gauges or controls in areas which may be regularly hosed down or are in very wet or oily conditions. Provides protection from dust, dirt, oil, and water. For outdoor applications a drip shield is recommended. For outdoor application a drip shield and drain vent is recommended.

For details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

#4 brushed finish on all exterior surfaces. Optional panels are powder coated white.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Accessories Included

SCE-ELJMFK Mtg Foot Kit (ELJ Enclosure)

Optional Accessories

SCE-12P10 Subpanel, Flat
SCE-12P10AL Subpanel, Flat Aluminum
SCE-12P10GALV Subpanel, Flat Galvannealed
SCE-BVK Breather Vent
SCE-12P10SS Subpanel, Type 316 SS
SCE-DFJ1210 Panel, Dead Front (ELJ & CH)

Similar Part Numbers

SCE-10086ELJWSS6 S.S. ELJ Enclosure W/Viewing Window
SCE-1008ELJWSS6 S.S. ELJ Enclosure W/Viewing Window
SCE-1210ELJWSS6 S.S. ELJ Enclosure W/Viewing Window
SCE-16148ELJWSS6 S.S. ELJ Enclosure W/Viewing Window
SCE-1614ELJWSS6 S.S. ELJ Enclosure W/Viewing Window

Installation Information

- Dead Front CH, ELJ and NEMA 1 Style Installation Instructions. REV. 1
- Enviroline Junction Enclosure

Notes

Recommend use as Type 3R rating in full outdoor exposure and extreme weather environments.

For more details see Design Considerations When Specifying Your Enclosure on our website.

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.