Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-1614FG



Product Specifications:

Part Number: SCE-1614FG
Description: Fiberglass Enclosure (Hinged Screw Cover)
Height: 17.47"
Width: 15.46"
Depth: 6.23"
Catalog Page: 346
Est. Ship Weight: 12 lbs

Construction

- Fiberglass reinforced compression molded polyester.
- Continuous memory retaining gasket.
- Mounting strips molded in.
- Captive screw fasteners.
- Integral panel mounting inserts.
- Stainless steel continuous hinge.

Application

Designed for indoor or outdoor use to house electronic controls, instruments and components in areas that may be regularly hosed down, are in very wet conditions, or are exposed to corrosive agent. Provides protection from dust, dirt, oil, and water.

Finish

Light gray fiberglass. Optional sub-panels are marine grade aluminum.

Industry Standards - (IS5)

- NEMA: Type 4, 4X, 12 and Type 13
- UL: Listed Type 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes

UL File E64358

Optional Accessories

SCE-16P14AL Subpanel, Flat Aluminum

Similar Part Numbers

SCE-10086FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-1008FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-1210FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-1212FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-1407FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-1412FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-1816FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-2016FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-604FG Fiberglass Enclosure (Hinged Screw Cover)
SCE-606FG Fiberglass Enclosure (Hinged Screw Cover)

Installation Information

- Non-Metallic Enclosure Guide