Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-2016CHQRFG



Product Specifications:

Part Number: SCE-2016CHQRFG
Description: Fiberglass Enclosure
Height: 21.68"
Width: 17.68"
Depth: 8.84"
Catalog Page: 348
Est. Ship Weight: 21 lbs

Construction
- Fiberglass reinforced compression molded polyester.
- Pour in place oil & water resistant gasket
- Mounting strip molded in.
- Quick release padlock latch.
- Integral panel mounting inserts.
- Stainless steel continuous hinge.

Application
Designed for indoor or outdoor use to house electrical and electronic controls, instruments and components in areas that may be regularly hosed down, are in very wet conditions, or are exposed to corrosive agents. Provided protection from dust, dirt, oil and water. Provides protection from occasional temporary or prolonged submersion.

Finish
Light gray fiberglass. Optional sub-panels are marine grade aluminum.

Industry Standards - (IS5)
- NEMA: Type 4, 4X, 12 and Type 13
- UL: Listed Type 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes
UL File E64358

Optional Accessories
SCE-20PJ16AL Subpanel, Flat Aluminum

Similar Part Numbers
SCE-10085CHQRFG Fiberglass Enclosure
SCE-12105CHQRFG Fiberglass Enclosure
SCE-1212CHQRFG Fiberglass Enclosure
SCE-14087CHQRFG Fiberglass Enclosure
SCE-14127CHQRFG Fiberglass Enclosure
SCE-16147CHQRFG Fiberglass Enclosure
SCE-18169CHQRFG Fiberglass Enclosure
SCE-202011CHQRFG Fiberglass Enclosure
SCE-242011CHQRFG Fiberglass Enclosure
SCE-242411CHQRFG Fiberglass Enclosure

Installation Information
- Non-Metallic Enclosure Guide