Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-20EL1606SSST



Product Specifications:

Part Number: SCE-20EL1606SSST
Description: S.S. EL Sloping Top Enclosure
Height: 20.00"
Width: 16.00"
Depth: 6.00"
Catalog Page: 260
Est. Ship Weight: 50 lbs

Construction

- 0.075 In. stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- 15 degree sloping top.
- Collar studs 3/8-16 provided for mounting optional panels.
- Mounting holes in back of the enclosure for wall mounting.
- Mounting hardware, sealing washers and hole plugs included.
- Stainless Steel Concealed hinges.
- Removable and interchangeable doors.
- Black quarter turn latches.
- Latches are opened or closed with a screwdriver (optional tamper resistant latches are available)
- Removable print pocket furnished if height and width of enclosure is greater than 12 inches.
- Pour in place oil & water resistant gasket
- Ground stud on door and body.
- Provision for Lifting Lugs will be included on enclosures with Height >48 In. and with Depth >16 In. The Lifting Lug assembly will be included with the enclosure bolt pack.

Application

Designed to house electrical and electronic controls, instrumentation and components in indoor, outdoor and sanitary locations.

For Details about the Design, Performance Expectations, Applications and Design Suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

#4 brushed finish on all exterior surfaces. Optional sub-panels are powder coated white.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12

Optional Accessories

SCE-20P16 Subpanel, Flat
SCE-BVK Breather Vent
SCE-WMS3SS Wall-Mount Standoff, 3 Inch (4-Pack)
SCE-WMS2SS Wall-Mount Standoff, 2 Inch (4-Pack)
SCE-WMS1SS Wall-Mount Standoff, 1 Inch (4-Pack)
SCE-ELMFK4 Foot Kit, EL Mounting (4pc.)
SCE-ELSP3 KIT, Swing-Out Panel (20 High & Up)
SCE-DF20EL16LP Panel, Dead Front (Wall Mount)
SCE-WMS4SS Wall-Mount Standoff, 4 Inch (4-Pack)
SCE-RD20EL16SS Door, Replacement
SCE-ELMFK4SS6-OS Foot Kit, S.S. EL Mounting (4pc.)

Similar Part Numbers

SCE-16EL1208SSST S.S. EL Sloping Top Enclosure
SCE-16EL1608SSST S.S. EL Sloping Top Enclosure
SCE-20EL1608SSST S.S. EL Sloping Top Enclosure
SCE-20EL1612SSST S.S. EL Sloping Top Enclosure
SCE-20EL2008SSST S.S. EL Sloping Top Enclosure
SCE-20EL2012SSST S.S. EL Sloping Top Enclosure
SCE-24EL2008SSST S.S. EL Sloping Top Enclosure
SCE-24EL2012SSST S.S. EL Sloping Top Enclosure
SCE-24EL2408SSST S.S. EL Sloping Top Enclosure
SCE-24EL2412SSST S.S. EL Sloping Top Enclosure

Installation Information

- Mounting Foot Kit for Enviroline Enclosures
- Swing Panel ELSP3 for Encl. Height > 16
- Swing Panel ELSP for Encl. Height <= 16
- Swing Panel ELSP3 for Encl. Height > 16
- Sealing Washer Specifications
- Center Channel Re-Install
- Service Parts Wall Mount Enclosures
- Dead Front Wall Mount < 20 In Height Installation Instructions. EL-LP REV. 2
- Dead Front Wall Mount Installation Instructions. EL-LP REV. 2

- IEC: IEC 60529
- IP: IP 66

Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.