Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-242411CHQRFG



Product Specifications:

Part Number: SCE-242411CHQRFG
Description: Fiberglass Enclosure
Height: 26.12"
Width: 26.12"
Depth: 11.71"
Catalog Page: 348
Est. Ship Weight: 32 lbs

Construction

- Fiberglass reinforced compression molded polyester.
- Pour in place oil & water resistant gasket
- Mounting strip molded in.
- Quick release padlock latch.
- Integral panel mounting inserts.
- Stainless steel continuous hinge.

Application

Designed for indoor or outdoor use to house electrical and electronic controls, instruments and components in areas that may be regularly hosed down, are in very wet conditions, or are exposed to corrosive agents. Provided protection from dust, dirt, oil and water. Provides protection from occasional temporary or prolonged submersion.

Finish

Light gray fiberglass. Optional sub-panels are marine grade aluminum.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes

UL File E64358

Optional Accessories

SCE-24PFG24AL Aluminum Subplate - Fiberglass Enclosure

Similar Part Numbers

SCE-16147CHQRFG Fiberglass Enclosure
SCE-18169CHQRFG Fiberglass Enclosure
SCE-2016CHQRFG Fiberglass Enclosure
SCE-202011CHQRFG Fiberglass Enclosure
SCE-242011CHQRFG Fiberglass Enclosure
SCE-243012CHQRFG Fiberglass Enclosure
SCE-302412CHQRFG Fiberglass Enclosure

Installation Information

- Non-Metallic Enclosure Guide