Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-24EL4210SSWFLP



Product Specifications:

Part Number: SCE-24EL4210SSWFLP
Description: S.S. EL WFLP Enclosure
Height: 24.00"
Width: 42.00"
Depth: 10.00"
Catalog Page: 272
Est. Ship Weight: 91 lbs

Construction

- 0.075 In. stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Collar studs 3/8-16 provided for mounting optional panels.
- Removable centerposts permit easy panel installation.
- Mounting holes in back of the enclosure for wall mounting.
- Mounting hardware, sealing washers and hole plugs included.
- Stainless Steel concealed hinges.
- Removable and interchangeable doors.
- Black keylocking padlocking handles.
- 3-point latching mechanism.
- Removable print pocket.
- Pour in place oil & water resistant gasket
- Ground stud on door and body.

Application

Designed to house electrical and electronic controls, instrumentation and components. For outdoor application a drip shield and drain vent is recommended.

For details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Options

Provisions for mechanical interlock. See Accessory section to order.

**Mechanical Interlock not for use in Enclosures 24" in height.

Finish

#4 brushed finish on all exterior surfaces. Optional sub-panels are powder coated white.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12

Optional Accessories

SCE-42P24 Subpanel, Bent
SCE-42P24GALV Subpanel, Bent Galvanized
SCE-ELMFK4SS6-OS Foot Kit, S.S. EL Mounting (4pc.)
SCE-ELSP3 KIT, Swing-Out Panel (20 High & Up)
SCE-BVK Breather Vent
SCE-24P20 Subpanel, Bent for use with SCE-ELSP3
SCE-DS42SS Shield, S.S. Drip
SCE-RDL24EL42SSWF Door, Replacement
SCE-RDR24EL42SSWF Door, Replacement
SCE-ELMFK6 Foot Kit, EL Mounting (6pc.)

Similar Part Numbers

SCE-24EL4810SSWFLP S.S. EL WFLP Enclosure
SCE-30EL4210SSWFLP S.S. EL WFLP Enclosure
SCE-30EL4810SSWFLP S.S. EL WFLP Enclosure
SCE-36EL4212SSWFLP S.S. EL WFLP Enclosure
SCE-36EL4812SSWFLP S.S. EL WFLP Enclosure

Installation Information

- Mounting Foot Kit for WFLP Enclosures
- Drip Shield Kit Assembly
- Swing Panel ELSP3 for Encl. Height > 16
- Mechanical Interlock
- Sealing Washer Specifications
- Service Parts Free Standing & Floor Mount Enclosures
- Center Channel Re-Install
- Enviroline Series Wall Mount Two Door Enclosures With 3 Point Hardware
- Dead Front Wall Mount Installation Instructions. EL-WFLP REV. 2
- Dead Front Wall Mount 2 Door Installation Instructions Rev. 2

- IEC: IEC 60529
- IP: IP 66

Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.