Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-30EL6010WFLP

Product Specifications:



Part Number: SCE-30EL6010WFLP
Description: EL WFLP Enclosure
Height: 30.00"
Width: 60.00"
Depth: 10.00"
Catalog Page: 102
Est. Ship Weight: 187 lbs

Construction

- 0.075 In. carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Collar studs 3/8-16 provided for mounting optional panels.
- Removable centerposts permit easy panel installation.
- Mounting holes in back of the enclosure for wall mounting
- Mounting hardware, sealing washers and hole plugs included.
- Concealed hinges.
- Removable and interchangeable doors.
- Black keylocking/padlocking handles.
- 3-point latching mechanism.
- Removable print pocket.
- Pour in place oil & water resistant gasket
- Ground stud on door and body.

Application

Designed to house electrical and electronic controls, instrumentation and components in indoor locations. For outdoor application a drip shield and drain vent is recommended.

For details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

ANSI-61 gray powder coating inside and out. Optional sub-panels are powder coated white.

Industry Standards - (IS4)

- NEMA: Type 3R, 4, 12 and Type 13
- UL: Listed Type 3R, 4 and 12
- CSA: Type 3R, 4 and 12
- IEC: IEC 60529
- IP: IP 66

Notes

Optional Accessories

SCE-60P30 Subpanel, Bent
SCE-60P30GALV Subpanel, Bent Galvanized
SCE-ELMFK4SS6-OS Foot Kit, S.S. EL Mounting (4pc.)
SCE-30P30 Subpanel, Bent for use with SCE-ELSP3
SCE-RDR30EL60WF Door, Replacement
SCE-RDL30EL60WF Door, Replacement
SCE-30P30GALV Subpanel, Bent Galvanized
for use with SCE-ELSP3
SCE-BVK Breather Vent
SCE-ELSP3 KIT, Swing-Out Panel (20 High & Up)
SCE-DS60N4 Shield, Drip
SCE-DF30EL30LP Panel, Dead Front (Wall Mount)
SCE-130224 Interlock, Mechanical for Left Door as Main
SCE-130223 Interlock, Mechanical for Right Door as Main
SCE-ELMFK6 Foot Kit, EL Mounting (6pc.)

Similar Part Numbers

SCE-24EL4810WFLP EL WFLP Enclosure
SCE-30EL4810WFLP EL WFLP Enclosure
SCE-36EL4812WFLP EL WFLP Enclosure
SCE-36EL6012WFLP EL WFLP Enclosure
SCE-42EL4812WFLP EL WFLP Enclosure
SCE-42EL6012WFALP EL WFALP Enclosure

Installation Information

- Mounting Foot Kit for WFLP Enclosures
- Drip Shield Kit Assembly
- Swing Panel ELSP3 for Encl. Height > 16
- Mechanical Interlock
- Sealing Washer Specifications
- Enviroline Series Wall Mount Two Door Enclosures With 3 Point Hardware
- Design Considerations When Specifying Your Enclosure
- Sub-Plate Layout & Grounding for 3/8-16
- Dead Front Wall Mount Installation Instructions. EL-WFLP REV. 2

Mechanical interlocks for use on enclosures greater than or equal to 30" in height with a center channel.

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

- Dead Front Wall Mount 2 Door Installation Instructions Rev. 2