Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-36EL3612SSLPPL

Product Specifications:



Part Number: SCE-36EL3612SSLPPL
Description: S.S. LPPL Enclosure
Height: 36.00"
Width: 36.00"
Depth: 12.00"
Catalog Page: 254
Est. Ship Weight: 122.5 lbs

Construction

- 0.075 In. stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Collar studs 3/8-16 provided for mounting optional panels.
- Mounting holes in back of the enclosure for wall mounting.
- Mounting hardware, sealing washers and hole plugs included.
- Stainless steel concealed hinges.
- Removable and interchangeable doors.
- Black zinc die cast keylocking/padlocking handles.
- 3-point latching mechanism.
- Removable print pocket.
- Pour in place oil & water resistant gasket
- Ground stud on door and body.

Application

Designed to house electrical and electronic controls, instrumentation and components in indoor or outdoor locations. For outdoor application a drip shield and drain vent is recommended.

For details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

#4 Brushed finish on all exterior surfaces. Optional sub-panels are powder coated white.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes

Optional Accessories

SCE-36P36 Subpanel, Bent
SCE-DF36EL36LP Panel, Dead Front (Wall Mount)
SCE-ELMFK4SS6-OS Foot Kit, S.S. EL Mounting (4pc.)
SCE-DS36SS Shield, S.S. Drip
SCE-ELMFK4 Foot Kit, EL Mounting (4pc.)
SCE-36P36GALV Subpanel, Bent Galvanized
SCE-BVK Breather Vent
SCE-ELSP3 KIT, Swing-Out Panel (20 High & Up)
SCE-RD36EL36SSLPPL Door, Replacement
SCE-ELFM36HSS S.S. EL Flush Mount Frame
SCE-ELFM36WSS S.S. EL Flush Mount Frame

Similar Part Numbers

SCE-24EL2410SSLPPL S.S. LPPL Enclosure
SCE-30EL2412SSLPPL S.S. LPPL Enclosure
SCE-30EL3012SSLPPL S.S. LPPL Enclosure
SCE-36EL2412SSLPPL S.S. LPPL Enclosure
SCE-36EL3012SSLPPL S.S. LPPL Enclosure
SCE-42EL3612SSLPPL S.S. LPPL Enclosure
SCE-48EL3612SSLPPL S.S. LPPL Enclosure
SCE-48EL3616SSLPPL S.S. LPPL Enclosure

Installation Information

- Sealing Washer Specifications
- EL Flush Mount Frame
- Swing Panel ELSP3 for Encl. Height > 16
- Drip Shield Kit Assembly
- Service Parts Wall Mount Enclosures
- Dead Front Wall Mount Installation Instructions. EL-LP REV. 2
- Dead Front Wall Mount With 3 Point Latching Hardware. EL-LPPL REV. 2

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.