Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

# SCE-42EL3016LPLG



## Product Specifications:

**Part Number:** SCE-42EL3016LPLG
**Description:** EL Enclosure
**Height:** 42.00"
**Width:** 30.00"
**Depth:** 16.00"
**Catalog Page:** 93
**Est. Ship Weight:** 117 lbs

## Construction

- 0.075 In. carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Pour in place oil & water resistant gasket
- Collar studs 3/8-16 provided for mounting optional panels.
- Concealed hinges.
- Removable and interchangeable doors.
- Black quarter turn latches.
- Latches are opened or closed with a screwdriver.
- Mounting holes in back of enclosure.
- Mounting hardware, sealing washer and hole plug included.
- Removable print pocket furnished if height and width of enclosure is greater than 12 inches.
- Ground studs on door and body.

## Application

Designed to house electrical and electronic controls, instruments and components. Provides protection from dust, oil and water. For outdoor application a drip shield and drain vent is recommended.

For details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

## Options

- Optional tamper-resistant inserts are available.
- Optional mounting feet available.
- Door hardware available.
- Interchangeable latches and handles available in the accessory section.

## Finish

RAL 7035 gray powder coating inside and out. Optional sub-panels are powder coated white.

## Industry Standards - (IS4)

- NEMA: Type 3R, 4, 12 and Type 13

## Optional Accessories

SCE-42P30 Subpanel, Bent
SCE-42P30GALV Subpanel, Bent Galvanized
SCE-ELMFK4 Foot Kit, EL Mounting (4pc.)
SCE-ELSP3 KIT, Swing-Out Panel (20 High & Up)
SCE-DS30N4LG Shield, Drip
SCE-DF42EL30LP Panel, Dead Front (Wall Mount)
SCE-BVK Breather Vent
SCE-ELMFK4SS6-OS Foot Kit, S.S. EL Mounting (4pc.)

## Similar Part Numbers

SCE-30EL2008LPLG EL Enclosure
SCE-30EL2010LPLG EL Enclosure
SCE-30EL2406LPLG EL Enclosure
SCE-30EL2408LPLG EL Enclosure
SCE-30EL2410LPLG EL Enclosure
SCE-30EL2412LPLG EL Enclosure
SCE-30EL2416LPLG EL Enclosure
SCE-30EL2420LPLG EL Enclosure
SCE-30EL2424LPLG EL Enclosure
SCE-30EL3008LPLG EL Enclosure

## Installation Information

- Design Considerations When Specifying Your Enclosure
- Sub-Plate Layout & Grounding for 3/8-16
- Service Parts Wall Mount Enclosures
- Dead Front Wall Mount Installation Instructions. EL-LP REV. 2
- Dead Front Wall Mount < 20 In Height Installation Instructions. EL-LP REV. 2
- HMI Enclosure Reinforcement Installation

- UL: Listed Type 3R, 4 and 12
- CSA: Type 3R, 4 and 12
- IEC: IEC 60529
- IP: IP 66

## Notes

Provision for Lifting Lugs will be included on enclosures with Height >48" and with Depth >16". The Lifting Lug assembly will be included with the enclosure bolt pack.

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.