Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-462519DC



Product Specifications:

Part Number: SCE-462519DC
Description: Console, Dual Access Single Door
Height: 46.25"
Width: 25.25"
Depth: 18.50"
Catalog Page: 28
Est. Ship Weight: 140 lbs

Construction

- 0.075 In. carbon steel.
- Seams continuously welded and ground smooth.
- 25 degree sloped top.
- Door props on sloped door to hold in the open position.
- Pour in place oil & water resistant gasket
- Flange trough collar around all sides of door opening.
- Concealed hinges.
- Removable doors.
- Removable print pocket.
- Ground studs on door and body.
- Rubber pads with provision for leveling pads on bottom of enclosure.
- Black, quarter turn latches on top door.
- Keylocking black 3-point flush swing handle in front and rear doors.
- Mounting channels welded on sides of interior body for mounting optional panels.
- Mounting hardware included for (1) optional sub-panel.

Application

This product is intended for indoor use. It provides protection to personnel against access to hazardous parts. In addition, it protects the equipment inside the enclosure against introduction of solid foreign objects, falling dirt and water. It is designed for use in a standing or sitting position, supports both single and dual access, and boasts a top that opens for easier accessibility.

For Details about the Design, Performance Expectations, Applications and Design Suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Options

Optional tamper-resistant inserts or padlocking handles are available.

Finish

ANSI-61 gray powder coating inside and out. Optional sub-panels are powder coated white.

Industry Standards - (IS4)

- NEMA: Type 3R, 4, 12 and Type 13

Optional Accessories

SCE-36P24 Subpanel, Bent
SCE-36P24GALV Subpanel, Bent Galvanized
SCE-RDF4625DC Door, Replacement
SCE-RDR4625DC Door, Replacement
SCE-RDS4625DC Door, Replacement

Similar Part Numbers

SCE-463719DC Console, Dual Access Single Door

- UL: Listed Type 3R, 4 and 12
- CSA: Type 3R, 4 and 12
- IEC: IEC 60529
- IP: IP 66

Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.