Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-604808LP

Product Specifications:



Part Number: SCE-604808LP
Description: 2DR LP Enclosure
Height: 60.00"
Width: 48.00"
Depth: 8.00"
Catalog Page: 130
Est. Ship Weight: 337 lbs

Construction

- 0.104 In. carbon steel.
- Flange trough collar around all sides of door opening.
- Seams continuously welded and ground smooth.
- Strong, rigid construction with body stiffeners.
- Gasketed overlapping doors eliminate need for center post.
- Black zinc die cast keylocking/padlocking handle.
- 3-point latching mechanism.
- Latch rods have ramp shoes for easier door closing.
- Concealed hinges.
- Removable print pocket provided on door with 3-point latch.
- 12 inch removable floor stands.
- Heavy duty lifting eyes.
- Panel supports.
- Pour in place oil & water resistant gasket
- Collar studs 3/8-16 provided for mounting optional panels.
- Ground stud on door and body.
- Hole plugs provided to seal holes in bottom of enclosure.

Application

Designed to house electrical and electronic controls, instruments and compartments. Provides protection from dust, oil and water. For outdoor application a drip shield and drain vent is recommended.

For Details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

ANSI-61 gray powder coating inside and out. Optional sub-panels are powder coated white.

Industry Standards - (IS3)

- NEMA: Type 3R, 12 and Type 13
- UL: Listed Type 3R and 12
- CSA: Type 3R and 12
- IEC: IEC 60529

Accessories Included

SCE-HS2S Hole Seal, 2 Inch Square

Optional Accessories

SCE-60P48 Subpanel, Bent
SCE-60P48GALV Subpanel, Bent Galvanized
SCE-BVK Breather Vent
SCE-DS48N4 Shield, Drip
SCE-DF6048 Panel, Dead Front (Overlapping Two Door)
SCE-LF18 Fixture, LED Light
SCE-LF18NO Fixture, LED Light w/o Outlet
SCE-13ELJEXPP Pocket, Exterior Print
SCE-19ELJEXPP Pocket, Exterior Print
SCE-FS1212 Shelf, Folding
SCE-FS1818 Shelf, Folding
SCE-FS2424 Shelf, Folding
SCE-RD6048 Door, Replacement
SCE-RDL6048 Door, Replacement

Similar Part Numbers

SCE-604810LP 2DR LP Enclosure
SCE-604812LP 2DR LP Enclosure
SCE-604816LP 2DR LP Enclosure
SCE-604824LP 2DR LP Enclosure
SCE-606010LP 2DR LP Enclosure
SCE-606012LP 2DR LP Enclosure
SCE-606016LP 2DR LP Enclosure
SCE-606024LP 2DR LP Enclosure
SCE-724812ULP 2DR LP Enclosure
SCE-726010ULP 2DR LP Enclosure

Installation Information

- Drip Shield Kit Assembly
- Folding Shelf Hole Pattern
- LED Light Fixture
- Hole Seal
- Overlapping Two Door Enclosures

- IP: IP 55

Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

- Design Considerations When Specifying Your Enclosure
- Sub-Plate Layout & Grounding for 3/8-16
- Dead Front Overlapping Door Installation Instructions Rev. 2