Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-60EL6018SS6LPPL



Product Specifications:

Part Number: SCE-60EL6018SS6LPPL
Description: S.S. 2DR EL LPPL Enclosure
Height: 60.00"
Width: 60.00"
Depth: 18.00"
Catalog Page: 302
Est. Ship Weight: 590 lbs

Construction

- 0.104 In. stainless steel Type 316/316L.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Removable center post.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners.
- Stainless steel concealed hinge.
- Black key locking padlocking handles.
- 3-point latching mechanism.
- Removable print pocket.
- 12 inch removable floor stands.
- Panel supports.
- Provision for mechanical interlock.
- Pour in place oil & water resistant gasket
- Ground stud on door & body.
- Provisions for light kit.
- Collar studs 3/8-16 provided for mounting optional panels.

Application

Designed to house electrical and electronic controls, instrumentation and components in indoor & outdoor locations. For outdoor application a drip shield and drain vent is recommended.

For details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Options

Provisions for mechanical interlock. See Accessory section to order.

Finish

#4 brushed finish on all exterior surfaces. Optional sub-panels are powder coated white.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13

Optional Accessories

SCE-60P60 Subpanel, Bent
SCE-DF60EL60 Panel, Dead Front (Enviroline Floor Mount)
SCE-60P60GALV Subpanel, Bent Galvanized
SCE-BVK Breather Vent
SCE-13ELJEXPP Pocket, Exterior Print
SCE-19ELJEXPP Pocket, Exterior Print
SCE-FS1212SS Shelf, S.S. Folding
SCE-FS1818SS Shelf, S.S. Folding
SCE-FS2424SS Shelf, S.S. Folding
SCE-BP5618 Plate, Barrier
SCE-BPEX18 Barrier Extension
SCE-RDR60EL60SS6 Door, Replacement
SCE-RDL60EL60SS6 Door, Replacement
SCE-130224 Interlock, Mechanical for Left Door as Main
SCE-130223 Interlock, Mechanical for Right Door as Main
SCE-DS60SS6 Shield, S.S. Drip
SCE-LF18 Fixture, LED Light
SCE-LF18NO Fixture, LED Light w/o Outlet

Similar Part Numbers

SCE-60EL4812SS6LPPL S.S. 2DR EL LPPL Enclosure
SCE-60EL4818SS6LPPL S.S. 2DR EL LPPL Enclosure
SCE-60EL6012SS6LPPL S.S. 2DR EL LPPL Enclosure
SCE-72EL6012SS6LPPL S.S. 2DR EL LPPL Enclosure
SCE-72EL6018SS6LPPL S.S. 2DR EL LPPL Enclosure
SCE-72EL7212SS6LPPL S.S. 2DR EL LPPL Enclosure
SCE-72EL7218SS6LPPL S.S. 2DR EL LPPL Enclosure
SCE-72EL7224SS6LPPL S.S. 2DR EL LPPL Enclosure

Installation Information

- Mechanical Interlock
- Folding Shelf Hole Pattern
- Drip Shield Kit Assembly
- LED Light Fixture
- Service Parts Free Standing & Floor Mount Enclosures
- Center Channel Re-Install

- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

- Dead Front 2 Door W/Center Post Installation Instructions Rev. 2