Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-60XEL6112SS6ST



Product Specifications:

Part Number: SCE-60XEL6112SS6ST
Description: S.S. 2DR XEL Sloping Top Enclosure
Height: 60.00"
Width: 61.00"
Depth: 12.00"
Catalog Page: 316
Est. Ship Weight: 584 lbs

Construction

- 0.104 In. stainless steel Type 316/316L.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- 15 degree sloping top.
- Removable center post.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners.
- Stainless steel concealed hinges.
- Mechanical interlock.
- Stainless Steel coinproof/padlocking handle on main door with Stainless Steel padlocking handle on slave doors.
- 3-point latching mechanism.
- Removable print pocket on main door of disconnect enclosures.
- Provisions for floor stands.
- Panel supports.
- Pour in place oil & water resistant gasket
- Ground stud on door and body.
- Provisions for light kit.
- Collar studs 3/8-16 provided for mounting optional panels.

Application

Designed to house electrical and electronic controls, instrumentation and components in indoor, outdoor and sanitary locations. Designed to house most standard type disconnects.

For Details about the Design, Performance Expectations, Applications and Design Suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

#4 brushed finish on all exterior surfaces. Optional sub-panels are powder coated white

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12

Optional Accessories

SCE-60P60 Subpanel, Bent
SCE-BVK Breather Vent
SCE-BP5612 Plate, Barrier
SCE-FS2424SS Shelf, S.S. Folding
SCE-FS1818SS Shelf, S.S. Folding
SCE-FS1212SS Shelf, S.S. Folding
SCE-19ELJEXPP Pocket, Exterior Print
SCE-13ELJEXPP Pocket, Exterior Print
SCE-LF18NO Fixture, LED Light w/o Outlet
SCE-LF18 Fixture, LED Light
SCE-DF60EL60 Panel, Dead Front (Enviroline Floor Mount)
SCE-DS60SS Shield, S.S. Drip
SCE-60P60GALV Subpanel, Bent Galvanized

Similar Part Numbers

SCE-60XEL4912SS6ST S.S. 2DR XEL Sloping Top Enclosure
SCE-60XEL4918SS6ST S.S. 2DR XEL Sloping Top Enclosure
SCE-60XEL6118SS6ST S.S. 2DR XEL Sloping Top Enclosure
SCE-72XEL6112SS6ST S.S. 2DR XEL Sloping Top Enclosure
SCE-72XEL6118SS6ST S.S. 2DR XEL Sloping Top Enclosure
SCE-72XEL7312SS6ST S.S. 2DR XEL Sloping Top Enclosure
SCE-72XEL7318SS6ST S.S. 2DR XEL Sloping Top Enclosure
SCE-72XEL7324SS6ST S.S. 2DR XEL Sloping Top Enclosure

Installation Information

- Service Parts Free Standing & Floor Mount Enclosures
- Center Channel Re-Install

- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes

Disconnect switch (or circuit breaker) and operating mechanism are not furnished with this enclosure.

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.