Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-72EL6018SS6ST



Product Specifications:

Part Number: SCE-72EL6018SS6ST
Description: S.S. 2DR EL Sloping Top Enclosure
Height: 72.00"
Width: 60.00"
Depth: 18.00"
Catalog Page: 304
Est. Ship Weight: 609.06 lbs

Construction

- 0.104 in stainless steel Type 316.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- 15 degree sloping top.
- Removable center post.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners.
- Black quarter turn latches as required.
- Stainless steel concealed hinges.
- Stainless Steel padlocking handles.
- 3-point latching mechanism.
- Removable print pocket.
- Provisions for floor stands.
- Panel supports.
- Ground stud on door and body.
- Provisions for light kit.
- Pour in place oil and water resistant gasket.
- Collar studs 3/8-16 provided for mounting optional panels.

Application

Designed to house electrical and electronic controls, instrumentation and components in indoor, outdoor and sanitary locations.

For Details about the Design, Performance Expectations, Applications and Design Suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Options

Test

Finish

316 brushed finish on all exterior surfaces.
Optional sub-panels powder coated white.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13

Optional Accessories

SCE-72P60 Subpanel, Bent
SCE-DS60SS Shield, S.S. Drip
SCE-BVK Breather Vent
SCE-130223 Interlock, Mechanical for Right Door as Main
SCE-130224 Interlock, Mechanical for Left Door as Main
SCE-BPEX18 Barrier Extension
SCE-BP6818 Plate, Barrier
SCE-FS2424SS Shelf, S.S. Folding
SCE-FS1818SS Shelf, S.S. Folding
SCE-FS1212SS Shelf, S.S. Folding
SCE-LF18NO Fixture, LED Light w/o Outlet
SCE-LF18 Fixture, LED Light
SCE-DF72EL60 Panel, Dead Front (Enviroline Floor Mount)
SCE-72P60GALV Subpanel, Bent Galvanized

Similar Part Numbers

SCE-60EL4812SS6ST S.S. 2DR EL Sloping Top Enclosure
SCE-60EL4818SS6ST S.S. 2DR EL Sloping Top Enclosure
SCE-60EL6012SS6ST S.S. 2DR EL Sloping Top Enclosure
SCE-60EL6018SS6ST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL6012SS6ST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL7212SS6ST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL7218SS6ST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL7224SS6ST S.S. 2DR EL Sloping Top Enclosure

Installation Information

- Service Parts Free Standing & Floor Mount Enclosures
- Center Channel Re-Install

- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.