Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-72EL6036FSD



Product Specifications:

Part Number: SCE-72EL6036FSD
Description: EL FSD Enclosure
Height: 72.00"
Width: 60.00"
Depth: 36.00"
Catalog Page: 136
Est. Ship Weight: 730 lbs

Construction

- 0.104 In. carbon steel.
- Two-Door Single Access.
- Removable and inchangeable doors.
- Seams continuously welded and ground smooth.
- Lifting eyes for easy handling.
- Black zinc die cast keylocking/padlocking handle.
- 3-point latching mechanism.
- Latch rods have ramp shoes for easier door closing.
- Flange trough collar around all sides of door opening.
- Removable center post.
- Mounting channels welded horizontally on sides of interior body at top, bottom and middle for mounting optional panels or rack mounting angles.
- Pour in place oil & water resistant gasket
- Ground stud on door and body.
- Provisions for light kit.
- Concealed hinges.
- Holes plugs provided to seal holes in bottom of enclosure.
- Removable print pocket.

Application

Designed to house a variety of electrical and electronic controls and instruments. Provisions for optional surface mounting or rack mounting of almost any type of equipment. Provides protection from dust, dirt, water and oil. The enclosures are extra deep for applications requiring more interior space. For outdoor application a drip shield and drain vent is recommended.

For Details about the design, performance expectations, applications and design suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

ANSI-61 gray finish Inside and outside. Optional sub-panels are powder coated white.

Industry Standards - (IS4)

- NEMA: Type 3R, 4, 12 and Type 13
- UL: Listed Type 3R, 4 and 12

Accessories Included

SCE-HS2S Hole Seal, 2 Inch Square

Optional Accessories

SCE-72P60F1 Subpanel, Full
SCE-BVK Breather Vent
SCE-130223 Interlock, Mechanical for Right Door as Main
SCE-130224 Interlock, Mechanical for Left Door as Main
SCE-DS60N4 Shield, Drip
SCE-72FSCPS Support, Center Panel
SCE-72FSCS Support, Center
SCE-72P30F1 Subpanel, Full
SCE-72P30F2 Subpanel, Half
SCE-72SMP14 Subpanel, Side Mount
SCE-72P60F1GALV Subpanel, Full Galvanized
SCE-72P30F1GALV Subpanel, Full Galvanized
SCE-72FSHDPS Panel Support Heavy Duty
SCE-72RP30F6 Angle, Rack
SCE-72RP30F5 Angle, Rack
SCE-LF18 Fixture, LED Light
SCE-LF18NO Fixture, LED Light w/o Outlet
SCE-13ELJEXPP Pocket, Exterior Print
SCE-19ELJEXPP Pocket, Exterior Print
SCE-FS1212 Shelf, Folding
SCE-FS1818 Shelf, Folding
SCE-FS2424 Shelf, Folding
SCE-7230SOF19 Frame, Swing Out Rack Mounting
SCE-72SP30F3 Panel, Swingout Full
SCE-72SP30F4 Panel, Swingout Half
SCE-72RA24TH Angle, Rack
SCE-RDL72EL60FSD Door, Replacement
SCE-RDR72EL60FSD Door, Replacement

Similar Part Numbers

SCE-60EL4818FSD EL FSD Enclosure
SCE-72EL4818FSD EL FSD Enclosure
SCE-72EL4824FSD EL FSD Enclosure

- CSA: Type 3R, 4 and 12
- IEC: IEC 60529
- IP: IP 66

Notes

Optional panels and accessories available.

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

SCE-72EL6018FSD EL FSD Enclosure
SCE-72EL6024FSD EL FSD Enclosure
SCE-72EL7218FSD EL FSD Enclosure
SCE-72EL7224FSD EL FSD Enclosure

Installation Information

- Center Panel Support Assembly
- Heavy Duty Panel Supports - In Two Door FS Enclosure
- Rack Mounting Angles
- Swing-Out Full Panel
- Swing-Out Rack Mounting Frame
- Swing-Out Half Panel
- Drip Shield Kit Assembly
- Folding Shelf Hole Pattern
- Removable Wire Cover
- LED Light Fixture
- Hole Seal
- Free-Standing Two-Door Single Access Accessories
- Service Parts Free Standing & Floor Mount Enclosures
- Design Considerations When Specifying Your Enclosure