Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-72EL7212SSST



Product Specifications:

Part Number: SCE-72EL7212SSST
Description: S.S. 2DR EL Sloping Top Enclosure
Height: 72.00"
Width: 72.00"
Depth: 12.00"
Catalog Page: 304
Est. Ship Weight: 740 lbs

Construction

- 0.104 In. stainless steel Type 304.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- 15 degree sloping top.
- Removable center post.
- Heavy duty lifting eyes anchor into reinforced top.
- Body stiffeners.
- Stainless Steel concealed hinges.
- Stainless Steel padlocking handles.
- 3-point latching mechanism.
- Removable print pocket.
- Provisions for 12in. removable floor stands.
- Panel Supports.
- Pour in place oil & water resistant gasket
- Ground stud on door and body.
- Provisions for light kit.
- Collar studs 3/8-16 provided for mounting optional panels.

Application

Designed to house electrical and electronic controls, instrumentation and components in indoor, outdoor and sanitary locations.

For Details about the Design, Performance Expectations, Applications and Design Suggestions - See Design Considerations
www.saginawcontrol.com/instman/considerations.pdf

Finish

#4 brushed finish on all exterior surfaces. Optional sub-panels are powder coated white.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Optional Accessories

SCE-72P72GALV Subpanel, Bent Galvanized
SCE-72P72 Subpanel, Bent
SCE-BVK Breather Vent
SCE-DF72EL72 Panel, Dead Front (Enviroline Floor Mount)
SCE-LF18 Fixture, LED Light
SCE-LF18NO Fixture, LED Light w/o Outlet
SCE-LF24 Fixture, LED Light
SCE-LF24NO Fixture, LED Light w/o Outlet
SCE-13ELJEXPP Pocket, Exterior Print
SCE-19ELJEXPP Pocket, Exterior Print
SCE-FS1212SS Shelf, S.S. Folding
SCE-FS1818SS Shelf, S.S. Folding
SCE-FS2424SS Shelf, S.S. Folding
SCE-130224 Interlock, Mechanical for Left Door as Main
SCE-130223 Interlock, Mechanical for Right Door as Main
SCE-BP6812 Plate, Barrier
SCE-RDL72EL72SSST Door, Replacement
SCE-RDR72EL72SSST Door, Replacement

Similar Part Numbers

SCE-60EL6012SSST S.S. 2DR EL Sloping Top Enclosure
SCE-60EL6018SSST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL6012SSST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL6018SSST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL7218SSST S.S. 2DR EL Sloping Top Enclosure
SCE-72EL7224SSST S.S. 2DR EL Sloping Top Enclosure

Installation Information

- Drip Shield Kit Assembly
- Folding Shelf Hole Pattern
- LED Light Fixture
- Service Parts Free Standing & Floor Mount Enclosures
- Center Channel Re-Install
- Enviroline Series Sloping Top Two Door Enclosures (Stainless Steel)

Notes

Special Instructions apply for IS3, IS4 and IS6 to maintain the environmental rating of Type 3R for these parts. Instructions are located on the enclosure door. Drip shield is required on IS3, drip shield is recommended on IS4 and IS6. Drain holes are required on all.

- Dead Front 2 Door W/Center Post Installation Instructions Rev. 2