Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-806FW



Product Specifications:

Part Number: SCE-806FW
Description: Fiberglass Enclosure W/Window
Height: 9.52"
Width: 7.52"
Depth: 4.71"
Catalog Page: 350
Est. Ship Weight: 4 lbs

Construction
- Fiberglass reinforced compression molded polyester.
- Continuous memory retaining gasket.
- Mounting strips molded in.
- Quick release padlock latch.
- Integral panel mounting inserts.
- Stainless steel continuous hinge.
- UVA acrylic bonded polycarbonate window.

Application
Designed for indoor or outdoor use to house electronic controls, instruments and components in areas that may be regularly hosed down, are in very wet conditions, or are exposed to corrosive agents and require unrestricted viewing of gauges or controls. Provides protection from dust, dirt, oil, and water.

Finish
Light gray fiberglass. Optional sub-panels are marine grade aluminum.

Industry Standards - (IS5)
- NEMA: Type 4, 4X, 12 and Type 13
- UL: Listed Type 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Notes
UL File E64358

Optional Accessories
SCE-8P6AL Subpanel, Flat Aluminum

Similar Part Numbers
SCE-10086FW Fiberglass Enclosure W/Window
SCE-1008FW Fiberglass Enclosure W/Window
SCE-1210FW Fiberglass Enclosure W/Window
SCE-1407FW Fiberglass Enclosure W/Window
SCE-1412FW Fiberglass Enclosure W/Window
SCE-1614FW Fiberglass Enclosure W/Window
SCE-1816FW Fiberglass Enclosure W/Window
SCE-604FW Fiberglass Enclosure W/Window
SCE-606FW Fiberglass Enclosure W/Window

Installation Information
- Non-Metallic Enclosure Guide