Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-N68C7818SS6



Product Specifications:

Part Number: SCE-N68C7818SS6
Description: S.S. 2DR Enc. Center Bay - Both Side Open
Height: 68.00"
Width: 77.75"
Depth: 18.00"
Catalog Page: 292
Est. Ship Weight: 690 lbs

Construction

- .104 in stainless steel Type 316.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Body stiffeners in large enclosures for extra rigidity.
- Heavy duty lifting eyes anchor into reinforced top.
- Removable centerposts permit easy panel installation.
- Concealed hinges.
- Black zinc die cast coinproof/padlocking handle on primary door with black zinc die cast padlocking handle on secondary doors.
- 3-point latching mechanism.
- End of latch rods have ramp shoes for easier door closing.
- Panel supports.
- Pour-in-place oil & water resistant gasket.
- Optional panels mount to collar studs.
- Ground stud on door and body.
- Provisions for light kit.
- Mechanical interlock provided for two-door or more.
- Enclosures include provisions for system expansion.

Application

Can be bolted together in any desired multiple door arrangement for maximum versatility. Designed to house a variety of electrical and electronic controls and instruments. Provides protection from dust, dirt, water and oil. The enclosures are extra deep for applications requiring more interior space. For outdoor application a drip shield and drain vent is recommended.

Finish

#4 brushed finish on all exterior surfaces. Optional subpanels powder coated white or galvanized.

Industry Standards - (IS6)

- NEMA: Type 3R, 4, 4X, 12 and Type 13
- UL: Listed Type 3R, 4, 4X and 12
- CSA: Type 4, 4X and 12
- IEC: IEC 60529
- IP: IP 66

Optional Accessories

SCE-N68P78 Subpanel, Bent
SCE-13ELJEXPP Pocket, Exterior Print
SCE-19ELJEXPP Pocket, Exterior Print
SCE-N68P78GALV Subpanel, Galvanized
SCE-NEP6818ss6 End Plate Stainless Steel
SCE-NBP6818 Barrier Plate
SCE-BVK Breather Vent
SCE-FS1212 Shelf, Folding
SCE-FS1818 Shelf, Folding
SCE-FS2424 Shelf, Folding
SCE-LF18 Fixture, LED Light
SCE-LF18NO Fixture, LED Light w/o Outlet
SCE-BPEX18 Barrier Extension
SCE-LF24 Fixture, LED Light
SCE-LF24NO Fixture, LED Light w/o Outlet
SCE-SLMS700 LED w/ Motion 700 Lumens
SCE-SLOF700 LED Light w/On/Off Switch 700 Lumens
SCE-130518 Mechanical Interlock Cable Length 168 inch
SCE-BP6018 Plate, Barrier
SCE-130516 NextGen Gasket Bolt Pack
SCE-DF68N40 Dead Front, NextGen

Similar Part Numbers

SCE-N80C7818SS6 S.S. 2DR Enc. Center Bay - Both Side Open
SCE-N80C7824SS6 S.S. 2DR Enc. Center Bay - Both Side Open

Installation Information

- NextGen Free-Standing Center Bay
- Cable Interlock
- NextGen Free-Standing Barrier Plate Installation
- NextGen Free-Standing End Plate Installation
- LFMTGK Installation Instructions
- Sub-Plate Layout & Grounding for 3/8-16
- Design Considerations When Specifying Your Enclosure
- Center Channel Re-Install
- Dead Front NextGen Free-Standing 2 Door w/Center Post