Saginaw Control & Engineering
95 Midland Road Saginaw, MI 48638-5770
Phone: 989/799-6871 Fax: 989/799-4524
sce@saginawcontrol.com

SCE-N68EXD4018



Product Specifications:

Part Number: SCE-N68EXD4018
Description: Both sides Solid- Provisions for EXD
Height: 68.00"
Width: 40.25"
Depth: 18.00"
Catalog Page: 162
Est. Ship Weight: 363 lbs

Construction

- Provisions for external disconnect.
- .104 carbon steel.
- Seams continuously welded and ground smooth.
- Flange trough collar around all sides of door opening.
- Body stiffeners in large enclosures for extra rigidity.
- Heavy duty lifting eyes anchor into reinforced top.
- Concealed hinges.
- Black zinc die cast coinproof/padlocking handle on door.
- 3-point latching mechanism.
- End of latch rods have ramp shoes for easier door closing.
- Panel supports.
- Pour-in-place oil & water resistant gasket.
- Optional panels mount to collar studs.
- Ground stud on door and body.
- Provisions for light kit.
- Holes plug provided to seal holes in bottom of enclosure.
- Enclosures include provisions for system expansion.

Application

Designed to house a variety of electrical and electronic controls and instruments, and most standard type disconnects. Provides protection from dust, dirt, water and oil. Provisions for external disconnect.

Finish

SCE-09 Gray powder coated inside and out. Optional subpanels powder coated white or galvanized.

Industry Standards - (IS4)

- NEMA: Type 3R, 4, 12 and Type 13
- UL: Listed Type 3R, 4 and 12
- CSA: Type 3R, 4 and 12
- IEC: IEC 60529
- IP: IP 66

Optional Accessories

SCE-NEXD18 External disconnect 30/200 AMP
SCE-NEXDMLK Interlock Kit 30 to 600 Amp (NEXD & NEXR)
SCE-N68P40 Subpanel, Bent
SCE-N68P40GALV Subpanel, Galvanized
SCE-NEXD18A6 External disconnect 400/600 AMP
SCE-DF68N40 Dead Front, NextGen
SCE-NEXR18 Rotary External disconnect 30 To 200 AMP

Similar Part Numbers

SCE-N68EXD2818 Both sides Solid- Provisions for EXD
SCE-N68EXD3418 Both sides Solid- Provisions for EXD
SCE-N80EXD4018 Both sides Solid- Provisions for EXD
SCE-N80EXD4024 Both sides Solid- Provisions for EXD

Installation Information

- NextGen Free-Standing Enclosures
- NextGen Mechanical Interlock Kit Installation
- NextGen External Disconnect Installation
- Cable Interlock for RXS Enclosures